University of Groningen

Generalized Multiscale Finite Element Methods for problems in perforated heterogeneous domains

Chung, Eric T.; Efendiev, Yalchin; Li, Guanglian; Vasilyeva, Maria

Published in:
Applicable Analysis

DOI:
[10.1080/00036811.2015.1040988](https://doi.org/10.1080/00036811.2015.1040988)

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version
Publisher's PDF, also known as Version of record

Publication date:
2016

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

Chung, E. T., Efendiev, Y., Li, G., & Vasilyeva, M. (2016). Generalized Multiscale Finite Element Methods for problems in perforated heterogeneous domains. *Applicable Analysis*, 95(10), 2254-2279.
<https://doi.org/10.1080/00036811.2015.1040988>

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Generalized multiscale finite element methods for problems in perforated heterogeneous domains

Eric T. Chung, Yalchin Efendiev, Guanglian Li & Maria Vasilyeva

To cite this article: Eric T. Chung, Yalchin Efendiev, Guanglian Li & Maria Vasilyeva (2016) Generalized multiscale finite element methods for problems in perforated heterogeneous domains, *Applicable Analysis*, 95:10, 2254-2279, DOI: [10.1080/00036811.2015.1040988](https://doi.org/10.1080/00036811.2015.1040988)

To link to this article: <https://doi.org/10.1080/00036811.2015.1040988>

Published online: 08 Jun 2015.

Submit your article to this journal [↗](#)

Article views: 158

View related articles [↗](#)

View Crossmark data [↗](#)

Citing articles: 15 View citing articles [↗](#)

Generalized multiscale finite element methods for problems in perforated heterogeneous domains

Eric T. Chung^a, Yalchin Efendiev^{bc*}, Guanglian Li^d and Maria Vasilyeva^{ef}

^aDepartment of Mathematics, The Chinese University of Hong Kong (CUHK), Hong Kong SAR, China; ^bDepartment of Mathematics & Institute for Scientific Computation (ISC), Texas A&M University, College Station, TX, USA; ^cCenter for Numerical Porous Media (NumPor), King Abdullah University of Science and Technology (KAUST), Thuwal 23955-6900, Kingdom of Saudi Arabia; ^dDepartment of Mathematics, Texas A&M University, College Station, TX 77843-3368, USA; ^eDepartment of Computational Technologies, Institute of Mathematics and Informatics, North-Eastern Federal University, Yakutsk, Republic of Sakha (Yakutia) 677980, Russia; ^fInstitute for Scientific Computation, Texas A&M University, College Station, TX 77843-3368, USA

Communicated by M. Jurak

(Received 5 January 2015; accepted 11 April 2015)

Complex processes in perforated domains occur in many real-world applications. These problems are typically characterized by physical processes in domains with multiple scales. Moreover, these problems are intrinsically multiscale and their discretizations can yield very large linear or nonlinear systems. In this paper, we investigate multiscale approaches that attempt to solve such problems on a coarse grid by constructing multiscale basis functions in each coarse grid, where the coarse grid can contain many perforations. In particular, we are interested in cases when there is no scale separation and the perforations can have different sizes. In this regard, we mention some earlier pioneering works, where the authors develop multiscale finite element methods. In our paper, we follow Generalized Multiscale Finite Element Method (GMsFEM) and develop a multiscale procedure where we identify multiscale basis functions in each coarse block using snapshot space and local spectral problems. We show that with a few basis functions in each coarse block, one can approximate the solution, where each coarse block can contain many small inclusions. We apply our general concept to (1) Laplace equation in perforated domains; (2) elasticity equation in perforated domains; and (3) Stokes equations in perforated domains. Numerical results are presented for these problems using two types of heterogeneous perforated domains. The analysis of the proposed methods will be presented elsewhere.

Keywords: perforated domain; multiscale finite element method; model reduction; Laplace equation; Stokes equations; elasticity equation

AMS Subject Classifications: 65M60; 74S05; 76M10

*Corresponding author. Email: efendiev@math.tamu.edu

1. Introduction

Among multiscale problems, the problems in perforated domains are of great interest to many applications. The main characteristics of these problems is that the underlying processes occur in multiscale domains where the geometry of the domain has multiple scales, e.g. domain outside inclusions (see Figure 1). There are many important applications for processes in perforated domains. For example, fluid flow in porous media, diffusion in perforated domains, mechanical processes in hollow materials, and so on. Typically, it is a combination of a physical process and a heterogeneous media that gives rise to problems in perforated domains.

The problems in perforated domains are of multiscale nature. The solution techniques for these problems require high resolution. In particular, the discretization needs to honor the irregular boundaries of perforations. This gives rise to a fine-scale problems with many degrees of freedom which can be very expensive to solve. In this paper, our goal is to develop coarse-grid approaches where the coarse grids do not have to align with perforations and the perforated domains do not need to have a scale separation. Our objective is to construct a low-dimensional approximate model for solving fine-scale problems.

When the perforated domains have some scale separation, there are numerous works which include the works on the homogenization and asymptotic expansion in periodic perforated domains.[1–3] Recently, a novel method of mesoscale asymptotic approximation for Laplace operator is introduced [4] for the cases with a large number of perforations. The multiscale analysis of the perforated domain has been conducted using heterogeneous multiscale finite element method (HMMFEM) and Multiscale Finite Element Method (MsFEM).[1,5,6] The authors in [6–8] have extended multiscale finite element methods to arbitrary-perforated domains and presented novel numerical approaches using Crouzeix–Raviart coupling of multiscale finite element basis. Their approach allows perforations to intersect the boundaries of coarse-grid blocks. In their approach, the authors use oversampling technique and weak coupling via Crouzeix–Raviart to avoid directly imposing boundary conditions for the basis functions. The latter can be difficult for multiscale basis function construction in perforated domains. We would like to mention that in [9], the authors consider the Laplace equation in perforated domain and use a local orthogonal decomposition (LOD) method to improve subgrid errors. In our paper, we also follow this general concept and avoid constructing boundary conditions for multiscale basis functions and construct them via local spectral decomposition. Our approach follows a Generalized Multiscale Finite Element Method (GMsFEM) [10] in constructing multiscale basis functions which we discuss next.

GMsFEM is a general multiscale procedure where multiscale basis functions in each coarse grid are constructed and it is designed for many applications.[11–13] In the GMsFEM framework, one divides the computations into two stages, i.e. the offline stage and the online stage. In the offline stage, a reduced dimensional space is constructed, and it is then used in the online stage to construct multiscale basis functions. These multiscale basis functions can be reused for any input parameter to solve the problem on a coarse grid. The main idea behind the construction of the offline and online spaces is to design appropriate snapshot spaces and determine an appropriate local spectral problem to select important modes in the snapshot space. In [10], several general strategies for designing the local spectral procedures have been proposed. To apply GMsFEM for problems in perforated domains, one needs a novel way to construct the snapshot space and local spectral problem. In

earlier works, [14,15] heterogeneous problems in “homogeneous” single-connected domains have been studied. The main challenge is to take into account the domain heterogeneities when constructing multiscale basis functions. Compared to problems in heterogeneous media without perforated regions, we impose boundary conditions on perforations. We generate local snapshot space using harmonic extensions of appropriately chosen large set of boundary conditions. Local spectral problems are used to select dominant modes. We also discuss the use of randomized snapshots [16] that allow calculating a few snapshot vectors. The latter is important in reducing the computational cost.

The above procedure is formulated for a general problem in perforated media. In this paper, we apply it to three different problems that arise in many applications. These include: (1) Laplace equation in perforated domain; (2) elasticity equation in perforated domain; and (3) Stokes equations in perforated domain. We show that our general concept can be applied to all these problems. We consider several numerical examples using two sets of perforated domains. One domain contains several large inclusions (with the sizes comparable to the coarse-grid sizes) and the other domain contains small inclusions (with the sizes much smaller than the size of the domain). We solve the above three PDEs in these two sets of domains and compare the multiscale solutions with the fine-grid solutions. Our preliminary numerical results demonstrate a fast convergence of the proposed GMsFEM approaches. In particular, we show that one can achieve a good accuracy with a very few degrees of freedom, especially for Laplace and elasticity problems. We discuss it in our numerical results.

The rest of the paper is organized as follows. In Section 2, we present preliminaries on the problems in perforated domains and the GMsFEM framework. The construction of the coarse spaces for the GMsFEM is discussed in Section 3. In Section 4, numerical results for several representative examples are presented. Finally, we conclude our paper with some remarks in Section 5.

2. Preliminaries

In this section, we first present the underlying problem and the corresponding fine-scale discretization. Then, we discuss the multiscale strategy of solving this problem. We consider

$$\mathcal{L}^\epsilon(u) = f \quad \text{in } \Omega^\epsilon, \quad (1)$$

$$u = 0 \text{ or } \frac{\partial u}{\partial n} = 0, \quad \text{on } \partial\Omega^\epsilon \cap \partial\mathcal{B}^\epsilon, \quad (2)$$

$$u = g, \quad \text{on } \partial\Omega \cap \partial\Omega^\epsilon. \quad (3)$$

Here, $\Omega \subset \mathbb{R}^d$ ($d = 2, 3$) is a bounded domain covered by inactive cells (for Stokes flow and Darcy flow) or active cells (for elasticity problem) $\mathcal{B}^\epsilon$. We call active cells where the underlying problem is solved, while inactive cells are being the rest of the region. Suppose the distance between inactive cells (or active cells) is at most ϵ and we use ϵ scripts to denote the perforated domains. Denote the remaining part as Ω^ϵ , i.e. $\Omega^\epsilon = \Omega \setminus \mathcal{B}^\epsilon$. See Figure 1 for an illustration of the perforated domain. $\mathcal{L}^\epsilon$ denotes a linear differential operator, e.g. $\mathcal{L}^\epsilon(u) = -\Delta u$ for Darcy flow. n is the unit outward normal to the boundary and $f \in F(\Omega^\epsilon)$ and $g \in G(\Omega^\epsilon)$ denote functions with a suitable regularity. Note that ϵ is used to denote heterogeneous domains, even though we do not assume periodicity or scale separation.

Figure 1. Illustration of a perforated domain.

To simplify the notation, we denote by $V(\Omega^\epsilon)$ the appropriate solution space, and

$$V_0(\Omega^\epsilon) = \{v \in V(\Omega^\epsilon), v = 0 \text{ on } \partial\Omega^\epsilon\}.$$

The variational formulation of Problem (1) is to find $u \in V(\Omega^\epsilon)$ such that

$$\langle \mathcal{L}^\epsilon(u), v \rangle_{\Omega^\epsilon} = \langle f, v \rangle_{\Omega^\epsilon} \quad \text{for all } v \in V_0(\Omega^\epsilon),$$

$\langle \cdot, \cdot \rangle_{\Omega^\epsilon}$ denotes a specific inner product over Ω^ϵ for either scalar functions or vector functions.

In the following, we give some specific examples for the above abstract notations.

- For the Laplace operator with homogeneous Dirichlet boundary conditions on $\partial\Omega^\epsilon$, we have

$$\mathcal{L}^\epsilon(u) = -\Delta u, \quad (4)$$

and $V(\Omega^\epsilon) = H_0^1(\Omega^\epsilon)$, $\langle \mathcal{L}^\epsilon(u), v \rangle_{\Omega^\epsilon} = \langle \nabla u, \nabla v \rangle_{\Omega^\epsilon}$.

- For the elasticity operator with a homogeneous Dirichlet boundary condition on $\partial\Omega^\epsilon$, we let $u \in (H^1(\Omega^\epsilon))^d$ be the displacement field. The strain tensor $\epsilon(u) \in (L^2(\Omega^\epsilon))^{d \times d}$ is defined by

$$\epsilon(u) = \frac{1}{2} (\nabla u + \nabla u^T).$$

In this paper, we assume the medium is isotropic. Thus, the stress tensor $\sigma(u) \in (L^2(\Omega^\epsilon))^{d \times d}$ relates to the strain tensor $\epsilon(u)$ in the following way

$$\sigma(u) = 2\mu\epsilon + \lambda \nabla \cdot u \, I,$$

where $\lambda > 0$ and $\mu > 0$ are the Lamé coefficients. We have

$$\mathcal{L}^\epsilon(u) = -\nabla \cdot \sigma, \quad (5)$$

where $V(\Omega^\epsilon) = (H_0^1(\Omega^\epsilon))^d$ and $\langle \mathcal{L}^\epsilon(u), v \rangle_{\Omega^\epsilon} = 2\mu \langle \epsilon(u), \epsilon(v) \rangle_{\Omega^\epsilon} + \lambda \langle \nabla \cdot u, \nabla \cdot v \rangle_{\Omega^\epsilon}$.

- For Stokes equations, we have

$$\mathcal{L}^\epsilon(u, p) = \begin{pmatrix} \nabla p - \mu \Delta u \\ \nabla \cdot u \end{pmatrix}, \quad (6)$$

where μ is the viscosity, p is the fluid pressure, u represents the velocity, $V(\Omega^\epsilon) = (H_0^1(\Omega^\epsilon))^d \times L_0^2(\Omega^\epsilon)$, and

$$\langle \mathcal{L}^\epsilon(u, p), (v, q) \rangle_{\Omega^\epsilon} = \begin{pmatrix} \langle \nabla u, \nabla v \rangle_{\Omega^\epsilon} - \langle \nabla \cdot v, p \rangle_{\Omega^\epsilon} \\ \langle \nabla \cdot u, q \rangle_{\Omega^\epsilon} \end{pmatrix}.$$

We recall that $L_0^2(\Omega^\epsilon)$ contains functions in $L^2(\Omega^\epsilon)$ with zero average in Ω^ϵ .

We now turn our attention to a numerical approximation of the variational problem above. Due to the nature of this multiscale problem, we consider the framework of multiscale finite element method.[14] The idea is computing the solution on a coarse grid instead of calculating on the fine grid directly. In the following, we introduce the necessary concepts and notations.

Let $\mathcal{T}_H$ be a coarse-grid partition of the domain Ω^ϵ and $\mathcal{T}_h$ be a conforming fine triangulation of Ω^ϵ . We assume that $\mathcal{T}_h$ is a refinement of $\mathcal{T}_H$, where h and H represent the fine and coarse mesh sizes, respectively. Typically, we assume that $0 < h \ll H < 1$, and that the fine-scale mesh $\mathcal{T}_h$ is sufficiently fine to fully resolve the small-scale information of the domain while $\mathcal{T}_H$ is a coarse mesh containing many fine-scale features. On the triangulation $\mathcal{T}_h$, we introduce the following finite element spaces

$$V_h := \{v \in V(\Omega^\epsilon) | v|_K \in (P^k(K))^l \text{ for all } K \in \mathcal{T}_h\},$$

where $k = 1, 2$, P^k denotes the polynomial approximation space, and $l = 1, d$ indicates either a scalar or a vector.

In this paper, Generalized Multiscale Finite Element Method (GMsFEM) framework is applied. In the GMsFEM methodology, one divides the computations into offline and online computations. The offline computations are based on a preliminary dimension reduction of the fine-grid finite element spaces (that may include dealing with additionally important physical parameters, uncertainties and nonlinearities), and then the online procedure (if needed) is applied to construct a reduced order model. We start by constructing offline spaces.

We construct the coarse function space

$$V_{\text{off}} := \text{span}\{\phi_i\}_{i=1}^N,$$

where N is the number of coarse basis functions. Each ϕ_i is supported in some coarse neighborhood w_l (see Figures 2 and 3 for an illustration of coarse neighborhoods).

The overall performance of the resulting GMsFEM depends on the approximation properties of the resulting offline and online coarse spaces directly. Usually, a spectral problem is involved for a good approximation of the local solution space. In this paper, we focus on the construction of the offline spaces since the differential operators $\mathcal{L}^\epsilon$ is parameter independent and linear.

The GMsFEM seeks an approximation $u_0 \in V^{\text{off}}$, which satisfies the coarse-scale offline formulation,

$$\langle \mathcal{L}^\epsilon(u_0), v \rangle_{\Omega^\epsilon} = (f, v)_{\Omega^\epsilon} \quad \text{for all } v \in V^{\text{off}}. \quad (7)$$

Recall that the definitions of the bilinear forms $\langle \mathcal{L}^\epsilon(u_0), v \rangle_{\Omega^\epsilon}$ are defined above, and $(f, v)_{\Omega^\epsilon}$ is the L^2 inner product.

We can interpret the method in the following way using matrix representations. Recall that the coarse basis functions $\{\phi_i\}_{i=1}^N$ are defined on the fine grid, and can be represented by the fine-grid basis functions. Specifically, we introduce the following matrices:

$$R_0^T = [\phi_1, \dots, \phi_N],$$

where we identify the basis ϕ_i with their coefficient vectors on the fine-grid basis. Then, the matrix analog of the system (7) can be equivalently written as

$$R_0 \langle \mathcal{L}^\epsilon(\eta_i), \eta_j \rangle_{\Omega^\epsilon} R_0^T u_0 = R_0 F, \quad (8)$$

where F is the fine-grid discretization of f and $\eta_1, \dots, \eta_n$ denote the fine-scale basis. Here, n denotes the number of fine-scale basis. Further, once we solve the coarse system (8), we can recover the fine-scale solution by $R_0^T u_0$. In other words, R_0^T can be regarded as the transformation (also known as interpolation or downscaling) matrix from the space V_{off} to the space V_h .

The accuracy of the GMsFEM relies on the coarse basis functions $\{\phi_i\}$. We shall present the construction of suitable basis functions for the differential operators in Section 3.

3. Local basis functions

In this section, we describe the offline–online computational procedure, and elaborate on some applicable choices for the associated bilinear forms to be used in the coarse space construction. Below, we offer a general outline for the procedure.

(1) Offline computations:

- 1.0. Coarse-grid generation.
- 1.1. Construction of a snapshot space that will be used to compute an offline space.
- 1.2. Construction of a small dimensional offline space by performing dimension reduction in the space of local snapshots.

(2) Online computations:

- 2.1. For each input parameter, compute multiscale basis functions (it is needed for parameter-dependent or nonlinear problems).
- 2.2. Solve a coarse-grid problem for a forcing term and boundary condition.
- 2.3. Iterative solvers, if needed.

In the offline computation, we first construct a snapshot space $V_{\text{snap}}^{\omega_i^+}$ or $V_{\text{snap}}^{\omega_i}$, depending on the choice of domain to generate the snapshot space, where ω_i^+ is an oversampled region that contains a coarse neighborhood ω_i . Construction of the snapshot space involves solving the local problems for various choices of input parameters, and we describe the details below.

3.1. Snapshot space

First, we introduce the concept of a coarse neighborhood, as before. An illustration of a coarse neighborhood is shown in Figures 2 and 3, respectively, for Darcy and Stokes equations. The snapshot space is composed of a harmonic extension of fine-grid functions defined on $\omega_i \setminus \mathcal{B}^\epsilon$. The local snapshots satisfy boundary conditions imposed on $\partial \mathcal{B}^\epsilon$. More precisely, for each fine-grid function $\delta_l^h(x)$ on $\partial \omega_i$, we are solving a local problem to obtain one basis. Here, $\delta_l^h(x)$ is defined as $\delta_l^h(x) = \delta_{l,k}$, $\forall l, k \in J_h(\omega_i)$, $\delta_l^h(x) = 0$ on $\partial \mathcal{B}^\epsilon$, where $J_h(\omega_i)$ denotes the fine-grid boundary node on $\partial \omega_i \setminus \mathcal{B}^\epsilon$.

For a parameter-independent problem, we solve

$$\mathcal{L}^\epsilon(\psi_l^{\omega_i, \text{snap}}) = 0 \text{ in } \omega_i \setminus \mathcal{B}^\epsilon \quad (9)$$

Figure 2. Illustration of a coarse neighborhood and oversampled domain.

Figure 3. Illustration of a coarse neighborhood for Stokes equations.

subject to the boundary condition $\psi_l^{\text{snap}} = \delta_l^h(x)$ on $\partial\omega_i$ and $\psi_l^{\text{snap}} = 0$ on $\partial\mathcal{B}^\epsilon \cap \bar{\omega}_i$. Note that for the differential operator with Neumann boundary conditions $\frac{\partial u}{\partial n} = 0$, we will use Neumann boundary conditions instead for the local problems proposed above. Throughout the paper, we use the same notations to denote discrete and continuous variables whenever there is no confusion. All local problems are solved on a fine grid.

We denote the space composed of $\psi_l^{\omega_i, \text{snap}}$ as

$$V_{\text{snap}}^{\omega_i} = \text{span} \{ \psi_l^{\omega_i, \text{snap}} : 1 \leq l \leq M_i^{\text{snap}} \},$$

for each coarse neighborhood ω_i , where M_i^{snap} denotes the number of snapshots in the region ω_i . We emphasize that an oversampling strategy (refer to Figure 2 for an illustration of oversampling domain) can be applied for the construction of snapshots to obtain a higher accuracy.[17]

Remark 3.1 The snapshots described above are referred to as the harmonic basis in Section 4.

Remark 3.2 One can also use all the fine-grid functions as snapshots. These snapshots are referred to as the spectral basis in Section 4.

3.2. Offline space

This section is devoted to the construction of the offline space via a spectral decomposition. In order to construct the offline space V_{off} , we perform a dimension reduction in the snapshot space using an auxiliary spectral decomposition. The main objective is to seek a subspace of the snapshot space such that it can approximate any element of the snapshot space in an appropriate sense defined via auxiliary bilinear forms. We will consider the following eigenvalue problems in the space of snapshots:

$$A^{\omega_i, \text{off}} \Psi_k^{\omega_i, \text{off}} = \lambda_k^{\omega_i, \text{off}} S^{\omega_i, \text{off}} \Psi_k^{\omega_i, \text{off}}. \quad (10)$$

The definitions of $A^{\omega_i, \text{off}}$ and $S^{\omega_i, \text{off}}$ for Laplace, elasticity and Stokes equations are, respectively, listed below. To generate the offline space, we then choose the smallest M_i^{off} eigenvalues from Equation (10) and form the corresponding eigenvectors in the respective snapshot spaces by setting $\psi_k^{\omega_i, \text{off}} = \sum_j \Psi_{kj}^{\omega_i, \text{off}} \psi_j^{\omega_i, \text{snap}}$, for $k = 1, \dots, M_i^{\text{off}}$, where $\Psi_{kj}^{\omega_i, \text{off}}$ are the coordinates of the vector $\Psi_k^{\omega_i, \text{off}}$. The offline space is defined as the span of $\chi_i \psi_k^{\omega_i, \text{off}}$, where χ_i is the usual nodal basis function for the node i . We then create the offline matrices

$$R_{\text{off}}^{\omega_i} = \begin{bmatrix} \chi_i \psi_1^{\omega_i, \text{off}}, \dots, \chi_i \psi_{M_i^{\text{off}}}^{\omega_i, \text{off}} \end{bmatrix}.$$

- For Laplace operator (4),

$$\begin{aligned} A^{\omega_i, \text{off}} &= [a_{mn}^{\text{off}}] = \int_{\omega_i \setminus \mathcal{B}^\epsilon} \nabla \psi_m^{\omega_i, \text{snap}} \cdot \nabla \psi_n^{\omega_i, \text{snap}}, \text{ and} \\ S^{\omega_i, \text{off}} &= [s_{mn}^{\text{off}}] = \int_{\omega_i \setminus \mathcal{B}^\epsilon} \psi_m^{\omega_i, \text{snap}} \psi_n^{\omega_i, \text{snap}}. \end{aligned} \quad (11)$$

- For elasticity operator (5),

$$\begin{aligned} A^{\omega_i, \text{off}} &= [a_{mn}^{\text{off}}] = \int_{\omega_i \setminus \mathcal{B}^\epsilon} \left(2\mu \boldsymbol{\varepsilon}(\psi_m^{\omega_i, \text{snap}}) : \boldsymbol{\varepsilon}(\psi_n^{\omega_i, \text{snap}}) \right. \\ &\quad \left. + \lambda \nabla \cdot \psi_m^{\omega_i, \text{snap}} \nabla \cdot \psi_n^{\omega_i, \text{snap}} \right), \text{ and} \\ S^{\omega_i, \text{off}} &= [s_{mn}^{\text{off}}] = \int_{\omega_i \setminus \mathcal{B}^\epsilon} (\lambda + 2\mu) \psi_m^{\omega_i, \text{snap}} \cdot \psi_n^{\omega_i, \text{snap}}. \end{aligned} \quad (12)$$

- For Stokes operator (6),

$$\begin{aligned} A^{\omega_i, \text{off}} &= [a_{mn}^{\text{off}}] = \int_{\omega_i \setminus \mathcal{B}^\epsilon} \nabla \psi_m^{\omega_i, \text{snap}} : \nabla \psi_n^{\omega_i, \text{snap}}, \text{ and} \\ S^{\omega_i, \text{off}} &= [s_{mn}^{\text{off}}] = \int_{\omega_i \setminus \mathcal{B}^\epsilon} \psi_m^{\omega_i, \text{snap}} \cdot \psi_n^{\omega_i, \text{snap}}. \end{aligned} \quad (13)$$

Note that for the Stokes operator, multiscale spaces are constructed for velocity field only in this section. For elasticity equations, we use P^1 to solve the fine-scale problem. Here, we do not consider the incompressible limit for the elasticity equations that will require a different fine-grid discretization.

In the following section, we will show the enrichment of the pressure space as well.

We remark that some adaptive procedures for choosing the offline basis are proposed and analyzed in [18,19]. In our future work, we plan to present an analysis of the method which can guide us in choosing the local spectral problems.

3.3. An enrichment of pressure space for Stokes equation

For the approximation of the Stokes Equation (6), an enrichment of the pressure space is needed. In this section, we present our approach of enriching the pressure space. For the fine-scale element, we apply Crouzeix–Raviart element for the velocity space and piecewise constant element for the pressure space as shown in Figure 4. In this figure, we denote the coarse neighborhood around the interior coarse block ω . The coarse block is denoted as K in Figure 5.

Suppose we have obtained the local velocity snapshot space over coarse neighborhood ω_i from Section 3.2, $\Psi_{\text{off}}^{\omega_i} = \left[\chi_i \psi_1^{\omega_i, \text{off}}, \dots, \chi_i \psi_{M_i^{\text{off}}}^{\omega_i, \text{off}} \right]$. Then the velocity basis is calculated by multiplying the corresponding nodal basis χ_i . Denote V_{off} as the space spanned by the velocity basis, then $V_{\text{off}} = \text{span} \left\{ \bigcup_{i=1}^{N_c} \bigcup_{j=1}^{M_i^{\text{off}}} \chi_i \psi_j^{\omega_i, \text{off}} \right\}$, where N_c denotes the number of interior coarse nodes. In each coarse block K , to guarantee that $\text{div} V_{\text{off}} \subset W_{\text{off}}$, [20] where W_{off} denotes piecewise constant space over the coarse mesh $\mathcal{T}_H$ for the pressure, we solve the following problems

$$\begin{aligned} -\Delta \tilde{\psi}_j + \nabla \tilde{r}_j &= 0 \text{ in } K, \\ \text{div } \tilde{\psi}_j &= \tilde{c} \text{ in } K, \\ \tilde{\psi}_j &= \chi_i \psi_j^{\omega_i, \text{off}} \text{ on } \partial K. \end{aligned}$$

and replace $\chi_i \psi_j^{\omega_i, \text{off}}$ by $\tilde{\psi}_j$. In the above system, $\tilde{c} = \frac{1}{|K|} \int_{\partial K} \chi_i \psi_j^{\omega_i, \text{off}} \cdot n \, ds$ and χ_i denotes the nodal basis over the coarse mesh on coarse node i . χ_i plays the role of partition

Figure 4. Fine mesh, coarse mesh and coarse neighborhood.

Figure 5. Fine mesh, coarse mesh and coarse block.

of the unity function to ensure the continuity of the global basis. As pointed in [20], in order to obtain an accurate approximation of the velocity as well as the pressure solution, an enrichment of the pressure space is needed.

We will enrich the pressure space by solving the local problems

$$\begin{aligned} -\Delta \phi_j^{\omega_i, \text{snap}} &= 0 \quad \text{in } \omega_i \setminus \mathcal{B}^\epsilon, \\ \phi_j^{\omega_i, \text{snap}} &= \delta_j, \quad \text{on } \partial \omega_i, \\ \frac{\partial}{\partial n} \phi_j^{\omega_i, \text{snap}} &= 0, \quad \text{on } \partial \mathcal{B}^\epsilon \end{aligned}$$

and we denote the pressure snapshot space as $W_{\text{snap}}^{\omega_i}$, i.e.

$$W_{\text{snap}}^{\omega_i} = [\phi_1^{\omega_i, \text{snap}}, \dots, \phi_{N_b}^{\omega_i, \text{snap}}],$$

where N_b denotes the number of nodes on boundary $\partial\omega_i \setminus \partial\mathcal{B}^\epsilon$. To compute the offline space, we perform a local spectral decomposition of $W_{\text{snap}}^{\omega_i}$ following Equation (11) and the resulting space is denoted by $W_{\text{off}}^{\omega_i}$.

Now, we are ready to enlarge the velocity space as well for each pressure basis in $W_{\text{off}}^{\omega_i}$ by the following local problem on ω_i ,

$$\begin{aligned} -\Delta \tilde{\psi}_j^{\omega_i, \text{off}} + \nabla \tilde{r}_j &= 0, \quad \text{in } \omega_i \setminus \mathcal{B}^\epsilon, \\ \text{div } \tilde{\psi}_j^{\omega_i, \text{off}} &= \phi_j^{\omega_i, \text{off}} - \tilde{c}, \quad \text{in } \omega_i \setminus \mathcal{B}^\epsilon, \\ \tilde{\psi}_j^{\omega_i, \text{off}} &= 0 \text{ on } \partial\omega_i. \end{aligned}$$

where $\tilde{c} = \frac{1}{|K|} \int_K \phi_j^{\omega_i, \text{off}} \, ds$. We denote the obtained velocity space as $\tilde{V}_{\text{off}}^{\omega_i}$, i.e.

$$\tilde{V}_{\text{off}}^{\omega_i} = [\tilde{\psi}_1^{\omega_i, \text{off}}, \dots, \tilde{\psi}_{N_b}^{\omega_i, \text{off}}],$$

Therefore, the enriched local coarse offline space is $\Psi_{\text{off}}^{\omega_i} = \Psi_{\text{off}}^{\omega_i} \cup \tilde{V}_{\text{off}}^{\omega_i}$.

4. Numerical results

In this section, we present simulation results using the framework presented in Section 3 for Laplace equation, elasticity equations and Stokes equations, respectively. We set $\Omega = [0, 1] \times [0, 1]$ and use two types of perforated domains as illustrated in Figure 6, where the perforated regions $\mathcal{B}^\epsilon$ are circular. Later, we will consider another numerical example and emphasize the computational cost. Note that we have also use perforated regions of other shapes instead and obtained similar results. The computational domain is discretized coarsely using uniform triangulation as shown in the left of Figures 7 and 8, where the coarse mesh size $H = \frac{1}{5}$. Furthermore, nonuniform triangulation is used inside each coarse triangle element to obtain a finer discretization. Examples of this triangulation

Figure 6. Two heterogeneous perforated media used in the simulations.

Figure 7. Coarse-scale and fine-scale discretization corresponds to the heterogeneous medium on the left of Figure 6.

Figure 8. Coarse-scale and fine-scale discretization corresponds to the heterogeneous medium on the right of Figure 6.

are displayed on the right of Figures 7 and 8, where 2188 and 2364 nonuniform triangle elements are generated, respectively.

4.1. Laplace equation in perforated domain

First, we consider the Laplace operator (4) imposed with zero Dirichlet boundary condition on the holes $\partial\Omega^\epsilon \cap \partial\mathcal{B}^\epsilon$ and $u = 1$ on $\partial\Omega$, and $f = 0$.

Figure 9. Fine-scale and coarse-scale solution to the Laplace equation in the heterogeneous medium on the left of Figure 6. The dimension of the coarse space is 432.

Figure 10. Fine-scale and coarse-scale solution to the Laplace equation in the heterogeneous medium on the right of Figure 6. The dimension of the coarse space is 432.

The simulation results in perforated domains as shown in Figure 6 are illustrated in Figures 9 and 10, respectively. The multiscale solution is obtained in an offline space of dimension 432 (using 12 basis functions per coarse neighborhood) and the fine-scale reference solution is obtained in a space of dimension 1187. Compared the fine-scale solution on the left with the coarse-scale solution on the right of the figures, we observe that the GMsFEM can approximate the fine-scale solution accurately.

Besides, two types of snapshot spaces are applied in our simulations with the results shown in Tables 1 and 2. The first column of each table shows the number of basis in each

Table 1. Numerical tests for Laplace operator in heterogeneous medium shown on the left of Figure 6. Fine-scale problem dimension is 1187.

N_b	dim	Harmonic basis		Spectral basis	
		L^2	H^1	L^2	H^1
1	36	0.18	0.75	0.19	0.63
2	72	0.12	0.65	0.10	0.45
4	144	0.06	0.48	0.02	0.18
8	288	0.03	0.35	0.01	0.09
12	432	0.01	0.17	0.002	0.02
16	576	0.004	0.04	0.001	0.009

Table 2. Numerical tests for Laplace operator in heterogeneous medium shown on the right of Figure 6. Fine-scale problem dimension is 1269.

N_b	dim	Harmonic basis		Spectral basis	
		L^2	H^1	L^2	H^1
1	36	0.10	0.89	0.06	0.34
2	72	0.09	0.88	0.03	0.25
4	144	0.05	0.65	0.01	0.10
8	288	0.03	0.52	0.005	0.05
12	432	0.01	0.29	0.001	0.02
16	576	0.003	0.06	0.0006	0.009

coarse node (N_b). The dimensions of the offline spaces are given in the second column. The next two columns display the L^2 and H^1 relative errors for using harmonic extension basis, and the last two columns are relative errors for spectral basis. We can see that the L^2 and H^1 relative errors are 0.2 and 2%, respectively, when the dimension of the coarse space is 432. The results applying harmonic extension type of basis (Eqn. (9)) are listed in the last two columns. As displayed in Table 1, the L^2 and H^1 relative errors are 1 and 17%, respectively, when the dimension of the coarse space is 432.

Note that the GMsFEM gives a very good solution in both cases with only about 36% of unknown compared to the fine-scale solver. We also observe in Tables 1 and 2 that a decay in the errors as we increase the number of basis functions.

4.2. Elasticity equations in perforated domain

Next, we consider elasticity operator (5). We use zero displacements $u = 0$ on the holes, $u_x = 0, \sigma_y = 0$ on the left boundary, $\sigma_x = 0, u_y = 0$ on the bottom boundary and $\sigma_x = 0, \sigma_y = 0$ on the top and right boundaries. Here, $u = (u_x, u_y)$ and $\sigma = (\sigma_x, \sigma_y)$. The source term is defined by $f = (10^7, 10^7)$, the elastic modulus is given by $E = 10^9$, Poisson's ratio is $\nu = 0.22$, where

$$\mu = \frac{E}{2(1+\nu)}, \quad \lambda = \frac{E\nu}{(1+\nu)(1-2\nu)}.$$

The fine-scale solution and coarse-scale solution corresponding to different perforated domains in Figure 6 are presented in Figures 11 and 12. The fine-scale displacement is displayed on the left, while the coarse-scale displacement is displayed on the right. The multiscale solution is obtained in an offline space of dimension 864 (using 12 basis functions per coarse neighborhood for each component of the displacement) and the fine-scale reference solution is obtained in a space of dimension 2374. Comparing the fine-scale solution with the coarse-scale solution in Figures 11 and 12, we can observe a good accuracy.

Furthermore, the relative errors for different dimensions of coarse spaces with harmonic basis functions (Eqn. (9)) and spectral basis functions are shown in Tables 3 and 4, respectively. As displayed in Table 3, the L^2 and H^1 relative errors using harmonic basis are 3 and 14%, respectively, when the dimension of the coarse space is 1152 for the perforated domain shown in the left of Figure 6. In addition, for the same dimension of the coarse

Figure 11. The fine-scale and coarse-scale solutions of the elasticity equation correspond to the heterogeneous perforated domain shown on the left of Figure 6. The dimension of the fine-scale solution is 2374 and the dimension of the coarse space is 864.

Figure 12. The fine-scale and coarse-scale solutions of the elasticity equation correspond to the heterogeneous perforated domain shown on the right of Figure 6. The dimension of the fine-scale solution is 2538 and the dimension of the coarse space is 864.

space and the same domain, the L^2 and H^1 relative errors using spectral basis are 0.5% and 5%, respectively. Note that the dimension of the fine-scale solution is 2374. Thus, we see that the proposed GMsFEM gives accurate solutions. We also observe that GMsFEM gives more accurate solution when more basis are included in the offline space. We remark that the results (see Table 4) follow a similar pattern for the domain shown on the right of Figure 6.

4.3. Stokes equations in perforated domain

In our final example, we consider the Stokes operator (6) with zero velocity $u = (0, 0)$ on $\partial\Omega^\epsilon \cap \partial\mathcal{B}^\epsilon$ and $u = (1, 0)$ on $\partial\Omega$. For approximation of the Stokes problem, we use Crouzeix–Raviart elements for velocity and piecewise constants for pressure. To improve the accuracy, we have enriched pressure spaces and constructed associated velocity spaces as discussed before.

Table 3. Numerical tests for elasticity equations in heterogeneous medium shown on the left of Figure 6. The fine-scale problem dimension is 2374.

N_b	dim	Harmonic basis		Spectral basis	
		L^2	H^1	L^2	H^1
1	72	0.65	0.74	0.58	0.75
2	144	0.41	0.57	0.21	0.46
4	288	0.32	0.48	0.07	0.26
8	576	0.16	0.32	0.02	0.13
12	864	0.11	0.25	0.009	0.08
16	1152	0.03	0.14	0.005	0.05
20	1440	0.01	0.04	0.003	0.03

Table 4. Numerical tests for elasticity equations in heterogeneous medium shown on the right of Figure 6. The fine-scale problem dimension is 2538.

N_b	dim	Harmonic basis		Spectral basis	
		L^2	H^1	L^2	H^1
1	72	0.79	0.86	0.65	0.81
2	144	0.53	0.69	0.11	0.35
4	288	0.45	0.62	0.04	0.20
8	576	0.22	0.41	0.01	0.12
12	864	0.16	0.34	0.007	0.07
16	1152	0.06	0.20	0.003	0.05
20	1440	0.01	0.12	0.002	0.04

The numerical results corresponding to different perforated domains in Figure 6 are listed in Figures 13 and 14.

The L^2 relative errors for velocity and pressure in different perforated domains in Figure 6 are listed in Tables 5 and 6, respectively. We observe that the relative errors for velocity and pressure are 5% and 8%, respectively, when the dimension of the coarse space is 3920 for the perforated domain shown in the left of Figure 6. As more velocity basis (N_b^u) are taken in the construction of the offline space, the L^2 relative errors become smaller. In general, enriching pressure spaces and constructing associated velocity spaces (N_b^p) can significantly improve the accuracy. The results (see Table 6) for the perforated domain shown in the right of Figure 6 follow a similar pattern.

4.4. Discussion on computational cost

Next, we discuss the complexity of our approach. Assume that in each coarse grid, we have n_{off} basis functions. Furthermore, we assume that the number of coarse-grid blocks is n_{coarse} and the number of fine-grid blocks is n_{fine} . Then, the dimension of the coarse problem is $n_{\text{off}} \times n_{\text{coarse}}$ and the number of non-zero elements in the stiffness matrix is $n_{\text{off}}^2 \times n_{\text{coarse}}$.

Figure 13. The fine-scale and coarse-scale solutions of the pressure, x -component and y -component of the velocity correspond to the heterogeneous perforated domain shown on the left of Figure 6. The dimension of the fine-scale solution is 8956 and the dimension of the coarse space is 3920.

Figure 14. The fine-scale and coarse-scale solutions of the pressure, x -component and y -component of the velocity correspond to the heterogeneous perforated domain shown on the right of Figure 6. The dimension of the fine-scale solution is 9652 and the dimension of the coarse space is 3920.

Table 5. Numerical tests for Stokes operator in heterogeneous medium shown on the left of Figure 6. Fine-scale problem dimension is 8956.

N_b^p	dim	Velocity error L^2	Pressure error L^2
Number of velocity basis, $N_b^u = 4$			
1	830	0.58	0.54
2	980	0.33	0.22
Number of velocity basis, $N_b^u = 8$			
1	1510	0.44	0.56
2	1660	0.25	0.18
4	1960	0.15	0.14
Number of velocity basis, $N_b^u = 12$			
1	2190	0.36	0.60
2	2340	0.20	0.25
4	2640	0.17	0.12
8	3240	0.09	0.08
Number of velocity basis, $N_b^u = 16$			
1	2870	0.35	0.66
2	3020	0.20	0.31
4	3320	0.09	0.11
8	3920	0.05	0.08
12	4520	0.05	0.07

On the other hand, the dimension of the fine problem is $n_{\text{fine}} \times n_{\text{fine}}$ and the number of non-zero elements in the stiffness matrix is n_{fine} . Our proposed approaches are efficient if the local solution has sparsity “on average” (i.e. it has sparsity in most of the regions). This is the case, for example, when the media has a scale separation and then we can use only one multiscale basis function to achieve the accuracy of order of the inclusion sizes. In general, the n_{off} can be independent of n_{fine} (i.e. a few basis functions can approximate the fine-scale solution accurately no matter how fine is the fine grid). Moreover, one may need very fine grid around touching inclusions and other fine-scale complex feature that can be effectively localized (we did not study this in our paper). In general, we may need more basis functions in some regions. Assuming that the computational cost of solving a linear system with an iterative solve is $m^\gamma * n_{\text{iter}}$ (where m is the number of non-zero elements and n_{iter} is the number of iterations), then we can easily compare the computational compare the computational cost of solving coarse and fine problems. We note that for multiscale problems, the computational cost of solving linear systems depends on the contrast. For direct solvers, γ can be large compared to the iterative solvers.

In general, we can improve the accuracy of our approaches by choosing better boundary conditions for initial basis and using oversampling as well as using an adaptivity. We can also use parallel computations to calculate basis functions.

Table 6. Numerical tests for Stokes operator in heterogeneous medium shown on the right of Figure 6. Fine-scale problem dimension is 9652.

N_b^p	dim	Velocity error L^2	Pressure error L^2
Number of velocity basis, $N_b^u = 4$			
1	830	0.47	0.30
2	980	0.36	0.30
Number of velocity basis, $N_b^u = 8$			
1	1510	0.35	0.27
2	1660	0.26	0.33
4	1960	0.17	0.24
Number of velocity basis, $N_b^u = 12$			
1	2190	0.25	0.36
2	2340	0.18	0.24
4	2640	0.11	0.13
8	3240	0.08	0.09
Number of velocity basis, $N_b^u = 16$			
1	2870	0.22	0.45
2	3020	0.16	0.32
4	3320	0.09	0.19
8	3920	0.05	0.11
12	4520	0.05	0.11

Figure 15. Coarse and fine grids. Fine grid have 3809 vertices and 7222 cells.

Table 7. Numerical tests for Laplace operator. Fine-scale problem dimension is 3809.

N_b	dim	Harmonic basis		Spectral basis	
		L^2	H^1	L^2	H^1
1	36	0.20	0.75	0.20	0.62
2	72	0.14	0.67	0.10	0.44
4	144	0.07	0.51	0.02	0.18
8	288	0.04	0.36	0.01	0.09
12	432	0.02	0.20	0.002	0.02
16	576	0.01	0.14	0.001	0.01

Figure 16. The fine-scale and coarse-scale solutions of the pressure, x -component and y -component of the velocity correspond to the heterogeneous perforated domain shown on the left of Figure 15. The dimension of the fine-scale solution is 29358 and the dimension of the coarse space is 1960.

Table 8. Randomized GMsFEM algorithm.

<i>Input:</i>	Fine-grid size h , coarse-grid size H , oversampling size t , buffer number $p_{\text{bf}}^{\omega_i}$ for each ω_i , the number of local basis functions $k_{\text{nb}}^{\omega_i}$ for each ω_i ;
<i>Output:</i>	Coarse-scale solution u_H .
1.	Generate oversampling region for each coarse block: $\mathcal{T}^H$, $\mathcal{T}^h$, and ω_i^+ ;
2.	Generate $k_{\text{nb}}^{\omega_i} + p_{\text{bf}}^{\omega_i}$ random vectors r_l and obtain randomized snapshots in ω_i^+ ; Add a snapshot that represents the constant function on ω_i^+ ;
3.	Obtain $k_{\text{nb}}^{\omega_i}$ offline basis by a spectral decomposition restricted to the original region;
4.	Construct multiscale basis functions and solve it.

Table 9. Numerical tests for elasticity in heterogeneous media shown on the left of Figure 6. Randomized oversampling for GMsFEM.

N_b	Full snapshots		Randomized snapshots	
	L^2	H^1	L^2	H^1
Without oversampling, w_i				
	100%		39.7%	
1	0.572	0.753	0.764	0.853
2	0.217	0.466	0.592	0.742
4	0.071	0.261	0.317	0.529
8	0.023	0.136	0.173	0.386
12	0.009	0.079	0.101	0.286
16	0.005	0.054	0.055	0.214
With oversampling, $w_i^+ = w_i + 2$				
	100%		25.2%	
1	0.506	0.716	0.533	0.729
2	0.223	0.472	0.203	0.450
4	0.069	0.258	0.065	0.252
8	0.025	0.143	0.025	0.146
12	0.010	0.083	0.013	0.095
16	0.006	0.058	0.007	0.069

We remark that the proposed approaches are more effective when the local solution space has smaller dimension, e.g. problems with scale separation, closely packed inclusions, and so on. In this paper, our goal is to present a framework for GMsFEM in perforated domains. We do not discuss cases where one can greatly benefit from multiscale approaches. In particular, when the local region has small perforations that are close to each, it will require very fine mesh. On the other hand, multiscale effects in these problems are localized and one can represent the solution space with a fewer degrees of freedom. To illustrate this, we depict a geometry in Figure 15. In this geometry, we have modified the geometry presented

Table 10. Numerical tests for elasticity in heterogeneous media shown on the right of Figure 6. Randomized oversampling for GMsFEM.

N_b	Full snapshots		Randomized snapshots	
	L^2	H^1	L^2	H^1
Without oversampling, w_i				
	100%		39.2%	
1	0.692	0.822	0.858	0.908
2	0.116	0.351	0.673	0.798
4	0.039	0.207	0.510	0.678
8	0.016	0.128	0.358	0.551
12	0.007	0.078	0.204	0.418
16	0.003	0.055	0.132	0.334
With oversampling, $w_i^+ = w_i + 2$				
	100%		23.3%	
1	0.665	0.800	0.611	0.762
2	0.115	0.355	0.131	0.383
4	0.038	0.214	0.049	0.241
8	0.015	0.135	0.020	0.157
12	0.006	0.087	0.008	0.108
16	0.006	0.089	0.008	0.102

in Figure 4 by including additional small perforations near large ones. Because of proximity of these perforations, one needs to use very fine grid and, consequently, the fine-grid degrees of freedom is large in these coarse regions. On other hand, we observe from Table 7, one can achieve similar errors as before with a very few basis functions. For example, with only 8 multiscale velocity basis functions, the L^2 relative error is 4%. In this case, in the few regions with many small inclusions, we have about 390 fine-grid elements and the size of the (total) fine-scale problem size is 3809, while the size of the coarse-scale system is 288. Similarly, we have observed larger reduction in the computational cost for Stokes' equations when the geometry in Figure 15 is used. In particular, we can achieve 17% error with 1960 degrees of freedom (vs. 29358 fine-grid degrees of freedom). In Figure 16, we depict these two solutions. Thus, we can achieve a substantial speed-up for these problems. Moreover, using adaptivity [18,19] and online basis functions [21] (if successfully developed for these problems), we can improve the computational cost further.

4.5. Randomized snapshots for GMsFEM

In this subsection, we will investigate the oversampling randomized algorithm proposed in [16] (shown in Table 8). In this table, $k_{nb}^{\omega_i}$ denotes the number of offline basis we take at ω_i , $p_{bf}^{\omega_i}$ denotes the number of extra basis we generate at each coarse neighborhood ω_i . r_l denotes random fields used as boundary conditions. These fields consist of independent normal Gaussian random variables assigned each boundary node. The advantage of

this algorithm lies in the fact that a much fewer number of snapshot basis functions are calculated maintaining a good accuracy to the solution space concurrently. Besides, the oversampling strategy is used to reduce the mismatching effects of boundary conditions imposed artificially in the construction of snapshot basis functions. For the sake of brevity, the results for elasticity equation are shown only.

The simulation results are presented in Tables 9 and 10 for elasticity problem. The results without oversampling are shown on the top of each table, while those with the oversampling strategy are shown on the bottom part of each table. In our simulation, we set the oversampling size $t = 2$ (i.e. two extra fine-grid blocks are added to the original coarse region) and a buffer number $p_{\text{bf}}^{\omega_i} = 4$ for each coarse neighborhood ω_i , i.e. we will generate four more snapshot basis functions in each coarse neighborhood. In the numerical results, we report the fraction of the snapshots computed compared to all snapshot vectors. For the sake of completeness, we list the algorithm in Table 8.

Comparing the results on the left columns (using full snapshot space) of Tables 9 and 10 with those on the right columns that correspond to the randomized snapshots, we observe that the randomized algorithm provides a nearly similar results, particularly with oversampling strategy. This is consistent with our previous observations for heterogeneous problems. Oversampling avoids the oscillations on the boundary conditions due to the randomness. The effect of oversampling strategy is much more obvious for the randomized snapshot space.

5. Conclusion

In this paper, we develop a generalized multiscale finite element framework for problems in perforated domains. Our approach follows GMSFEM. The main contributions of this paper are the development of snapshot space and local spectral problems for solving problems in perforated domains with multiple scales and no scale separation. Our approaches differ from previously developed GMSFEM techniques for heterogeneous problems. In particular, the snapshot vectors and local eigenvalue problems need to be developed in a multiscale domain and take into account the boundaries that may be disconnected. We show that using GMSFEM framework, we can propose a unified framework for solving problems in perforated domains. In the paper, we discuss three applications: (1) Laplace equation in perforated domain; (2) elasticity equation in perforated domain; and (3) Stokes equations in perforated domain. We present some numerical results that show that one can efficiently solve these problems on a coarse grid using fewer degrees of freedom. We also discuss the use of randomized snapshots to reduce the offline computational cost associated with computing the snapshot space. In our future work, we plan to present analysis and design new more efficient coarse spaces based on the analysis.

Disclosure statement

No potential conflict of interest was reported by the authors.

Funding

YE's work is partially supported by the US Department of Energy Office of Science, Office of Advanced Scientific Computing Research, Applied Mathematics program under Award Number

DE-FG02-13ER26165 and the DoD Army ARO Project and NSF (DMS 0934837 and DMS 0811180). Eric Chung's research is partially supported by Hong Kong RGC General Research Fund (Project: 400813) and CUHK Faculty of Science Research Incentive Fund 2015-16.

References

- [1] Jikov VV, Kozlov SM, Oleinik OA. Homogenization of differential operators and integral functionals. Berlin: Springer-Verlag; 1991.
- [2] Cao L. Multiscale asymptotic expansion and finite element methods for the mixed boundary value problems of second order elliptic equation in perforated domains. *Numer. Math.* 2006;103:11–45.
- [3] Cao L, Zhang Y, Allegretto W, Lin Y. Multiscale asymptotic method for Maxwell's equations in composite material. *SIAM J. Numer. Anal.* 2010;47:4257–4289.
- [4] Maz'ya V, Movchan A, Nieves M. Green Kernels and meso-scale approximations in perforated domains. 2077, *Lecture notes in Mathematics*. Berlin: Springer; 2013.
- [5] Henning P, Ohlberger M. The heterogeneous multiscale finite element method for elliptic homogenization problems in perforated domains. *Numer. Math.* 2009;113:601–629.
- [6] Le Bris L, Legoll F, Lozinski A. An MsFEM type approach for perforated domains. *Forthcoming* 2014.
- [7] Le Bris C, Legoll F, Lozinski A. MsFEM à la Crouzeix-Raviart for highly oscillatory elliptic problems. *Chinese Ann. Math. Ser. B.* 2013;34:113–138.
- [8] Muljadi B, Narski J, Lozinski A, Degond P. Non-conforming multiscale finite element method for Stokes flows in heterogeneous media. Part I: methodologies and numerical experiments. *Forthcoming* 2014.
- [9] Brown D, Peterseim D. A multiscale method for porous microstructures, *ArXiv e-prints*. Also available as INS Preprint No. 1410; 2014.
- [10] Efendiev Y, Galvis J, Hou T. Generalized multiscale finite element methods. *J. Comput. Phys.* 2013;251:116–135.
- [11] Chung E, Efendiev Y, Leung WT. Generalized multiscale finite element method for wave propagation in heterogeneous media. *Multiscale Model. Simul.* 2014;12:1691–1721.
- [12] Chung E, Efendiev Y, Fu S. Generalized multiscale finite element method for elasticity equations. *Int. J. Geomath.* 2014;5:225–245.
- [13] Chung E, Efendiev Y, Lee C. Mixed generalized multiscale finite element methods and applications. *Multiscale Model. Simul.* 2015;13:338–366.
- [14] Hou T, Wu X. A multiscale finite element method for elliptic problems in composite materials and porous media. *J. Comput. Phys.* 1997;134:169–189.
- [15] Efendiev Y, Hou T, Wu X. Convergence of a nonconforming multiscale finite element method. *SIAM J. Numer. Anal.* 2000;37:888–910.
- [16] Calo V, Efendiev Y, Galvis J, Li G. Randomized oversampling for generalized multiscale finite element methods. *arXiv:1409.7114*. *Forthcoming*.
- [17] Efendiev Y, Galvis J, Li G, Presho M. Generalized multiscale finite element methods. Oversampling strategies. *Int. J. Multiscale Comput. Eng.* 2014;12:465–484.
- [18] Chung ET, Efendiev Y, Li G. An adaptive GMsFEM for high contrast flow problems. *J. Comput. Phys.* 2014;273:54–76.
- [19] Chung E, Efendiev Y, Leung WT. An adaptive generalized multiscale discontinuous Galerkin method (GMsDGM) for high-contrast flow problems. *arXiv:1409.3474*. *Forthcoming* 2014.
- [20] Galvis J, Li G, Shi K. A generalized multiscale finite element method for the Brinkman equation. *J. Comput. Appl. Math.* 2015;280:294–309.
- [21] Chung E, Efendiev Y, Leung WT. Residual-driven online generalized multiscale finite element methods. *arXiv:1501.04565*. *Forthcoming* 2015.