University of Groningen

Capacity Analysis of Sequential Zone Picking Systems

van der Gaast, J. P.; de Koster, M. B. M.; Adan, I. J. B. F.; Resing, J. A. C.

Published in:
Operations Research

DOI:
[10.1287/opre.2019.1885](https://doi.org/10.1287/opre.2019.1885)

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version
Publisher's PDF, also known as Version of record

Publication date:
2020

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

van der Gaast, J. P., de Koster, M. B. M., Adan, I. J. B. F., & Resing, J. A. C. (2020). Capacity Analysis of Sequential Zone Picking Systems. *Operations Research*, 68(1), 161-179.
<https://doi.org/10.1287/opre.2019.1885>

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Operations Research

Publication details, including instructions for authors and subscription information:
<http://pubsonline.informs.org>

Capacity Analysis of Sequential Zone Picking Systems

Jelmer P. van der Gaast, René B. M. de Koster, Ivo J. B. F. Adan, Jacques A. C. Resing

To cite this article:

Jelmer P. van der Gaast, René B. M. de Koster, Ivo J. B. F. Adan, Jacques A. C. Resing (2020) Capacity Analysis of Sequential Zone Picking Systems. Operations Research 68(1):161-179. <https://doi.org/10.1287/opre.2019.1885>

Full terms and conditions of use: <https://pubsonline.informs.org/Publications/Librarians-Portal/PubsOnLine-Terms-and-Conditions>

This article may be used only for the purposes of research, teaching, and/or private study. Commercial use or systematic downloading (by robots or other automatic processes) is prohibited without explicit Publisher approval, unless otherwise noted. For more information, contact permissions@informs.org.

The Publisher does not warrant or guarantee the article's accuracy, completeness, merchantability, fitness for a particular purpose, or non-infringement. Descriptions of, or references to, products or publications, or inclusion of an advertisement in this article, neither constitutes nor implies a guarantee, endorsement, or support of claims made of that product, publication, or service.

Copyright © 2019, INFORMS

Please scroll down for article—it is on subsequent pages

With 12,500 members from nearly 90 countries, INFORMS is the largest international association of operations research (O.R.) and analytics professionals and students. INFORMS provides unique networking and learning opportunities for individual professionals, and organizations of all types and sizes, to better understand and use O.R. and analytics tools and methods to transform strategic visions and achieve better outcomes.

For more information on INFORMS, its publications, membership, or meetings visit <http://www.informs.org>

Contextual Areas

Capacity Analysis of Sequential Zone Picking Systems

Jelmer P. van der Gaast,^a René B. M. de Koster,^b Ivo J. B. F. Adan,^c Jacques A. C. Resing^d

^aDepartment of Management Science, Fudan University, 200086 Shanghai, China; ^bDepartment of Management of Technology & Innovation, Erasmus Universiteit, 3062 PA Rotterdam, Netherlands; ^cDepartment of Industrial Engineering & Innovation Sciences, Technische Universiteit, 5612 AZ Eindhoven, Netherlands; ^dDepartment of Mathematics and Computer Science, Technische Universiteit, 5612 AZ Eindhoven, Netherlands

Contact: jpgaast@fudan.edu.cn, <https://orcid.org/0000-0001-7591-1552> (JPvdG); rkoster@rsm.nl, <https://orcid.org/0000-0002-1740-7822> (RBMdK); i.j.b.f.adan@tue.nl, <https://orcid.org/0000-0002-4493-6367> (IJBFA); j.a.c.resing@tue.nl (JACR)

Received: November 19, 2012

Revised: November 14, 2014; February 23, 2016; May 11, 2017; August 17, 2018

Accepted: November 25, 2018

Published Online in Articles in Advance: November 21, 2019

Subject Classifications: queues: networks, approximations; facilities/equipment planning: design, stochastic

Area of Review: Transportation

<https://doi.org/10.1287/opre.2019.1885>

Copyright: © 2019 INFORMS

Abstract. This paper develops a capacity model for sequential zone picking systems. These systems are popular internal transport and order-picking systems because of their scalability, flexibility, high-throughput ability, and fit for use for a wide range of products and order profiles. The major disadvantage of such systems is congestion and blocking under heavy use, leading to long order throughput times. To reduce blocking and congestion, most systems use the block-and-recirculate protocol to dynamically manage workload. In this paper, the various elements of the system, such as conveyor lanes and pick zones, are modeled as a multiclass block-and-recirculate queueing network with capacity constraints on subnetworks. Because of this blocking protocol, the stationary distribution of the queueing network is highly intractable. We propose an approximation method based on jump-over blocking. Multiclass jump-over queueing networks admit a product-form stationary distribution and can be efficiently evaluated by mean value analysis and Norton's theorem. This method can be applied during the design phase of sequential zone picking systems to determine the number of segments, number and length of zones, buffer capacities, and storage allocation of products to zones to meet performance targets. For a wide range of parameters, the results show that the relative error in the system throughput is typically less than 1% compared with simulation.

Supplemental Material: The online appendix is available at <https://doi.org/10.1287/opre.2019.1885>.

Keywords: warehousing • queueing theory • material handling • logistics

1. Introduction

Order picking, the process of picking products to fill customer orders, is the most labor-intensive warehouse activity and accounts for about 55% of warehouse total operating costs (Drury 1988). E-commerce and other recent trends in distribution and manufacturing have increased the importance of efficient order picking even more (Le-Duc and De Koster 2007). This paper focuses on the modeling and capacity analysis of sequential zone picking systems.

Zone picking is one of the most popular picker-to-parts order-picking method, in which the order-picking area is zoned. In each zone, an order picker is responsible for picking from a dedicated part of the warehouse (Petersen 2002, Gu et al. 2010). In practice, the zones are often connected by conveyors to reduce travel. The major advantages of zone picking systems are high-throughput ability, scalability, and flexibility in handling both small and large order volumes and fit for use for different product sizes with a varying number of order pickers. These systems are often applied in

warehouses handling customer orders with a large number of order lines and with a large number of different products kept in stock (Park 2012). A disadvantage of such systems, however, is congestion and blocking under heavy use, leading to long order throughput times.

Zone picking systems can be categorized into parallel and sequential systems (De Koster et al. 2007). In parallel zone picking, a customer order consisting of several order lines is picked simultaneously in multiple zones. A downstream sorting process consolidates the picked order lines into customer orders after the picking process has been completed. In sequential zone picking (or pick-and-pass picking), shown in Figure 1, an order is assigned to an order tote or order carton that travels on the conveyor. Upon arrival at a zone, the tote enters the buffer if the zone stores products that should be added to the order or travels to the next zone. At a zone, each picker picks for one tote at a time. The advantage of sequential zone picking is that order integrity is

Figure 1. (Color online) A Sequential Multisegment Zone Picking System (Vanderlande 2007)

maintained, and no sorting and product consolidation is required (Petersen 2000).

There are two types of sequential zone picking systems: *single-segment routing* and *multisegment routing*. In single-segment routing, the conveyor forms a circular loop connecting all zones, whereas in multisegment routing, zones are grouped in segments, and within each segment, the zones are connected to a conveyor with a recirculation loop. The segments are then connected by a central (or main) conveyor that diverts the totes to the required segments (see Figure 1). Multisegment routing improves the system throughput significantly because of shorter conveyor loops that avoid unnecessary tote travel times. However, investment costs and space requirements are higher compared with single-segment routing.

De Koster (1994), Yu and De Koster (2008, 2009), and Melacini et al. (2010) model a zone picking system as a network of queues. They use Whitt's queueing network analyzer (Whitt 1982) to estimate performance statistics, such as utilization, throughput rate of a zone, and mean and standard deviation of the throughput time of the totes. However, a crucial aspect not taken into consideration is blocking. In most environments, the workload of the zones exhibit variability because of differences in work profiles of the orders. In peak periods, zones can become congested, leading to blockages that can propagate throughout the network, resulting in starved zones and increased throughput times. This can affect the performance of a zone picking system significantly and should not be ignored. Identifying and quantifying the effect of blocking is crucial in the design of zone picking systems.

In a zone picking system, congestion occurs in zones as well as in segments. In both cases, the *block-and-recirculate* protocol is used to dynamically manage

workload: a tote is blocked and recirculated on the conveyor loop if the destination buffer is full or the segment is congested. The tote potentially visits other zones or segments before attempting to reenter the zone or segment where it was blocked.

Queueing networks with the block-and-recirculate protocol are highly intractable: no exact results for the stationary distribution exist. In the literature, blocking protocols have been investigated for various applications (see Schmidt and Jackman (2000), Hsieh and Bozer (2005), and Osorio and Bierlaire (2009) for recent references on manufacturing systems with automated conveyors). For a review on queueing networks with blocking, the reader is referred to Papadopoulos et al. (1993), Perros (1994), and Balsamo et al. (2001). Yao and Buzacott (1987) were the first to study a variation of the block-and-recirculate protocol for flexible manufacturing systems. However, this variation is not applicable in the context of zone picking systems.

The objective of the paper is to develop a capacity model for sequential zone picking systems (hereafter zone picking) with either single-segment or multisegment routing, finite buffers, segment capacities, and the block-and-recirculate protocol. This model can be used in the design phase of zone picking systems to study the effects of layout, loading, and storage on blocking and congestion. It considerably extends the models of De Koster (1994), Yu and De Koster (2008, 2009), and Melacini et al. (2010) that consider zone picking systems with single-segment routing and no blocking. The capacity model is a multiclass queueing network with the block-and-recirculate protocol. Because an exact analysis of block-and-recirculate queueing networks is not feasible, we develop an approximation by iteratively estimating the blocking probabilities in a multiclass

queueing network with *jump-over* blocking (Van Dijk 1988, Economou and Fakinou 1998). We show that jump-over blocking admits a product-form stationary queue length distribution. Key to the approximation is to equip the jump-over queueing network with Markovian routing that reflects the relation to the block-and-recirculate queueing network; that is, the flows in both networks should match. It appears that the approximation is efficient and provides accurate estimates of key statistics. Hence, it is a powerful tool to support decisions on the required the number of segments, number and size of zones, buffer capacities, or storage allocation of products to zones to meet performance targets.

This paper is organized as follows: Section 2 presents the model for single-segment routing zone picking systems and develops the approximation and analysis. The model is extended to multisegment routing zone picking systems in Section 3. In Section 4, we analyze the results of the approximation for a range of parameters via computational experiments. In the final section, we conclude and suggest model extensions and topics for further research.

2. Single-Segment Zone Picking Systems

A zone picking system with single-segment routing comprises three parts: the entrance/exit, the conveyors, and the zones. Figure 2(a) shows a single-segment zone picking system with two zones.

Order release is regulated by a workload control mechanism (Park 2012), which sets an upper bound on the number of totes in the zones and on the conveyor. When this bound is reached, the control mechanism only releases a new order when a tote with all required order lines leaves the system. This mechanism prevents the conveyor from becoming the bottleneck of the system.

Once an order is released, it is assigned to a tote at the entrance station. The tote then receives its data, for example, its packing list, and moves to the buffer of a requested zone and enters if the buffer is not full. Otherwise, the tote is blocked and stays on the conveyor to potentially visit other zones before returning. When the picking process has finished, the picker pushes the tote back on the conveyor. The waiting time for an empty space on the conveyor is assumed to be negligible because of the workload control mechanism. The conveyor then transports the tote to the next zone. A weight check at the end of the conveyor loop ensures that the tote contains all the required order lines. Otherwise, the tote is sent back to the beginning of the loop and returns to the zones where it was blocked previously. When the tote has visited all the required zones, it exits the system, and a new tote is immediately released into the system. Hence, we assume a saturated system with an infinite supply of orders. This is a valid assumption for zone picking system design, which aims at studying the throughput capacity of the system. Operational issues, such as the effect of varying order arrival rates and order waiting times are not in the scope of this paper, but can be studied within the framework of semiopen queueing networks.

To model this system, we propose a queueing network, the topology of which is shown in Figure 2(b) for a case of two zones. The zone picking system is modeled as a closed queueing network with one entrance/exit, M zones, and $M + 1$ nodes describing the conveyor between either two adjacent zones or between the entrance/exit and the first or last zone. The system entrance/exit is denoted as e , $\mathcal{Z} = \{z_1, \dots, z_M\}$ denotes the set of zones, and $\mathcal{C} = \{c_1, \dots, c_{M+1}\}$ is the set of conveyors. Finally, $\mathcal{S} = \{e\} \cup \mathcal{C} \cup \mathcal{Z}$ is the set of

Figure 2. (Color online) A Zone Picking System with Single-Segment Routing and Its Corresponding Queueing Network

A zone picking system with single-segment routing and two zones

Corresponding queueing network with system entrance/exit e , conveyors $\mathcal{C} = \{c_1, c_2, c_3\}$ and zones $\mathcal{Z} = \{z_1, z_2\}$

all nodes in the network. We make the following assumptions:

- There is an infinite supply of orders and totes at the entrance of the system. This implies that a leaving tote is always immediately replaced by a new tote. Each tote initially has class $r \subseteq \mathcal{Z}$; for example, $r = \{z_2, z_3\}$ means that the tote has to visit the second and third zone. After visiting zone z_i , its class changes to $r \setminus \{z_i\}$, and when $r = \emptyset$, all required zones have been visited.

- The total number of totes in the system is always N . As long as the total number of totes in the zones and conveyor nodes is less than N , new totes are released one by one from the entrance/exit at an exponential rate μ_e , reflecting the rate at which a tote is prepared to enter the system (i.e., unfolding, adding labels, printing the packing list, etc.).

- The conveyor nodes are delay nodes with an exponential delay with mean $1/\mu_i$, $i \in \mathcal{C}$. Remark 1 discusses the extension to Erlang distributed and deterministic delays.

- Each zone $i \in \mathcal{Z}$ has $d_i (\geq 1)$ servers, which represent the order pickers in the zone. Orders are picked in order of arrival. The order-picking time is exponentially distributed with rate μ_i , $i \in \mathcal{Z}$, which captures both variations in the pick time per tote and variations in the number of order lines to be picked. This assumption is relaxed in Remark 3.

- When the order pickers are busy, incoming totes are stored in a finite input buffer of size q_i , $i \in \mathcal{Z}$. Incoming totes are blocked when the total number of totes in the buffer equals q_i .

Let x_{il} be the class of the tote in position l of node i and let n_i be the number of totes in node i . Then the vector $x_i = (x_{i1}, \dots, x_{i1}, \dots, x_{in_i})$ describes the detailed state of node i , and the queueing network with states $x = (x_i : i \in \mathcal{P})$ is a Markov process. Let $\mathbb{S}(N)$ be the state space of the network, that is, the set of states x for which $\sum_{i \in \mathcal{G}} n_i = N$ and $n_i \leq d_i + q_i$, $i \in \mathcal{Z}$.

The routing of totes through the network proceeds as follows. A new tote of class $r \subseteq \mathcal{Z}$ is released at the system entrance with probability ψ_r . These release probabilities correspond to a known order profile obtained from, for example, historical order data or forecasts. After release, a class r tote moves from the system entrance to the first conveyor node c_1 . After conveyor node c_i , the tote either enters the input buffer of zone i if $z_i \in r$ and the buffer is not full or move to the next conveyor node c_{i+1} . If the tote needs to enter and the buffer is full, the tote skips the zone and moves to c_{i+1} while keeping the same class. If the buffer is not full, the tote enters the buffer of zone i , and after waiting in the buffer, an order picker picks the required order lines. After all picks are completed, the tote enters c_{i+1} , and its class changes to $s = r \setminus \{z_i\}$. After visiting the last conveyor node c_{M+1} , all totes

with $r \neq \emptyset$ are routed to the first conveyor node c_1 . The other totes move to the exit and are immediately replaced by a new tote waiting for release at the entrance.

Formally, let $p_{ir,js}(x)$ be the state-dependent routing probability that a class r tote is routed from node i to node j , where it moves into the last position and changes to a class s tote given that the network is in state x . Then

$$p_{e0,c_1r}(x) = \psi_r, \quad (1)$$

$$p_{c_i r, z_i r}(x) = 1, \quad i = 1, \dots, M, z_i \in r \text{ and } n_{z_i} < d_{z_i} + q_{z_i}, \quad (2)$$

$$p_{c_i r, c_{i+1} r}(x) = 1, \quad i = 1, \dots, M, z_i \notin r \text{ or } n_{z_i} = d_{z_i} + q_{z_i}, \quad (3)$$

$$p_{z_i r, c_{i+1} s}(x) = 1, \quad i = 1, \dots, M, z_i \in r, s = r \setminus \{z_i\}, \quad (4)$$

$$p_{c_{M+1} \emptyset, e0}(x) = 1, \quad (5)$$

$$p_{c_{M+1} r, c_1 r}(x) = 1, \quad r \neq \emptyset, \quad (6)$$

where the other routing probabilities are equal to zero.

The stationary distribution of this queueing network is intractable because of the finite buffers (Stidham 2002) and the block-and-recirculate protocol, which justifies the development of an approximation. The first step is to approximate the block-and-recirculate network by a jump-over network. This is described in Section 2.1. This jump-over network exhibits a product-form steady-state distribution as shown in Section 2.2. Closed-form formulas of the visit ratios are derived in Section 2.3. In Section 2.4, performance statistics of the jump-over network can be easily calculated by, for example, mean value analysis (MVA). Section 2.5 explains how the jump-over network is used to approximate the original network, and Section 2.6 investigates the quality of the approximation.

2.1. Jump-Over Network

We approximate the block-and-recirculate protocol by the jump-over blocking protocol (Van Dijk 1988). This protocol, also known as “overtake full stations, skipping, and blocking and rerouting,” admits closed-form analytic results for single-class queueing networks (Pittel 1979, Schassberger 1984, Van Dijk 1988, Economou and Fakinos 1998). Figure 3 illustrates both blocking protocols.

In the block-and-recirculate protocol (Figure 3(a)), a class r tote that intends to visit zone $z_i \in r$ either enters the input buffer of z_i or skips z_i if its input buffer is full. Class r totes skipping zone z_i maintain their class, and class r totes leaving z_i always change to class $r \setminus \{z_i\}$ before entering conveyor c_{i+1} (because these totes visited z_i).

In the jump-over blocking protocol (Figure 3(b)), a class r tote also skips zone z_i if the input buffer is full and proceeds as a class r tote when leaving z_i .

Figure 3. Description of Zone Blocking in the Block-and-Recirculate Network and the Jump-Over Network

A Bernoulli trial then determines whether each class r tote leaving z_i changes class or not: it maintains class r with probability b_{z_i} and changes to class $s = r \setminus \{z_i\}$ otherwise independent of whether the tote visited or skipped zone z_i . Hence, the routing probabilities under jump-over blocking are state independent and given by the following (cf. (2)–(4)):

$$p_{c_i r, z_i r} = 1, \quad i = 1, \dots, M, z_i \in r, \quad (7)$$

$$p_{c_i r, c_{i+1} r} = 1, \quad i = 1, \dots, M, z_i \notin r, \quad (8)$$

$$p_{z_i r, c_{i+1} r} = b_{z_i}, \quad i = 1, \dots, M, z_i \in r, \quad (9)$$

$$p_{z_i r, c_{i+1} s} = 1 - b_{z_i}, \quad i = 1, \dots, M, z_i \in r, s = r \setminus \{z_i\}, \quad (10)$$

where the other routing probabilities are the same as in the block-and-recirculate network.

Key to the approximation is to choose b_{z_i} such that the flows of class r and $r \setminus \{z_i\}$ totes entering c_{i+1} match under both protocols. This can be done by taking b_{z_i} as the fraction of totes skipping z_i in the block-and-recirculate network. In other words, b_{z_i} is the blocking probability of zone z_i under block and recirculate. Naturally, this blocking probability is not known but is estimated by an iterative algorithm in Section 2.5.

2.2. Product-Form Stationary Distribution

Let λ_{ir} be the visit ratio of a class r tote to node i satisfying the traffic equations

$$\lambda_{ir} = \sum_{j \in \mathcal{F}} \sum_{s \subseteq \mathcal{Z}} \lambda_{js} p_{js, ir}, \quad i \in \mathcal{F}, r \subseteq \mathcal{Z}. \quad (11)$$

Equation (11) determines the visit ratios λ_{ir} up to a multiplicative constant. By substituting the routing probabilities (7)–(10), the traffic equations reduce to

$$\lambda_{e0} = \lambda_{c_{M+1}0}, \quad (12)$$

$$\lambda_{c_1 r} = \lambda_{e0} \psi_r + \lambda_{c_{M+1} r}, \quad r \subseteq \mathcal{Z}, \quad (13)$$

$$\lambda_{c_{i+1} r} = \lambda_{z_i r} b_{z_i}, \quad i = 1, \dots, M, z_i \in r \subseteq \mathcal{Z}, \quad (14)$$

$$\lambda_{c_{i+1} r} = \lambda_{c_i r} + \lambda_{z_i r \cup \{z_i\}} (1 - b_{z_i}), \quad i = 1, \dots, M, z_i \notin r \subseteq \mathcal{Z}, \quad (15)$$

$$\lambda_{z_i r} = \lambda_{c_i r}, \quad i = 1, \dots, M, z_i \in r \subseteq \mathcal{Z}, \quad (16)$$

where the other visit ratios are equal to zero.

Theorem 1. The single-segment jump-over network has stationary distribution

$$\pi(x) = \frac{1}{G} \prod_{i \in \mathcal{F}} \pi_i(x_i), \quad (17)$$

where G is the normalization constant and $\pi_i(x_i)$ are defined as

$$\pi_i(x_i) = \begin{cases} \prod_{l=1}^{n_i} \frac{\lambda_{ix_{il}}}{\mu_i}, & i = e, \\ \prod_{l=1}^{n_i} \frac{\lambda_{ix_{il}}}{\mu_i} \cdot \frac{1}{n_i!}, & i \in \mathcal{C}, \\ \prod_{l=1}^{n_i} \frac{\lambda_{ix_{il}}}{\mu_i} \cdot \frac{1}{\gamma(n_i)}, & i \in \mathcal{Z}, \end{cases} \quad (18)$$

with

$$\gamma(n_i) = \begin{cases} n_i!, & \text{if } n_i \leq d_i, \\ d_i! (d_i)^{n_i - d_i}, & \text{if } n_i > d_i. \end{cases}$$

Proof. Let $q(x, y)$ denote the transition rate from state x to y . The transition rates are specified as follows. We use the notation $x - r_{il} + s_{jk}$ to indicate the state obtained from x by removing the class r tote in position l of node i (so $r = x_{il}$) and inserting a class s tote into position k of node j . The events in this network are (single) totes departing from one node and moving to the next one. If, in state x , a new class r tote is released from entrance e , it moves to conveyor c_1 . The state after this event is $x - \emptyset_{e1} + r_{c_1 n_{c_1+1}}$, and the rate is equal to

$$q(x, x - \emptyset_{e1} + r_{c_1 n_{c_1+1}}) = \mu_e \psi_r. \quad (19)$$

Naturally, this event is only feasible if $n_e > 0$. If the class r tote in position l of conveyor c_i (with $i \leq M$) completes transportation and $z_i \notin r$, the tote continues to the next conveyor c_{i+1} , so

$$q(x, x - r_{c_i l} + r_{c_{i+1} n_{c_{i+1}+1}}) = \mu_{c_i}, \quad z_i \notin r. \quad (20)$$

If $z_i \in r$ and there is room in the buffer, the tote joins zone z_i . Hence, if $n_{z_i} < d_{z_i} + q_{z_i}$,

$$q(x, x - r_{c_i l} + r_{z_i n_{z_i}+1}) = \mu_{c_i}, \quad z_i \in r, \quad (21)$$

and if $n_{z_i} = d_{z_i} + q_{z_i}$, the tote skips z_i and changes class to $r \setminus \{z_i\}$ with probability $1 - b_{z_i}$,

$$q(x, x - r_{c_l} + s_{c_{i+1}n_{c_{i+1}}+1}) = \begin{cases} \mu_{c_i}(1 - b_{z_i}), & z_i \in r, s = r \setminus \{z_i\}, \\ \mu_{c_i}b_{z_i}, & z_i \in r, s = r. \end{cases} \quad (22)$$

If order picking for the class r tote in position l of zone z_i (with $l \leq \min(d_{z_i}, n_{z_i})$) finishes, the tote continues to c_{i+1} . So

$$q(x, x - r_{z_i} + s_{c_{i+1}n_{c_{i+1}}+1}) = \begin{cases} \mu_{z_i}(1 - b_{z_i}), & s = r \setminus \{z_i\}, \\ \mu_{z_i}b_{z_i}, & s = r. \end{cases} \quad (23)$$

Finally, if the class r tote in position l of the last conveyor c_{M+1} completes transportation and $r = \emptyset$, the tote joins exit e , and otherwise, it continues to the first conveyor c_1 . Hence,

$$q(x, x - r_{c_{M+1}l} + r_{j_{n_j+1}}) = \begin{cases} \mu_{c_{M+1}}, & r = \emptyset, j = e, \\ \mu_{c_{M+1}}, & r \neq \emptyset, j = c_1. \end{cases} \quad (24)$$

This completes the description of the nonzero transition rates. Note that the total rate from x is

$$q(x) = \sum_{y \in \mathbb{S}(N)} q(x, y) = \mu_e I_{(n_e > 0)} + \sum_{i=1}^{M+1} n_{c_i} \mu_{c_i} + \sum_{i=1}^M \min(d_{z_i}, n_{z_i}) \mu_{z_i}, \quad (25)$$

where $I_{(\cdot)}$ is the indicator function.

To prove (17) we use (Kelly 1979, theorem 1.13) stating that, if we can find a collection of numbers $\bar{q}(x, y)$, $x, y \in \mathbb{S}(N)$ such that

$$\bar{q}(x) = q(x), \quad x \in \mathbb{S}(N), \quad (26)$$

and a collection of positive numbers $\pi(x)$, $x \in \mathbb{S}(N)$, summing to unity, such that

$$\pi(x)q(x, y) = \pi(y)\bar{q}(y, x), \quad x, y \in \mathbb{S}(N), \quad (27)$$

then $\bar{q}(x, y)$ are the transition rates of the time-reversed process and $\pi(x)$ is the stationary distribution of both processes. Obviously, the proposed collection $\pi(x)$ is (17). Equation (27) then defines the rates $\bar{q}(x, y)$, and the only thing that remains to be done is verifying (26). First, we determine the rates $\bar{q}(x, y)$ from (27).

At entrance e , only class $\emptyset$ totes arrive from conveyor c_{M+1} . Hence, from (24), (27) and (17), we get, for $l = 1, \dots, n_{c_{M+1}} + 1$,

$$\begin{aligned} \bar{q}(x, x - \emptyset_{en_e} + \emptyset_{c_{M+1}l}) &= \mu_{c_{M+1}} \frac{\pi(x - \emptyset_{en_e} + \emptyset_{c_{M+1}l})}{\pi(x)} \\ &= \mu_{c_{M+1}} \frac{\frac{\lambda_{c_{M+1}\emptyset}}{\mu_{c_{M+1}}n_{c_{M+1}}+1}}{\frac{\lambda_{\emptyset\emptyset}}{\mu_e}} \\ &= \frac{\mu_e}{\lambda_{\emptyset\emptyset}} \frac{\lambda_{c_{M+1}\emptyset}}{n_{c_{M+1}} + 1}, \end{aligned} \quad (28)$$

provided $n_e > 0$. In conveyor c_1 , class r totes arrive from entrance e and conveyor c_{M+1} , so by (19),

$$\begin{aligned} \bar{q}(x, x - r_{c_1n_{c_1}} + \emptyset_{e1}) &= \mu_e \psi_r \frac{\pi(x - r_{c_1n_{c_1}} + \emptyset_{e1})}{\pi(x)} \\ &= \frac{n_{c_1} \mu_{c_1}}{\lambda_{c_1r}} \lambda_{e\emptyset} \psi_r, \end{aligned} \quad (29)$$

and by (24), for $l = 1, \dots, n_{c_{M+1}} + 1$,

$$\bar{q}(x, x - r_{c_1n_{c_1}} + r_{c_{M+1}l}) = \frac{n_{c_1} \mu_{c_1}}{\lambda_{c_1r}} \frac{\lambda_{c_{M+1}r}}{n_{c_{M+1}} + 1}. \quad (30)$$

In conveyor c_{i+1} , class r totes arrive from c_i and z_i . If $z_i \notin r$, then by (20), for $l = 1, \dots, n_{c_i} + 1$,

$$\bar{q}(x, x - r_{c_{i+1}n_{c_{i+1}}} + r_{c_i l}) = \frac{n_{c_{i+1}} \mu_{c_{i+1}}}{\lambda_{c_{i+1}r}} \frac{\lambda_{c_i r}}{n_{c_i} + 1}. \quad (31)$$

If $n_{z_i} = d_{z_i} + q_{z_i}$, then class r totes also arrive from c_i by changing class. By (22), for $l = 1, \dots, n_{c_i} + 1$,

$$\bar{q}(x, x - r_{c_{i+1}n_{c_{i+1}}} + r \cup \{z_i\}_{c_i l}) = \frac{n_{c_{i+1}} \mu_{c_{i+1}}}{\lambda_{c_{i+1}r}} \frac{\lambda_{c_i r \cup \{z_i\}}}{n_{c_i} + 1} (1 - b_{z_i}). \quad (32)$$

Otherwise, if $n_{z_i} < d_{z_i} + q_{z_i}$, class r totes arrive from z_i . By (23), for $l = 1, \dots, \min(d_{z_i}, n_{z_i} + 1)$,

$$\begin{aligned} \bar{q}(x, x - r_{c_{i+1}n_{c_{i+1}}} + r \cup \{z_i\}_{z_i l}) &= \frac{n_{c_{i+1}} \mu_{c_{i+1}}}{\lambda_{c_{i+1}r}} \frac{\lambda_{z_i r \cup \{z_i\}}}{\min(d_{z_i}, n_{z_i} + 1)} (1 - b_{z_i}). \end{aligned} \quad (33)$$

Also class r totes with $z_i \in r$ arrive in c_{i+1} from c_i and z_i . If $z_i \in r$, then by (22), for $l = 1, \dots, n_{c_i} + 1$,

$$\bar{q}(x, x - r_{c_{i+1}n_{c_{i+1}}} + r_{c_i l}) = \frac{n_{c_{i+1}} \mu_{c_{i+1}}}{\lambda_{c_{i+1}r}} \frac{\lambda_{c_i r}}{n_{c_i} + 1} b_{z_i} \quad (34)$$

if $n_{z_i} = d_{z_i} + q_{z_i}$, and otherwise, if $n_{z_i} < d_{z_i} + q_{z_i}$, then by (23), for $l = 1, \dots, \min(d_{z_i}, n_{z_i} + 1)$,

$$\bar{q}(x, x - r_{c_{i+1}n_{c_{i+1}}} + r_{z_i l}) = \frac{n_{c_{i+1}} \mu_{c_{i+1}}}{\lambda_{c_{i+1}r}} \frac{\lambda_{z_i r}}{\min(d_{z_i}, n_{z_i} + 1)} b_{z_i}. \quad (35)$$

Finally, in zone z_i , class r totes arrive from c_i with $z_i \in r$. By (21), for $l = 1, \dots, n_{c_i} + 1$,

$$\bar{q}(x, x - r_{z_i n_{z_i}} + r_{c_i l}) = \frac{\min(d_{z_i}, n_{z_i}) \mu_{z_i}}{\lambda_{z_i r}} \frac{\lambda_{c_i r}}{n_{c_i} + 1}. \quad (36)$$

This completes the specification of the nonzero rates $\bar{q}(x, y)$.

To determine $\bar{q}(x)$, note that, by (28), the rate of events in x coming from entrance e is equal to

$$\begin{aligned} \sum_{l=1}^{n_{c_{M+1}}+1} \bar{q}(x, x - \emptyset_{e_n} + \emptyset_{c_{M+1}l}) &= \sum_{l=1}^{n_{c_{M+1}}+1} \frac{\mu_e}{\lambda_{e\emptyset}} \frac{\lambda_{c_{M+1}\emptyset}}{n_{c_{M+1}} + 1} \\ &= \mu_e \frac{\lambda_{c_{M+1}\emptyset}}{\lambda_{e\emptyset}} = \mu_e, \end{aligned}$$

provided $n_e > 0$. The last equality follows from the traffic Equation (12). By (29) and (30) and using traffic Equation (13), it follows that the rate of events resulting from c_1 is given by

$$\begin{aligned} \bar{q}(x, x - r_{c_1 n_{c_1}} + \emptyset_{e1}) + \sum_{l=1}^{n_{c_{M+1}}+1} \bar{q}(x, x - r_{c_1 n_{c_1}} + r_{c_{M+1}l}) \\ = n_{c_1} \mu_{c_1} \frac{\lambda_{e\emptyset} \psi_r + \lambda_{c_{M+1}r}}{\lambda_{c_1 r}} = n_{c_1} \mu_{c_1}. \end{aligned}$$

If $z_i \notin r$, then it follows from (31)–(33) that the rate of events resulting from c_{i+1} is

$$\begin{aligned} \sum_{l=1}^{n_{c_i}+1} \bar{q}(x, x - r_{c_{i+1} n_{c_{i+1}}} + r_{c_{i+1}l}) \\ + \sum_{l=1}^{n_{c_i}+1} \bar{q}(x, x - r_{c_{i+1} n_{c_{i+1}}} + r \cup \{z_i\}_{c_{i+1}l}) \\ = n_{c_{i+1}} \mu_{c_{i+1}} \frac{\lambda_{c_i r} + \lambda_{c_i r \cup \{z_i\}} (1 - b_{z_i})}{\lambda_{c_{i+1} r}} = n_{c_{i+1}} \mu_{c_{i+1}} \quad (37) \end{aligned}$$

if $n_{z_i} = d_{z_i} + q_{z_i}$, and otherwise, if $n_{z_i} < d_{z_i} + q_{z_i}$,

$$\begin{aligned} \sum_{l=1}^{n_{c_i}+1} \bar{q}(x, x - r_{c_{i+1} n_{c_{i+1}}} + r_{c_{i+1}l}) \\ + \sum_{l=1}^{\min(d_{z_i}, n_{z_i}+1)} \bar{q}(x, x - r_{c_{i+1} n_{c_{i+1}}} + r \cup \{z_i\}_{z_{i+1}l}) \\ = n_{c_{i+1}} \mu_{c_{i+1}} \frac{\lambda_{c_i r} + \lambda_{z_i r \cup \{z_i\}} (1 - b_{z_i})}{\lambda_{c_{i+1} r}} = n_{c_{i+1}} \mu_{c_{i+1}}, \quad (38) \end{aligned}$$

where the last equalities in (37) and (38) follow from traffic Equations (15) and (16). Alternatively, if $z_i \in r$, then it follows from (34) and (35) and traffic Equations (14) and (16), that the rate of events resulting from c_{i+1} is also equal to $n_{c_{i+1}} \mu_{c_{i+1}}$. By (36) and (16), the rate of events resulting from z_i is

$$\begin{aligned} \sum_{l=1}^{n_{c_i}+1} \bar{q}(x, x - r_{z_i n_{z_i}} + r_{c_{i+1}l}) &= \min(d_{z_i}, n_{z_i}) \mu_{z_i} \frac{\lambda_{c_i r}}{\lambda_{z_i r}} \\ &= \min(d_{z_i}, n_{z_i}) \mu_{z_i}. \end{aligned}$$

The total rate $\bar{q}(x)$ is now obtained by adding the rate of events resulting from each of the nodes in the network. It is exactly the same as $q(x)$ given by (25). $\square$

Theorem 1 provides the stationary distribution of the jump-over network with detailed states x . However,

knowledge of the number of totes in each node is sufficient to determine statistics, such as throughput and waiting times in the zones. To present the stationary distribution in terms of the aggregate vector $(n_i : i \in \mathcal{I})$, we transform the class-dependent visit ratios λ_{ir} into chain visit ratios

$$V_i = \frac{\sum_{r \subseteq \mathcal{I}} \lambda_{ir}}{\sum_{r \subseteq \mathcal{I}} \lambda_{er}}, \quad i \in \mathcal{I}, \quad (39)$$

which can be interpreted as the average number of times an arbitrary tote visits node i before moving to the exit node e . Because every tote can be replaced by one of any other class at the exit, the jump-over network has a single chain of classes with a population of N totes.

Corollary 1. In aggregate form, the stationary distribution of the jump-over network is

$$\pi(n_i : i \in \mathcal{I}) = \frac{1}{G} \prod_{i \in \mathcal{I}} \pi_i(n_i), \quad (40)$$

where G is the normalization constant and $\pi_i(n_i)$ are defined as

$$\pi_i(x_i) = \begin{cases} \left(\frac{V_i}{\mu_i} \right)^{n_i}, & i = e, \\ \left(\frac{V_i}{\mu_i} \right)^{n_i} \cdot \frac{1}{n_i!}, & i \in \mathcal{C}, \\ \left(\frac{V_i}{\mu_i} \right)^{n_i} \cdot \frac{1}{\gamma(n_i)}, & i \in \mathcal{D}. \end{cases} \quad (41)$$

Remark 1. Corollary 1 can be extended to Erlang-distributed delays, similar as in the BCMP theorem (Baskett et al. 1975). Suppose every conveyor c_i consists of a tandem of k conveyor nodes $c_{i_1}, \dots, c_{i_k}$, each with exponential rate $k\mu_{c_i}$. So the mean total transportation time in conveyor c_i is still $1/\mu_{c_i}$ though its variability is less than exponential. This larger network also possesses a stationary distribution of the form (17) and (40), in which the set of conveyors is extended to $\{c_{i_1}, \dots, c_{i_k} : i = 1, \dots, M+1\}$ and in which $c_{i_1}, \dots, c_{i_k}$ have the same visit ratio as c_i . By considering the total number of totes n_{c_i} in the tandem $c_{i_1}, \dots, c_{i_k}$, we obtain

$$\begin{aligned} \sum_{n_{c_{i_1}} + \dots + n_{c_{i_k}} = n_{c_i}} \pi_{c_{i_1}}(n_{c_{i_1}}) \cdots \pi_{c_{i_k}}(n_{c_{i_k}}) \\ = \sum_{n_{c_{i_1}} + \dots + n_{c_{i_k}} = n_{c_i}} \frac{1}{n_{c_{i_1}}!} \left(\frac{V_{c_{i_1}}}{k\mu_{c_i}} \right)^{n_{c_{i_1}}} \cdots \frac{1}{n_{c_{i_k}}!} \left(\frac{V_{c_{i_k}}}{k\mu_{c_i}} \right)^{n_{c_{i_k}}} \\ = \frac{1}{n_{c_i}!} \sum_{n_{c_{i_1}} + \dots + n_{c_{i_k}} = n_{c_i}} \frac{n_{c_i}!}{n_{c_{i_1}}! \cdots n_{c_{i_k}}!} \left(\frac{V_{c_i}}{k\mu_{c_i}} \right)^{n_{c_i}} \\ = \frac{1}{n_{c_i}!} \left(\frac{V_{c_i}}{\mu_{c_i}} \right)^{n_{c_i}} = \pi_{c_i}(n_{c_i}). \end{aligned}$$

Hence, the aggregate product-form (40) is also valid if the delay in conveyor node c_i is Erlang- k distributed with mean $1/\mu_{c_i}$. Because this is true for every k , we

can take k to ∞ to conclude that Corollary 1 remains valid for conveyor nodes c_i with constant delay $1/\mu_{c_i}$ (Kelly 1979, lemma 3.9).

Remark 2. The notion of quasi-reversibility by Kelly (1979) was extended by Chao and Miyazawa (2000) and Henderson and Taylor (2001). They show that quasi-reversibility can be applied to obtain product-form solutions for queueing networks with signals, negative customers, transitions involving three or more nodes, and batch movements. This approach can also be used to study the jump-over network.

2.3. Chain Visit Ratios

To obtain the chain visit ratios V_i , $i \in \mathcal{S}$, we need to solve the traffic Equation (11). This might, however, require a large computational effort because the number of tote classes, 2^M , grows exponentially with the number of zones. Alternatively, V_i can be calculated directly per node type, that is, entrance/exit, conveyor, and zone. Clearly, $V_e = 1$ by (39). In the next subsections, we explain how the chain visit ratios of conveyors and zones are calculated.

2.3.1. Conveyor Nodes. A tote visits all conveyor nodes with the same frequency during its stay in the system. As a result, the chain visit ratios V_i of conveyor nodes are all the same and equal the average number of circulations of an arbitrary tote in the system before moving to the exit.

Let X_l denote the class of a tote at the last conveyor c_{M+1} after its l th circulation. Then $\{X_l, l \geq 0\}$ is an absorbing Markov chain with state space consisting of all subsets of $\mathcal{Z}$, transition probability matrix Φ , and absorbing state $\emptyset$. The chain starts in state $X_0 = r$ with probability ψ_r . The average number of circulations is then equal to the expected number of transitions before entering the absorbing state $\emptyset$. Transition probability $\Phi_{r,s}$ from state r at the start of a circulation to s at the end of this circulation is given by the following (cf. (8)–(10)):

$$\Phi_{r,s} = \prod_{j \in s} b_j \prod_{i \in r \setminus s} (1 - b_i), \quad s \subseteq r \subseteq \mathcal{Z},$$

and zero otherwise. Note that transitions are only possible to states with fewer zones. Hence, the states can be ordered such that Φ is an upper triangular matrix, which can be written as

$$\Phi = \begin{bmatrix} \Theta & \Upsilon \\ \mathbf{0} & \mathbf{1} \end{bmatrix}, \quad (42)$$

where Θ is an upper triangular matrix of transition probabilities between transient states, and Υ is a column vector of transition probabilities from transient states to absorbing state $\emptyset$. The last row of Φ corresponds to

state $\emptyset$. The expected number of transitions until absorption is then given by (Wolff 1989)

$$V_i = \psi(I - \Theta)^{-1}\mathbf{1}, \quad i \in \mathcal{C}, \quad (43)$$

where I is the identity matrix, $\mathbf{1}$ the column vector with ones, and $\psi = (\psi_r : r \subseteq \mathcal{Z} \setminus \emptyset)$ the row vector with release probabilities ordered in the same way as Θ . Because $(I - \Theta)$ is an upper triangular, its inverse can be easily determined by back-substitution. Denote $\omega = (I - \Theta)^{-1}\mathbf{1}$; then the j th element of ω follows from the recursion

$$\omega_j = \left(1 + \sum_{k=j+1}^{2^M-1} \Theta_{j,k} \omega_k\right) / (1 - \Theta_{j,j}), \quad j = 2^M - 1, 2^M - 2, \dots, 1.$$

2.3.2. Zones. The chain visit ratios V_i of the zones are equal to the mean number of times an arbitrary tote visits zone i before leaving the system. In the jump-over network, the number of times a tote visits zone i follows a geometric distribution with success probability $1 - b_i$. Hence,

$$V_i = \sum_{r: i \in r \subseteq \mathcal{Z}} \frac{\psi_r}{1 - b_i}, \quad i \in \mathcal{Z}. \quad (44)$$

2.4. Mean Value Analysis

We formulate an MVA algorithm (Reiser and Lavenberg 1980) to efficiently compute key performance statistics of the jump-over network. MVA is based on the arrival theorem, which holds because of the product form solution of the jump-over network. Let $E(T_i(n))$ be the expected time a tote spends in node i per visit, $X(n)$ be the system throughput, $E(L_i(n))$ be the mean number of totes in node i , and $\pi_i(j|n)$ be the marginal queue length probabilities of j totes in zone i given there are n totes in the network. MVA then iteratively calculates these statistics.

First, initialize $E(L_i(0)) = 0$, $i \in \mathcal{S}$, and $\pi_i(0|0) = 1$, $\pi_i(j|0) = 0$ for $j = 1, \dots, d_i + q_i$ if $i \in \mathcal{Z}$. The mean throughput time $E(T_i(n))$ in entrance/exit e and conveyor nodes $i \in \mathcal{C}$ can be calculated by

$$E(T_i(n)) = \begin{cases} \frac{1}{\mu_i} (1 + E(L_i(n-1))), & \text{if } i = e, \\ \frac{1}{\mu_i}, & \text{if } i \in \mathcal{C}. \end{cases} \quad (45)$$

This follows from the arrival theorem and the fact that e is a single server and conveyor nodes $i \in \mathcal{C}$ are infinite servers. The mean throughput time in zones $i \in \mathcal{Z}$ can be calculated by

$$E(T_i(n)) = \sum_{j=d_i}^{d_i+q_i-1} (j+1-d_i) \frac{1}{d_i \mu_i} \pi_i(j|n-1) + \frac{1}{\mu_i} (1 - \pi_i(d_i + q_i|n-1)), \quad i \in \mathcal{Z}. \quad (46)$$

The first term of (46) is the average waiting time given the number of totes j in zone i on arrival, and the second term is the tote's own average service time. When the buffer of zone i is full, the throughput time is zero because the tote skips the zone. The system throughput $X(n)$ is given by (Reiser and Lavenberg 1980)

$$X(n) = \frac{n}{\sum_{i \in \mathcal{I}} V_i E(T_i(n))}, \quad (47)$$

where the denominator is the average time a tote spends in the system, that is, the system throughput time. Applying Little's law yields

$$E(L_i(n)) = V_i X(n) E(T_i(n)), \quad i \in \mathcal{I}. \quad (48)$$

Finally, we determine the marginal queue length probabilities by balancing the number of transitions per time unit between state $j-1$ and j , where j is the number of totes in zone i . The rate from j to $j-1$ is given by $\min(j, d_i) \mu_i \pi_i(j|n)$ and, by the arrival theorem, the rate from $j-1$ to j is $V_i X(n) \pi_i(j-1|n-1)$. Hence,

$$\pi_i(j|n) = \frac{V_i X(n)}{\mu_i \min(j, d_i)} \pi_i(j-1|n-1), \quad j = 1, \dots, d_i + q_i, i \in \mathcal{I}, \quad (49)$$

where $\pi_i(0|n)$ follows from normalization

$$\pi_i(0|n) = 1 - \sum_{j=1}^{d_i+q_i} \pi_i(j|n), \quad i \in \mathcal{I}. \quad (50)$$

Equation (50) has often been reported as the cause of numerical instability in MVA (Chandy and Sauer 1980). A numerically stable alternative is equation (27) of Reiser (1981).

Performance statistics for $n = N$ can be determined by subsequently applying (45)–(50) for $n = 1, \dots, N$. Key statistics are the system throughput time $\sum_{i \in \mathcal{I}} V_i E(T_i(n))$; the probability that an arriving tote in zone i is blocked, that is, $b_i = \pi_i(d_i + q_i|N-1)$; and the utilization ρ_i given by

$$\rho_i = \begin{cases} X(N)/\mu_i, & \text{if } i = e, \\ V_i X(N)/\mu_i, & \text{if } i \in \mathcal{C}, \\ 1 - \sum_{j=0}^{d_i-1} ((d_i - j)/d_i) \pi_i(j|N), & \text{if } i \in \mathcal{I}, \end{cases} \quad (51)$$

where ρ_e is the fraction of time the entrance/exit is busy; ρ_i , $i \in \mathcal{I}$, is the fraction of time a picker in zone i is busy; and ρ_i , $i \in \mathcal{C}$ is the average number of totes in conveyor node i .

Remark 3. MVA is also exact in a jump-over network with deterministic conveyor delays (cf. Remark 1), but it is no longer exact in a network with nonexponential picking times. Still, closed queueing networks are known to be robust to service distributions (Bolch et al. 2006). When zone i is full, an arriving tote skips zone i

and its throughput time is zero. Otherwise, the tote enters zone i , where it first has to wait for the first departure in zone i and then continues to wait for as many departures as there are totes waiting for its arrival before entering service. Hence, by adopting the arrival theorem as an approximation (Adan and Van der Wal 2011), we get

$$\begin{aligned} E(T_i(n)) &= Q_i(n-1) \frac{E(R_i)}{d_i} \\ &+ \sum_{j=d_i}^{d_i+q_i-1} (j-d_i) \frac{E(B_i)}{d_i} \pi_i(j|n-1) \\ &+ E(B_i)(1 - \pi_i(d_i + q_i|n-1)), \quad i \in \mathcal{I}, \end{aligned} \quad (52)$$

which replaces (46). In (52), $E(B_i)$ is the expected service time of zone i , $E(R_i) = E(B_i^2)/2E(B_i)$ is the expected residual service time of zone i , and $Q_i(n-1) = \sum_{j=d_i}^{d_i+q_i-1} \pi_i(j|n-1)$ is the probability that all order pickers are busy upon entering zone i . Queue length probabilities $\pi_i(j|n)$ can again be determined by balancing the number of transitions per time unit between state $j-1$ and j , assuming as approximation that each order picker has an exponential service rate $1/E(B_i)$.

2.5. Iterative Algorithm for Calculating Blocking Probabilities

In the jump-over network, totes leaving zone i randomly change class according to probability b_i , independent of the state of zone i , $i \in \mathcal{I}$. Probability b_i should match the blocking probability of zone i in the block-and-recirculate network. However, this blocking probability is not known in advance, but can be iteratively estimated. Initially, we set $b_i^{(1)} = 0$, $i \in \mathcal{I}$. Then, we calculate the marginal queue length probabilities using Equations (49) and (50) and take the fraction of totes finding on arrival $d_i + q_i$ totes in zone i as new estimate for b_i . Thus, by the arrival theorem,

$$b_i^{(m+1)} = \pi_i^{(m)}(d_i + q_i|N-1), \quad i \in \mathcal{I}, \quad (53)$$

where superscript (m) indicates that the quantity has been calculated in the m th iteration. Based on this new estimate for b_i , routing probabilities and chain visit ratios are recalculated for all zones and conveyor nodes. After applying MVA, Equation (53) is used again to get a better estimate of b_i and so on. This process continues until the difference between $b_i^{(m+1)}$ and $b_i^{(m)}$ for all i is less than some small ϵ . The final estimates for performance statistics are then calculated. In our experience, convergence is fast and does not depend on the initial estimates of b_i .

2.6. Example of the Single-Segment Routing Model

To illustrate the performance and accuracy of the jump-over approximation, we consider the zone picking

Table 1. Performance Statistics for the Example with Varying Number of Totes N

N	$X(N)$ (in hours ⁻¹)								$E(T_{\mathcal{Z}}(N))$ (in seconds)							
	<i>Sim</i>	<i>Jump</i>	<i>CQN</i>	<i>YdK</i>	Error, %				<i>Sim</i>	<i>Jump</i>	<i>CQN</i>	<i>YdK</i>	Error, %			
					<i>Jump</i>	<i>CQN</i>	<i>YdK</i>						<i>Jump</i>	<i>CQN</i>	<i>YdK</i>	
10	104.4 (±0.16)	104.5	108.2	107.9	0.13	3.62	3.39		25.2 (±0.06)	25.3	27.1	28.6	0.12	7.27	13.15	
20	182.8 (±0.25)	182.9	206.5	204.9	0.04	12.93	12.06		29.9 (±0.08)	29.8	41.8	46.4	0.28	40.00	55.29	
30	234.3 (±0.52)	235.3	283.5	276.2	0.44	21.03	17.92		33.3 (±0.13)	33.1	72.8	86.0	0.58	119.07	158.47	
40	268.8 (±0.58)	269.8	326.2	313.4	0.40	21.39	16.61		35.5 (±0.08)	35.5	132.4	154.5	0.02	273.31	335.67	
50	291.5 (±0.39)	293.0	342.0	330.1	0.52	17.34	13.24		37.3 (±0.08)	37.3	216.8	240.4	0.06	481.65	544.82	
100	336.4 (±0.65)	338.6	354.9	350.1	0.67	5.50	4.07		42.4 (±0.22)	42.3	704.6	723.4	0.17	1,563.16	1,607.49	

N	$E(T_{\mathcal{C}}(N))$ (in seconds)								b_{z_1}						b_{z_2}		
	<i>Sim</i>	<i>Jump</i>	<i>CQN</i>	<i>YdK</i>	Error, %				<i>Sim</i>	<i>Jump</i>	Error, %	<i>Sim</i>	<i>Jump</i>	Error, %	<i>Sim</i>	<i>Jump</i>	Error, %
					<i>Jump</i>	<i>CQN</i>	<i>YdK</i>										
10	313.7 (±0.52)	313.4	300.0	300.0	0.08	4.37	4.37		0.01 (±0.00)	0.01	1.97	0.05 (±0.00)	0.05	0.62			
20	357.4 (±0.54)	357.3	300.0	300.0	0.04	16.07	16.07		0.07 (±0.00)	0.07	1.92	0.18 (±0.00)	0.18	0.06			
30	420.1 (±1.05)	418.7	300.0	300.0	0.34	28.59	28.59		0.16 (±0.00)	0.15	4.14	0.31 (±0.00)	0.31	0.27			
40	491.9 (±0.96)	490.4	300.0	300.0	0.32	39.02	39.02		0.24 (±0.00)	0.23	3.40	0.41 (±0.00)	0.41	0.23			
50	571.6 (±0.72)	568.8	300.0	300.0	0.49	47.51	47.51		0.32 (±0.00)	0.31	3.11	0.50 (±0.00)	0.50	0.41			
100	1017.7 (±1.93)	1,011.5	300.0	300.0	0.61	70.52	70.52		0.57 (±0.01)	0.55	4.41	0.72 (±0.00)	0.73	1.01			

system with two zones shown in Figure 2. There are 2^2 tote classes. The release probabilities are set to $\psi_0 = 0$ and $\psi_{\{z_1\}} = \psi_{\{z_2\}} = \psi_{\{z_1, z_2\}} = 1/3$, and the mean service times are $\mu_e^{-1} = 5$ seconds for the entrance/exit and $\mu_{z_1}^{-1} = \mu_{z_2}^{-1} = 15$ seconds for the zones. Conveyor delays are deterministic and equal to $\mu_{c_1}^{-1} = \mu_{c_2}^{-1} = \mu_{c_3}^{-1} = 100$ seconds. The number of order pickers d_{z_1} and d_{z_2} are equal to one, and the buffer sizes of the zones are $q_{z_1} = 2$ and $q_{z_2} = 1$, respectively.

Table 1 presents the average time in seconds a tote spends on the conveyor $E(T_{\mathcal{C}}(N)) = \sum_{i \in \mathcal{C}} E(T_i(n))$ and in zones $E(T_{\mathcal{Z}}(N)) = \sum_{i \in \mathcal{Z}} E(T_i(n))$ and the overall throughput rate per hour $X(N)$. These statistics are shown for the jump-over network (*Jump*), for the same closed queueing network with infinite buffers in the zones (*CQN*), and for the approximation of Yu and De Koster (2008) (*YdK*). *YdK* uses an open queueing network in its analysis. Using bisection, the arrival rate of this approximation is set such that the average number of totes in the open network is equal to N . The results show that the jump-over network produces more accurate results compared with the simulation of the original block-and-recirculate queueing network (*Sim*), in which the half width of the 95% confidence interval is given in brackets. In all cases, the algorithm stops after five iterations with $\epsilon = 10^{-3}$. Both *CQN* and *YdK* assume infinite buffers, which means that they cannot estimate the blocking probabilities. The run times for the *Jump*, *CQN*, and *YdK* methods are less than a second on a Core i7 with 2.4 GHz and 8 GB of RAM, whereas the simulation for $N = 100$ takes around 30 seconds (see Section 4 for more details on the simulation setup).

If the system contains a small number of totes N , the errors of the jump-over network are negligible and relatively small for *CQN* and *YdK*. This is obvious because almost no blocking occurs in the system; that is, only 5% of the totes that intend to visit the second zone are blocked. This means that the performance of *CQN* and *YdK* is similar to that of the jump-over network and the block-and-recirculate network. However, if the system contains a high number of totes, the blocking probability increases, and the totes have to recirculate more often.

If the number of totes in the system equals $N = 40$ or 50, blocking becomes more prominent. Because every zone is visited with the same frequency, more blocking occurs at zone 2 than at zone 1 because of differences in buffer sizes. Moreover, the system throughput time increases rapidly, whereas the throughput rate stabilizes because all the zones become saturated. *CQN* and *YdK* produce large errors in the average time a tote spends in the zones and at the conveyor nodes, which is due to the assumption of infinite buffers in the zones. This is not the case in the jump-over network. Because of recirculation, the conveyor nodes act as buffers for totes that cannot enter a zone. When $N = 100$, blocking negatively affects the performance of the system, and totes spend twice as long in the system compared with $N = 50$.

3. Multisegment Zone Picking Systems

This section presents the extension to multisegment zone-picking systems, which comprise three main parts: entrance/exit stations, conveyors, and zones. Figure 4 shows a zone picking system with four

Figure 4. (Color online) A Multisegment Zone Picking System with Four Segments and 11 Zones

segments and 11 zones. The workload control mechanism releases a tote, which travels to the first segment in which order lines have to be picked. The tote enters via the segment entrance station and stays in the segment until it has visited all required zones within the segment. When finished, the tote leaves the segment and is transported to another segment or to the system exit if the picking process has finished. The workload control mechanism controls the maximum number of totes in the system as well as the maximum number of totes within each segment. If a tote tries to enter a segment that is saturated, the control mechanism prevents it from entering. The blocked tote then skips the segment and stays on the main conveyor, potentially visiting other segments before again attempting to enter this segment. This is similar to zone blocking, but now blocking depends on the number of totes within an entire segment instead of in a single zone.

The multisegment zone-picking system is modeled as a closed queueing network with K segments. $\mathcal{E} = \{e_0, e_1, \dots, e_K\}$ denotes the set of entrance/exit stations, where e_0 is the system entrance/exit and e_k is the entrance of segment k , representing the conveyor connecting segment k with the main conveyor. Let $\mathcal{Z} = \bigcup_{k=1}^K \mathcal{Z}^k$ is the set of zones, where $\mathcal{Z}^k = \{z_1^k, \dots, z_{m_k}^k\}$ are the zones in segment k . The total number of

zones is $M = \sum_{k=1}^K m^k$. The set of conveyor nodes is $\mathcal{C} = \bigcup_{k=0}^K \mathcal{C}^k$, where $\mathcal{C}^0 = \{c_1^0, \dots, c_{K+1}^0\}$ are the main conveyor nodes and $\mathcal{C}^k = \{c_1^k, \dots, c_{m_k+1}^k\}$ are the conveyor nodes in segment k . Finally, $\mathcal{S} = \mathcal{E} \cup \mathcal{C} \cup \mathcal{Z}$ is the set of all nodes in the network. Figure 5 shows the topology of the queueing network with K segments.

The system is partitioned into $K + 1$ subsystems: $\{\mathcal{H}^0, \mathcal{H}^1, \dots, \mathcal{H}^K\}$, where $\mathcal{H}^0 = \{e_0\} \cup \mathcal{C}^0$ consists of the system entrance/exit and the nodes on the main conveyor, and $\mathcal{H}^k = \{e_k\} \cup \mathcal{C}^k \cup \mathcal{Z}^k$, the set of nodes belonging to the k th segment. We make the following assumptions:

- Each tote has a class $r \subseteq \mathcal{Z}$ of zones to be visited and $r^k \subseteq \mathcal{Z}^k$, $k = 1, \dots, K$, describes the zones a class r tote has to visit in segment k . A class r tote enters segment k if and only if $r^k \neq \emptyset$.
- Entrance station e_k to segment k is a delay node with an exponential delay with mean $1/\mu_{e_k}$, $k = 1, \dots, K$ that accounts for the time a tote needs for entering and leaving the segment.
- The maximum number of totes allowed in segment k is $N^k \leq N$, $k = 1, \dots, K$.

At system entrance e_0 , new totes of class $r \subseteq \mathcal{Z}$ are released with probability ψ_r . After release, a class r tote is transported from e_0 to the first main conveyor node c_1^0 . From c_k^0 , the tote is either transported to

Figure 5. (Color online) A Multisegment Zone Picking Queueing Network with K Segments

segment entrance e_k if $r^k \neq \emptyset$ or moved to the next main conveyor node c_{k+1}^0 . If the number of totes in segment k equals N^k , the tote skips segment k and also moves to c_{k+1}^0 while its class remains the same. If the tote enters segment k , it stays there until it has visited all required zones r^k . When the tote leaves segment k via $c_{m^k+1}^k$, its class changes from r upon entering segment k to $s = r \setminus r^k$ upon leaving. After visiting the last main conveyor node c_{K+1}^0 , all totes with $r \neq \emptyset$ are routed to exit e_0 and immediately replaced by a new one, waiting for release. The routing probabilities are formally described in Section EC.1.1.

The next step is to approximate the block-and-recirculate protocol by the jump-over blocking protocol in Section 3.1. The queueing network with jump-over blocking has a product-form stationary distribution, which is described in Section EC.1.2. The calculation of visit ratios is described in Section EC.1.3. Performance statistics of the jump-over network are

calculated in Section 3.2 using flow-equivalent servers (Chandy et al. 1975) and MVA. An iterative algorithm to estimate the blocking probabilities is presented in Section 3.3.

3.1. Jump-Over Network

Totes can be blocked either by a zone or by a segment. Zone blocking has been described in Section 2. This section focuses on segment blocking, illustrated in Figure 6. In the block-and-recirculate protocol (Figure 6(a)), a class r tote that intends to visit segment k , that is, $r^k \neq \emptyset$, either enters if the number of totes in segment k is below N^k or skips segment k . Class r totes skipping segment k maintain their class, and class r totes entering segment k always leave this segment as class $r \setminus r^k$ totes.

In the jump-over blocking protocol (Figure 6(b)), a class r tote also skips segment k when it is full and proceeds as a class $r \setminus r^k$ tote leaving segment k .

Figure 6. (Color online) Description of Segment Blocking in the Block-and-Recirculate Network and the Jump-Over Network

A Bernoulli trial then determines whether each tote of class $r \setminus r^k$ leaving segment k changes class or not. It maintains class $r \setminus r^k$ with probability $1 - B_k$ and reverts to class r otherwise, independent of whether the tote visited or skipped segment k . However, totes leaving segment k carry no information about which zones have been visited in segment k . To be able to revert to the correct class again, we add this information to the class description by including the initial class of the tote at the time of release from e_0 . Denote the new classes by $\bar{r} = \{h, r\}$, where $h \subseteq \mathcal{Z}$ is the initial class and $r \subseteq \mathcal{Z}$ is the current class of zones that still need to be visited. The initial class h only changes when the tote is released from e_0 . Hence, the routing probabilities of a class $\bar{s} = \{h, s\}$ tote leaving segment k , that is, $s^k = \emptyset$, are given by the following (cf. (9) and (10)):

$$\begin{aligned} p_{c_{m^k+1}^k, \bar{s}, c_{k+1}^0} &= 1 - B_k, & k = 1, \dots, K, \bar{s} = \{h, s\}, s^k = \emptyset, \\ p_{c_{m^k+1}^k, \bar{s}, c_{k+1}^0} &= B_k, & k = 1, \dots, K, \bar{s} = \{h, s\}, s^k = \emptyset, \\ \bar{r} &= \{h, s \cup h^k\}. \end{aligned}$$

The flows of class r and class $r \setminus r^k$ totes entering c_{k+1}^0 match under both protocols by choosing B_k as the fraction of totes skipping segment k in the block-and-recirculate network. In other words, B_k is the blocking probability of segment k under block and recirculate. It is estimated in Section 3.3.

3.2. Aggregation Technique

We can analyze the jump-over network by directly applying MVA as described in Section 2.4. However, it is computationally more efficient to first apply Norton's theorem by replacing all segments by flow-equivalent server centers with load-dependent exponential service rates (Chandy et al. 1975, Walrand 1983, Boucherie 1998) and then applying MVA. Norton's equivalent of the jump-over network is constructed by replacing each segment k by a flow equivalent server with exponential service rate

$$\mu_{FES_k}(n) = X^k(n), \quad n = 1, \dots, N^k, k = 1, \dots, K, \quad (54)$$

where $X^k(n)$ is the throughput of segment k in isolation when it contains n totes. Segment k is isolated by short-circuiting all nodes outside segment k . This

means that a tote leaving segment k through conveyor node $c_{m^k+1}^k$ is directly routed back to entrance e_k . The throughput of this isolated segment can be evaluated by MVA (where the entrance is now a delay node).

Figure 7 shows Norton's equivalent of Figure 5, which is identical to Figure 2(b) except that the zones are replaced by flow-equivalent servers. Norton's network can be analyzed by MVA, where Equation (46) should be replaced by the mean throughput time in the k th flow-equivalent server (Reiser 1981),

$$E(T_{FES_k}(n)) = \sum_{j=1}^{N^k-1} \frac{j}{\mu_{FES_k}(j)} \Pi_{FES_k}(j-1|n-1), \quad k=1, \dots, K, \quad (55)$$

where $\Pi_{FES_k}(j|n)$ are the marginal queue length probabilities of having j totes in the k th flow-equivalent server in a network with n circulating totes. These probabilities can be obtained through a balance argument, similar to in (49),

$$\begin{aligned} \Pi_{FES_k}(j|n) &= \frac{V_{FES_k} X(n)}{\mu_{FES_k}(j)} \Pi_{FES_k}(j-1|n-1), \\ j &= 1, \dots, N^k, k = 1, \dots, K, \end{aligned} \quad (56)$$

where V_{FES_k} is the visit ratio of the k th flow-equivalent server, which is equal to the visit ratio of entrance e_k . Equation (55) is obtained by applying Little's law and substitution of (56).

Performance statistics in Norton's network correspond to aggregated performance statistics of the segments, for example, $E(T_{FES_k}(N))$ is the mean throughput time of segment k , and $\Pi_{FES_k}(j|N)$ are the marginal probabilities of having j totes in segment k when there are N totes in the jump-over network. Detailed performance statistics of nodes within segments can be retrieved by disaggregation. Let $\pi_i^k(j|n)$ be the probability of j totes in node $i \in \mathcal{H}^k$ given there are n totes in segment k . The detailed queue length probabilities $\pi_i(j|N)$ are then given by (Baynat and Dallery 1993):

$$\pi_i(j|N) = \begin{cases} \Pi_i(j|N), & \text{if } i \in \mathcal{H}^0, \\ \sum_{l=1}^{N^k} \pi_i^k(j|l) \Pi_{FES_k}(l|N), & \text{if } i \in \mathcal{H}^k. \end{cases} \quad (57)$$

Figure 7. The Norton Equivalent of the Jump-Over Network

Note. Segments are replaced by a flow-equivalent server with load-dependent exponential service rates.

Performance statistics of all nodes can now be calculated as follows. Utilization of system entrance e_0 (with $d_{e_0} = 1$) and zones $i \in \mathcal{Z}$ is given by

$$\rho_i = 1 - \sum_{j=0}^{d_i-1} \frac{d_i - j}{d_i} \pi_i(j|N), \quad i \in e_0 \cup \mathcal{Z}. \quad (58)$$

The mean number of totes in node $i \in \mathcal{S}$ is given by

$$E(L_i(N)) = \sum_{j=1}^{\sigma_i} j \pi_i(j|N), \quad i \in \mathcal{S}, \quad (59)$$

where $\sigma_i = N$ if $i \in \mathcal{H}^0$, and $\sigma_i = N^k$ if $i \in \mathcal{H}^k \setminus \mathcal{Z}^k$ and $d_i + q_i$ if $i \in \mathcal{Z}$. Applying Little's law yields

$$E(T_i(N)) = E(L_i(N)) / V_i X(N), \quad i \in \mathcal{S}, \quad (60)$$

where $X(N)$ is the throughput rate of Norton's network.

3.3. Iterative Algorithm for Calculating the Blocking Probabilities

In the jump-over network, totes leaving segment k or zone i randomly change class according to probability B_k and b_i , respectively. The idea is to match B_k and b_i with the blocking probability of segment k and zone i in the block-and-recirculate network, which can be iteratively estimated as follows. Initially, $B_k^{(1)} = 0$, $k = 1, \dots, K$, and $b_i^{(1)} = 0$, $i \in \mathcal{Z}$. Then we calculate the marginal queue length probabilities using Equation (56) in Norton's network and estimate B_k as a fraction of arrivals finding N^k totes in flow-equivalent server k . By the arrival theorem,

$$B_k^{(m+1)} = \Pi_{FES_k}^{(m)}(N^k | N - 1), \quad k = 1, \dots, K, \quad (61)$$

where the superscript $^{(m)}$ corresponds to the iteration. Accordingly, by using the detailed marginal queue length probabilities of Equation (57), we get

$$\begin{aligned} b_i^{(m+1)} &= \pi_i^{(m)}(d_i + q_i | N^k - 1, N - 1), \\ &= \sum_{l=1}^{N^k-1} \pi_i^k(d_i + q_i | l) \Pi_{FES_k}(l | N - 1), \quad i \in \mathcal{Z}, \end{aligned} \quad (62)$$

which is the probability of finding a full buffer in zone i in a network with $N - 1$ totes, where at most $N^k - 1$ totes are allowed in segment k . Note that we apply a modification of the “usual” arrival theorem: an arriving tote in zone i not only sees the network in equilibrium without itself but *also* one in which the capacity of segment k containing zone i is reduced by one.

Subsequently, routing probabilities and visit ratios are recalculated and so on. This procedure is

repeated until the differences $B_k^{(m+1)} - B_k^{(m)}$ and $b_i^{(m+1)} - b_i^{(m)}$ for all k and i are less than some ϵ .

4. Numerical Results

We compare the results of the jump-over approximation with a discrete-event simulation of the block-and-recirculate network. This section is split into two parts. Section 4.1 is devoted to single-segment routing systems and Section 4.2 to multisegment routing systems. Both the jump-over network and the discrete-event simulation are implemented in Java. In each case, the simulation is run 10 times for 1,000,000 seconds, preceded by 10,000 seconds of initialization for the system to become stable. This guarantees that the width of the 95% confidence interval of the system throughput time is less than 1% of the mean value. All experiments are run on Core i7 with 2.4 GHz and 8 GB of RAM.

4.1. Single-Segment Systems

This section explores the performance of the approximation for the single-segment system. Table 2 lists the parameters of the test set. The number of zones M varies between one and eight, and the number of totes N varies between 10 and 80. We first assume that all zones and conveyor nodes are identical and that all tote classes are released into the system with equal probability. This ensures that the workload of all zones is balanced. In the test set, conveyor delays are deterministic and μ_i^{-1} , $i \in \mathcal{C}$ varies between 20 and 60 seconds. Picking times are exponential, and μ_i^{-1} , $i \in \mathcal{Z}$ varies between 10 and 30 seconds. The number of order pickers d_i , $i \in \mathcal{Z}$ and buffer places q_i , $i \in \mathcal{Z}$ varies between one and three and zero

Table 2. Parameters of the Test Set for the Single-Segment System

(a) Balanced test set (9,600 cases)	
Parameter	Value
Number of zones, M	1, 2, 3, 4, 5, 6, 7, 8
Number of totes, N	10, 20, 30, ..., 80
Conveyor delays, μ_i^{-1} , $i \in \mathcal{C}$	20, 30, 40, 50, 60
Mean picking times, μ_i^{-1} , $i \in \mathcal{Z}$	10, 15, 20, 25, 30
Number of order pickers, d_i , $i \in \mathcal{Z}$	1, 2, 3
Buffer size of a zone, q_i , $i \in \mathcal{Z}$	0, 1
(b) Imbalanced test set (224 cases)	
Parameter	Value
Number of zones, M	2, 3, 4, 5, 6, 7, 8
Number of totes, N	10, 20, 30, ..., 80
Mean picking times, μ_i^{-1} , $i \in \mathcal{Z}$	<ul style="list-style-type: none"> • 10, 10, 10, ... • 10, 12, 14, ... • 10, 15, 20, ... • 10, 20, 30, ...

Table 3. Results of the Balanced Test Set with a Varying Number of Zones M

M	Error % in system throughput				Error % in number of circulations				Error % in throughput times zones			
	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5
1	0.08	100.0	0.0	0.0	0.08	100.0	0.0	0.0	0.09	100.0	0.0	0.0
2	0.67	70.0	29.8	0.2	0.78	69.0	29.8	1.3	0.44	83.9	16.1	0.0
3	0.78	68.2	31.7	0.2	0.94	67.2	30.3	2.5	0.44	86.2	13.8	0.0
4	0.73	71.9	27.8	0.3	0.90	71.3	25.9	2.8	0.38	90.3	9.8	0.0
5	0.64	76.6	23.3	0.2	0.80	75.0	22.4	2.6	0.32	93.2	6.8	0.0
6	0.54	80.4	19.5	0.1	0.68	78.6	18.9	2.5	0.28	94.9	5.1	0.0
7	0.45	83.8	16.2	0.0	0.57	82.4	15.8	1.8	0.25	96.9	3.1	0.0
8	0.38	86.7	13.3	0.0	0.48	85.2	13.5	1.3	0.23	97.7	2.3	0.0

and one, respectively. In total, this leads to 9,600 cases.

We also examine the effect of workload imbalance resulting from differences in mean picking times among zones. In this test set, the deterministic delays $\mu_i^{-1}, i \in \mathcal{C}$ are equal to 30 seconds, and both the number of order pickers $d_i, i \in \mathcal{Z}$ and buffer places $q_i, i \in \mathcal{Z}$ are equal to one. Four different scenarios are created for the mean picking times. In the first scenario, the mean picking times are equal, whereas in the other three scenarios, they increase by either 2, 5, or 10 seconds per subsequent zone. This leads to an additional 224 cases. The run time per case for the analytical model is less than a second, whereas simulation takes at most 30 seconds for the larger systems.

The results of the balanced test set are summarized in Tables 3–6. Each table lists the average relative error between approximation and simulation of system throughput in hour⁻¹, the average number of circulations of a tote before moving to the exit, and the sum of mean throughput times of the zones. Each table also gives the percentage of cases that fall in three different error ranges. We can conclude from the results that the approximation produces very accurate results for the three performance statistics. The overall average error is 0.54% for the system throughput, 0.65% for the mean number of circulations, and 0.30% for the average mean throughput

times of the zones. Almost all errors are between 0–1%, with only a few larger than 5%.

Tables 3 and 4 show that the largest errors occur when the system has three or four zones and when the number of totes in the system is high. An explanation is that the probability of blockages increases with a lower number of zones M or with a higher number of totes N in the system. Moreover, if blocking is prevalent, more zones implies that the approximation needs to estimate more blocking probabilities. This creates more room for error. Eventually, M is high enough for blocking to be almost fully absent for any N . The approximation becomes exact because the network behaves precisely as the block-and-recirculate network, in which totes are hardly ever blocked.

Tables 5 and 6 show that the largest errors occur with low conveyor delays and high mean picking times. Here the product-form assumption that each node can be analyzed in isolation does not describe the real behavior adequately. For example, if a tote is blocked by a zone, it can circulate through the entire system and eventually encounter the zone still working on the same tote. This creates dependencies between successive visits to the nodes that are not captured by the approximation. However, this situation is unlikely in practice. The total recirculation time is usually much higher than the time a tote spends in a zone.

Table 4. Results of the Balanced Test Set with a Varying Number of Totes in the System N

N	Error % in system throughput				Error % in number of circulations				Error % in throughput times zones			
	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5
10	0.24	95.0	4.8	0.2	0.29	93.1	5.9	1.0	0.21	99.8	0.3	0.0
20	0.40	86.8	12.9	0.3	0.53	85.5	12.3	2.2	0.21	97.9	2.1	0.0
30	0.52	81.7	18.1	0.3	0.67	80.0	17.5	2.5	0.24	95.6	4.4	0.0
40	0.59	77.6	22.3	0.2	0.74	76.7	20.8	2.6	0.28	93.0	7.0	0.0
50	0.62	75.3	24.8	0.0	0.77	74.2	23.7	2.2	0.32	91.8	8.3	0.0
60	0.64	74.1	25.9	0.0	0.76	73.0	25.1	1.9	0.36	89.6	10.4	0.0
70	0.64	73.6	26.4	0.0	0.75	72.9	25.7	1.4	0.38	88.8	11.3	0.0
80	0.64	73.6	26.4	0.0	0.72	73.3	25.7	1.0	0.41	86.7	13.3	0.0

Table 5. Results of the Balanced Test Set with Varying Conveyor Delays $\mu_i^{-1}, i \in \mathcal{C}$

μ_i^{-1}	Error % in system throughput				Error % in number of circulations				Error % in throughput times zones			
	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5
20	0.91	66.5	33.0	0.5	1.21	65.3	28.1	6.7	0.47	85.4	14.6	0.0
30	0.64	74.1	25.9	0.0	0.79	72.7	25.2	2.2	0.33	91.0	9.0	0.0
40	0.47	81.4	18.6	0.0	0.55	80.3	19.4	0.4	0.27	94.4	5.6	0.0
50	0.36	86.3	13.7	0.0	0.41	85.5	14.5	0.0	0.23	96.3	3.8	0.0
60	0.29	90.2	9.8	0.0	0.31	89.2	10.8	0.0	0.21	97.3	2.7	0.0

Table 7 presents the results of the imbalanced test set. The errors of the three performance statistics are slightly larger than those of the balanced test set. In particular, the errors increase when there is more imbalance between the zones. Totes that need to visit the slowest zone now spend more time in the system because the probability of blockages is higher, which increases errors, as seen in the previous tables. Still, on average, the errors for the three statistics are well below 1%.

4.2. Multisegment Systems

We create a new test set for the multisegment system. Table 8 lists its parameters. In all test cases, the number of zones M equals 18, and the number of zones per segment m_k varies between three, six, and nine. Zones and conveyor nodes are identical within every segment, that is, $\mu_i^{-1} = 30, i \in \mathcal{C} \setminus \mathcal{C}^0$, $\mu_i^{-1} = 15, i \in \mathcal{Z}$, and $q_i = d_i = 1, i \in \mathcal{Z}$. Release probabilities ψ_r are the same for all r , and the service means of all entrances are equal to $\mu_i^{-1} = 5, i \in \mathcal{E}$. Picking times and system entrance times are exponential. Delays in conveyor nodes and segment entrances are deterministic. The number of totes in the system varies between 10 and 80, and the capacities of the segments N^k vary between 10 and 40 totes as long as $N \geq N^k$. The main conveyor times, $\mu_i^{-1}, i \in \mathcal{C}^0$ vary between 10 and 60. This leads to 1,320 test cases. The run time per case for the analytical model is around 10 seconds, whereas simulation takes at most one minute for larger systems.

The results of the multisegment test set are summarized in Tables 9 and 10. The overall average error is 0.21% for system throughput, 0.93% for the mean

number of circulations on the main conveyor, and 0.24% for the average throughput times of the zones. The tables show that the errors are the largest in cases with a low number of segments and a fast main conveyor. In these cases, totes are more likely to be blocked by a segment and subsequently need to recirculate on the main conveyor multiple times. As seen in the previous results, errors increase when there are more blockages in the system. Similar results can be seen when varying the segment capacities N^k .

Comparing the systems shows that, if the main conveyors are slow ($\mu_i^{-1} \geq 50$ seconds) and if the system contains a low number of totes ($N \leq 20$), the systems with $m^k = 9, k = 1, 2$ obtain the highest throughput because of less delay on the conveyors. However, if the segment capacity $N^k \leq 20$ is low, $m^k = 3, k = 1, \dots, 6$ has the highest throughput because the probability that a tote is blocked by a segment is lower, and less recirculation of totes is required.

A further validation for a real-life system with nonexponential picking times and multiple segments can be found in Section EC.2.

5. Conclusion and Further Research

In this paper, we study sequential zone picking systems with single-segment routing and those with multisegment routing. We propose a queueing network to estimate the throughput capacity. Because an exact analysis of this queueing network is not feasible, we approximate its blocking protocol with the jump-over protocol. This network admits a product-form solution. We use MVA and an aggregation technique to obtain accurate performance estimates. Results

Table 6. Results of the Balanced Test Set with Varying Mean Picking Times $\mu_i^{-1}, i \in \mathcal{Z}$

μ_i^{-1}	Error % in system throughput				Error % in number of circulations				Error % in throughput times zones			
	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5
10	0.24	93.0	7.0	0.0	0.23	92.7	7.3	0.0	0.17	98.2	1.8	0.0
15	0.40	84.9	15.1	0.0	0.46	83.5	16.1	0.4	0.23	95.5	4.5	0.0
20	0.55	78.4	21.6	0.0	0.67	76.8	21.7	1.5	0.30	92.7	7.3	0.0
25	0.68	72.9	27.0	0.2	0.86	71.8	25.3	2.9	0.37	90.1	9.9	0.0
30	0.80	69.3	30.3	0.4	1.05	68.1	27.3	4.5	0.43	87.8	12.2	0.0

Table 7. Results of the Imbalanced Test Set with Varying Mean Picking Times $\mu_i^{-1}, i \in \mathcal{I}$

μ_i^{-1}	Error % in system throughput				Error % in number of circulations				Error % in throughput times zones			
	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5
10,10,10,...	0.20	100.0	0.0	0.0	0.20	100.0	0.0	0.0	0.15	100.0	0.0	0
10,12,14,...	0.23	100.0	0.0	0.0	0.24	100.0	0.0	0.0	0.16	100.0	0.0	0.0
10,15,20,...	0.35	98.2	1.8	0.0	0.36	94.6	5.4	0.0	0.21	100.0	0.0	0.0
10,20,30,...	0.40	89.3	10.7	0.0	0.45	85.7	14.3	0.0	0.32	100.0	0.0	0.0

Table 8. Parameters of the Multisegment Routing Model Test Set (1,320 Cases)

Parameter	Value	Parameter	Value
Number of segments, K	2, 3, 4, 5, 6	Number of zones per segment, m_k	•9, 9
Number of totes, N	10, 20, ..., 80		•6, 6, 6
Mean main conveyor times, $\mu_i^{-1}, i \in \mathcal{C}^0$	10, 20, 30, 40, 50, 60		•3, 6, 3, 6
Segment capacity, $N^k, k = 1, \dots, K$	10, 15, 20, 25, 30, 35, 40		•3, 3, 6, 3, 3
			•3, 3, 3, 3, 3, 3

indicate that the relative error in the throughput estimate is typically less than 1% compared with simulation.

We suggest some directions for further research.

- Operational policies. The model can be used to evaluate and compare the throughput capacity of operational policies, such as order batching and order splitting, as in Yu and De Koster (2008). An optimization framework can be formulated for the

allocation of products to zones to maximize throughput capacity.

- Flexible order pickers. The model can be extended to study the impact of flexible order pickers in adjacent zones, helping each other when the workload in one of the zones is temporarily high.

- Merging of totes. When the zone picking system is heavily loaded, congestion can occur when streams of totes merge. For example, totes leaving a zone

Table 9. Results of the Multisegment Routing Test Set with a Varying Number of Zones per Segment m_k

m_k	Error % in system throughput				Error % in number of circulations				Error % in throughput times zones			
	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5
9,9	0.21	99.6	0.4	0.0	2.27	66.3	20.1	13.6	0.23	100.0	0.0	0.0
6,6,6	0.25	100.0	0.0	0.0	1.23	72.0	21.6	6.4	0.23	100.0	0.0	0.0
6,3,6,3	0.19	100.0	0.0	0.0	0.43	84.8	15.2	0.0	0.24	100.0	0.0	0.0
3,3,6,3,3	0.16	100.0	0.0	0.0	0.28	89.8	10.2	0.0	0.25	100.0	0.0	0.0
3,3,3,3,3,3	0.23	99.2	0.8	0.0	0.43	86.7	12.5	0.8	0.23	100.0	0.0	0.0

Table 10. Results of the Multisegment Routing Test Set with Varying Mean Conveyor Times $\mu_i^{-1}, i \in \mathcal{C}^0$

$\mu_i^{-1}, i \in \mathcal{C}^0$	Error % in system throughput				Error % in number of circulations				Error % in throughput times zones			
	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5	Average	0–1	1–5	> 5
10	0.28	99.1	0.9	0.0	2.23	66.8	22.3	10.9	0.23	100.0	0.0	0.0
20	0.24	100.0	0.0	0.0	1.15	75.5	18.6	5.9	0.23	100.0	0.0	0.0
30	0.21	100.0	0.0	0.0	0.77	77.3	18.2	4.5	0.24	100.0	0.0	0.0
40	0.19	99.5	0.5	0.0	0.58	83.6	14.5	1.8	0.24	100.0	0.0	0.0
50	0.18	100.0	0.0	0.0	0.45	86.8	11.8	1.4	0.24	100.0	0.0	0.0
60	0.16	100.0	0.0	0.0	0.37	89.5	10.0	0.5	0.24	100.0	0.0	0.0

have to wait for a sufficiently large open space on the conveyor before merging. This waiting time can be viewed as blocking after service and can be incorporated into the model to assess its impact on the throughput capacity (van der Gaast et al. 2018).

- External order arrivals. To estimate the throughput capacity, we assume that when a tote has collected all required items for a customer order, a new order tote can be released immediately; that is, there are always customer orders available. In an operational setting, the arrival rate λ of customer orders is lower than the throughput capacity, so it may happen that a new order is not available upon completion of a tote. Hence, the number of circulating totes is not always N , but can also be less. An appropriate model to study this situation is a *semiopen queueing network* (see Jia and Heragu (2009)), for which the proposed closed queueing network may be used as a building block as follows. For each population $n = 0, \dots, N$, the MVA algorithm in Sections 2.4 and 3.2 provides the throughput $X(n)$. Then the semiopen queueing network is replaced by a flow-equivalent server with service rate $\mu_n = X(n)$ for $n < N$ and $\mu_n = X(N)$ for $n \geq N$, and the resulting birth-and-death process with birth rate λ and death rate μ_n , can be solved to obtain relevant performance measures, such as mean order flow times.

Our approach to model and analyze queueing networks with blocking may be applied in many applications beyond zone picking systems, for example, end-of-aisle picking systems, AGV transportation systems, and vehicle-based compact storage systems.

References

- Adan IJBF, Van der Wal J (2011) Mean values techniques. Boucherie R, van Dijk N, eds. *Queueing Networks: A Fundamental Approach* (Springer, New York), 561–586.
- Balsamo S, De Nitto Personé V, Onvural R (2001) *Analysis of Queueing Networks with Blocking* (Springer, Boston).
- Baskett F, Chandy K, Muntz R, Palacios F (1975) Open, closed, and mixed networks of queues with different classes of customers. *J. ACM* 22(2):248–260.
- Baynat B, Dallery Y (1993) A unified view of product-form approximation techniques for general closed queueing networks. *Performance Evaluation* 18(3):205–224.
- Bolch G, Greiner S, de Meer H, Trivedi KS (2006) *Queueing Networks and Markov Chains: Modeling and Performance Evaluation with Computer Science Applications*, 2nd ed. (Wiley-Interscience, Hoboken, NJ).
- Boucherie RJ (1998) Norton's equivalent for queueing networks comprised of quasireversible components linked by state-dependent routing. *Performance Evaluation* 32(2):83–99.
- Chandy KM, Sauer CH (1980) Computational algorithms for product form queueing networks. *Comm. ACM* 23(10):573–583.
- Chandy KM, Herzog U, Woo L (1975) Parametric analysis of queueing networks. *IBM J. Res. Development* 19(1):36–42.
- Chao X, Miyazawa M (2000) Queueing networks with instantaneous movements: A unified approach by quasi-reversibility. *Adv. Appl. Probab.* 32(1):284–313.
- De Koster M (1994) Performance approximation of pick-to-belt orderpicking systems. *Eur. J. Oper. Res.* 72(3):558–573.
- De Koster M, Le-Duc T, Roodbergen KJ (2007) Design and control of warehouse order picking: A literature review. *Eur. J. Oper. Res.* 182(2):481–501.
- Drury J (1988) Toward more efficient order picking. Technical Report 1, The Institute of Materials Management, Cranfield, UK.
- Economou A, Fakinos D (1998) Product form stationary distributions for queueing networks with blocking and rerouting. *Queueing Systems* 30(3):251–260.
- Gu J, Goetschalckx M, McGinnis LF (2010) Research on warehouse design and performance evaluation: A comprehensive review. *Eur. J. Oper. Res.* 203(3):539–549.
- Henderson W, Taylor PG (2001) State-dependent coupling of quasireversible nodes. *Queueing Systems* 37(1):163–197.
- Hsieh YJ, Bozer YA (2005) Analytical modeling of closed-loop conveyors with load recirculation. *Computational Science and Its Applications - ICCSA 2005, Lecture Notes in Computer Science*, vol. 3483 (Springer, Berlin), 437–447.
- Jia J, Heragu S (2009) Solving semi-open queueing networks. *Oper. Res.* 57(2):391–401.
- Kelly FP (1979) *Reversibility and Stochastic Networks*, 1st ed. (Wiley, Chichester, UK).
- Le-Duc T, De Koster RMBM (2007) Travel time estimation and order batching in a 2-block warehouse. *Eur. J. Oper. Res.* 176(1):374–388.
- Melacini M, Perotti S, Tumino A (2010) Development of a framework for pick-and-pass order picking system design. *Internat. J. Adv. Manufacturing Tech.* 53(9):841–854.
- Osorio C, Bierlaire M (2009) An analytic finite capacity queueing network model capturing the propagation of congestion and blocking. *Eur. J. Oper. Res.* 196(3):996–1007.
- Papadopoulos HT, Heavey C, Browne J (1993) *Queueing Theory in Manufacturing Systems Analysis and Design* (Chapman and Hall, London).
- Park BC (2012) Order picking: Issues, systems and models. Manzini R, ed. *Warehousing in the Global Supply Chain: Advanced Models, Tools and Applications for Storage Systems*, 1st ed. (Springer-Verlag, London), 1–30.
- Perros HG (1994) *Queueing Networks with Blocking* (Oxford University Press, Inc., New York).
- Petersen CG (2000) An evaluation of order picking policies for mail order companies. *Production Oper. Management* 9(4):319–335.
- Petersen CG (2002) Considerations in order picking zone configuration. *Internat. J. Oper. Production Management* 22(7):793–805.
- Pittel B (1979) Closed exponential networks of queues with saturation: The Jackson-type stationary distribution and its asymptotic analysis. *Math. Oper. Res.* 4(4):357–378.
- Reiser M (1981) Mean-value analysis and convolution method for queue-dependent servers in closed queueing networks. *Performance Evaluation* 1(1):7–18.
- Reiser M, Lavenberg SS (1980) Mean-value analysis of closed multichain queueing networks. *J. ACM* 27(2):313–322.
- Schassberger R (1984) Decomposable stochastic networks: Some observations. *Model. Performance Evaluation Methodology* 60:135–150.
- Schmidt LC, Jackman J (2000) Modeling recirculating conveyors with blocking. *Eur. J. Oper. Res.* 124(2):422–436.
- Stidham S Jr (2002) Analysis, design, and control of queueing systems. *Oper. Res.* 50(1):197–216.
- van der Gaast JP, Adan IJBF, De Koster MBM (2018) Conveyor merges in zone picking systems: A tractable and accurate approximate model. *Transportation Sci.* 52(6):1428–1443.
- Van Dijk NM (1988) On Jackson's product form with "jump-over" blocking. *Oper. Res. Lett.* 7(5):233–235.
- Vanderlande (2007) Zone picking met VISION.ZPS. Product brochure, Vanderlande, Veghel, Netherlands.
- Walrand J (1983) A note on Norton's theorem for queueing networks. *J. Appl. Probab.* 20(2):442–444.
- Whitt W (1982) Approximating a point process by a renewal process I: Two basic methods. *Oper. Res.* 30(1):125–147.

- Wolff RW (1989) *Stochastic Modeling and the Theory of Queues*, 1st ed. (Prentice Hall, London).
- Yao DD, Buzacott JA (1987) Modeling a class of flexible manufacturing systems with reversible routing. *Oper. Res.* 35(1): 87–93.
- Yu M, De Koster R (2008) Performance approximation and design of pick-and-pass order picking systems. *IIE Trans.* 40(11): 1054–1069.
- Yu M, De Koster R (2009) The impact of order batching and picking area zoning on order picking system performance. *Eur. J. Oper. Res.* 198(2):480–490.

Jelmer P. van der Gaast is an assistant professor in the Department of Management Science at Fudan University, Shanghai. His research interests include warehouse operations, stochastic processes, optimization, and queueing theory.

René B. M. de Koster is a professor of logistics and operations management at Rotterdam School of Management,

Erasmus University. His research interests are warehousing, terminal, and behavioral operations.

Ivo J. B. F. Adan is a full professor in the sections operations, planning, accounting and control (Department of Industrial Engineering and Innovation Sciences) and dynamics and control (Department of Mechanical Engineering) at Eindhoven University of Technology and holds the Manufacturing Networks Chair. His expertise and tuition areas include probability theory/statistics, operations research, manufacturing networks, stochastic operations research, and queueing models.

Jacques A. C. Resing is an assistant professor in the stochastic operations research group at Eindhoven University of Technology. His research is, in general, focused on applied probability and, in particular, on queueing theory. Among others, he studies several polling systems, fluid queues, and tandem queues.