University of Groningen

How significant is vertical ground motion from low magnitude earthquakes?

van Ginkel, Janneke; Ruigrok, Elmer; Herber, Rien

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version

Publisher's PDF, also known as Version of record

Publication date:
2020

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

van Ginkel, J., Ruigrok, E., & Herber, R. (2020). *How significant is vertical ground motion from low magnitude earthquakes?* 5505. Abstract from EGU General Assembly 2020.
<http://adsabs.harvard.edu/abs/2020EGUGA..22.5505V>

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

EGU2020-5505

<https://doi.org/10.5194/egusphere-egu2020-5505>

EGU General Assembly 2020

© Author(s) 2020. This work is distributed under the Creative Commons Attribution 4.0 License.

How significant is vertical ground motion from low magnitude earthquakes?

Janneke van Ginkel^{1,2}, Elmer Ruigrok^{2,3}, and Rien Herber¹

¹ESRIG, Groningen University, Groningen, the Netherlands (j.a.van.ginkel@rug.nl)

²R&D Seismology and Acoustics, Royal Netherlands Meteorological Institute, De Bilt, The Netherlands

³Department of Earth Sciences, Utrecht University, Utrecht, The Netherlands

Up to now, almost all of the ground motion modeling and hazard assessment for seismicity in the Netherlands focuses on horizontal motion. As a rule of thumb, the strength of vertical ground motions is taken as 2/3 of that of horizontal ground motions. In reality of course, amplifications and V/H ratios are site-dependent and thus vary regionally. Recent studies have indeed shown that vertical ground motion is not always simply 2/3 of the horizontal motion. However, these studies are performed in areas with high magnitude ($M_w > 5.0$) earthquakes and the question is whether vertical motion is relevant to be included in seismic hazard assessment for low magnitude earthquakes (to date, max $M_w = 3.6$ in Groningen).

In the Netherlands, the top part of the soils is practically always unconsolidated, so the elastic waves generated by deeper (~3000m) seated earthquakes will be subject to transformation when arriving in these layers. Recordings over a range of depth levels in the Groningen borehole network show the largest amplification to occur in the upper 50 meters of the sedimentary cover. We not only observe a strong amplification from shear waves on the horizontal components, but also from longitudinal waves on the vertical component. A better understanding of vertical motion of low magnitude earthquakes aims to support the design of re-enforcement measures for buildings in areas affected by low magnitude seismicity. Furthermore, interference between the longitudinal -and shear waves might contribute to damage on structures.

This study presents observations of longitudinal wave amplification in the frequency band 1-10 Hz, corresponding to resonance periods of Dutch buildings. From 19 seismic events, with a minimum of magnitude two, we retrieved transfer functions (TFs) from the vertical component, showing a strong site response at certain locations. In addition, we calculate event V/H ratios and VH factors from the surface seismometer. These results are compared with the TFs and show a similar pattern in terms of site response. Furthermore, the sites with highest vertical amplification correspond to very low (800-900 m/s) P-wave velocities. Our study shows that vertical amplification is very site dependent. However, the question whether the vertical motion is significant enough to form a real hazard can only be answered through cooperation between seismologist and structural engineer.

How to cite: van Ginkel, J., Ruigrok, E., and Herber, R.: How significant is vertical ground motion from low magnitude earthquakes?, EGU General Assembly 2020, Online, 4–8 May 2020, EGU2020-5505, <https://doi.org/10.5194/egusphere-egu2020-5505>, 2020