University of Groningen

Towards a minimal order distributed observer for linear systems

Han, Weixin; Trentelman, Harry L.; Wang, Zhenhua; Shen, Yi

Published in:
System and Control Letters

DOI:
[10.1016/j.sysconle.2018.02.011](https://doi.org/10.1016/j.sysconle.2018.02.011)

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version
Publisher's PDF, also known as Version of record

Publication date:
2018

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

Han, W., Trentelman, H. L., Wang, Z., & Shen, Y. (2018). Towards a minimal order distributed observer for linear systems. *System and Control Letters*, 114, 59 - 65. <https://doi.org/10.1016/j.sysconle.2018.02.011>

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Towards a minimal order distributed observer for linear systems

Weixin Han^a, Harry L. Trentelman^b, Zhenhua Wang^{a,*}, Yi Shen^a^a Department of Control Science and Engineering, Harbin Institute of Technology, Harbin, 150001, PR China^b Johann Bernoulli Institute for Mathematics and Computer Science, University of Groningen, 9700 AK Groningen, The Netherlands

ARTICLE INFO

Article history:

Received 7 August 2017

Received in revised form 9 February 2018

Accepted 20 February 2018

Available online 22 March 2018

Keywords:

Distributed estimation
Linear system observers
Minimal order
LMI's
Sensor networks

ABSTRACT

In this paper we consider the distributed estimation problem for continuous-time linear time-invariant (LTI) systems. A single linear plant is observed by a network of local observers. Each local observer in the network has access to only part of the output of the observed system, but also receives information on the state estimates of its neighbors. Each local observer should in this way generate an estimate of the plant state. In this paper we study the problem of existence of a *reduced order* distributed observer. We show that if the observed system is observable and the network graph is a strongly connected directed graph, then a distributed observer exists with state space dimension equal to $Nn - \sum_{i=1}^N p_i$, where N is the number of network nodes, n is the state space dimension of the observed plant, and p_i is the rank of the output matrix of the observed output received by the i th local observer. In the case of a single observer, this result specializes to the well-known minimal order observer in classical observer design.

© 2018 Elsevier B.V. All rights reserved.

1. Introduction

Recently, there has been much interest in the problem of designing distributed observers for estimation of the state of a given linear time invariant plant. Whereas the classical observer problem is to find a single observer that receives the entire measured plant output in order to generate this state estimate, in the distributed version the aim is to find a given number of local observers that can communicate according to an a priori given network graph (see Fig. 1 for an illustration). Each of the local observers in the network receives only part of the plant output, but also information on the state estimates of its neighbors. Each local observer should in this way generate an estimate of the plant state. Thus, the problem of finding a distributed observer can be interpreted as the problem of finding a single observer that consists of a given number of local observers, interconnected by means of an a priori given network graph. Since each of the local observers receives only part of the plant output, properties like observability or detectability that might hold for the original plant output do no longer hold for the partial output, and hence classical observer design is not applicable for the local observer.

Among the many contributions on the distributed observer problem we mention [1,2] and [3]. In particular, in [3–5] a state augmented observer was constructed to cast the distributed estimation problem as a problem of decentralized stabilization, using the notion of fixed modes [6]. These references only discuss discrete-time systems. More recently, in [7], the idea of putting

the distributed observer problem in the context of decentralized control was applied to continuous time plants. In [2,8,9] local Luenberger observers at each node were constructed, based on applying the Kalman observable decomposition. There, the observer reconstructs a certain portion of the state solely by using its own measurements, and uses consensus dynamics to estimate the unobservable portions of the state at each node. Specifically, in [1] two observer gains were designed to achieve distributed state estimation, one for local measurements and the other for the information exchange. In [10], a simple LMI based approach was proposed for the design of distributed observers.

A standard result in classical observer design states that if the plant is observable, then an observer with arbitrary fast error convergence exists of order equal to the order of the plant, say n , minus the rank of the output matrix, say p , [11]. It was argued in [12] that indeed $n - p$ is the minimal order for state observers. Of course, similarly one can address the issue of existence of a reduced, or even minimal, order distributed observer. This issue will be the topic of the present paper. We assume that our plant is a continuous-time LTI system

$$\begin{aligned}\dot{x} &= Ax \\ y &= Cx\end{aligned}\tag{1}$$

where $x \in \mathbb{R}^n$ is the state and $y \in \mathbb{R}^m$ is the measurement output. We partition the output y as

$$y = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_N \end{bmatrix}$$

* Corresponding author.

E-mail addresses: h.l.trentelman@rug.nl (H.L. Trentelman), zhenhua.wang@hit.edu.cn (Z. Wang).

Fig. 1. Framework for distributed state estimation.

where $y_i \in \mathbb{R}^{m_i}$ and $\sum_{i=1}^N m_i = m$. Accordingly, we partition the output matrix as

$$C = \begin{bmatrix} C_1 \\ C_2 \\ \vdots \\ C_N \end{bmatrix}$$

with $C_i \in \mathbb{R}^{m_i \times n}$. In addition, a directed graph with N nodes is given. Each node in the graph will carry a local observer. The local observer at node i has only access to the measurement $y_i = C_i x$ and to the state estimates of its neighbors, including itself. In this paper, a standing assumption will be that the communication graph is strongly connected. We will also assume that the pair (C, A) is observable. For the discrete time case, it was shown in [5] that a distributed observer of order $Nn + N - 1$ exists. This bound was re-established in [7] for continuous time plants. Again for the discrete time case, in [9] it was shown that a distributed observer exists of order Nn . Also in [1], under certain assumptions, a dynamic order Nn was shown to be sufficient. More recently, in our paper [10] we reconfirmed that for the continuous time case a dynamic order Nn suffices.

In the present paper we will improve all sufficient dynamic orders established up to now and as our main result show that, for any desired error convergence rate, a distributed observer exists of dynamic order equal to $Nn - \sum_{i=1}^N p_i$, where p_i is the rank of the local output matrix C_i . This result extends in a natural way the minimal order $n - p$ for a single, non-distributed observer, with the rank of the output matrix C .

2. Preliminaries and problem formulation

2.1. Preliminaries

Notation: The rank of a given matrix M is denoted by $\text{rank } M$. If M has full column rank m then $M^\dagger = (M^T M)^{-1} M^T$ denotes its Moore–Penrose inverse, so $M^\dagger M = I_m$. The identity matrix of dimension N will be denoted by I_N . The vector $\mathbf{1}_N$ denotes the N -dimensional column vector comprising of all ones. For a symmetric matrix P , $P > 0$ ($P < 0$) means that P is positive (negative) definite. For a set $\{A_1, A_2, \dots, A_N\}$ of matrices, we use $\text{diag}\{A_1, A_2, \dots, A_N\}$ to denote the block diagonal matrix with the A_i 's along the diagonal, and the matrix $[A_1^T \ A_2^T \ \dots \ A_N^T]^T$ is denoted by $\text{col}(A_1, A_2, \dots, A_N)$. The Kronecker product of the matrices M_1 and M_2 is denoted by $M_1 \otimes M_2$. In this paper, $\mathbb{R}^n$ will denote the n -dimensional Euclidean space. For a $p \times n$ matrix A , $\ker A := \{x \in \mathbb{R}^n \mid Ax = 0\}$ and $\text{im } A := \{Ax \mid x \in \mathbb{R}^n\}$ will denote the kernel and image of A , respectively. If $\mathcal{V}$ is a subspace of $\mathbb{R}^n$, then $\mathcal{V}^\perp$ will denote the orthogonal complement of $\mathcal{V}$ with respect to the standard inner product in $\mathbb{R}^n$.

In this paper, a weighted directed graph is denoted by $\mathcal{G} = (\mathcal{N}, \mathcal{E}, \mathcal{A})$, where $\mathcal{N} = \{1, 2, \dots, N\}$ is a finite nonempty set of nodes, $\mathcal{E} \subset \mathcal{N} \times \mathcal{N}$ is an edge set of ordered pairs of nodes, and $\mathcal{A} = [a_{ij}] \in \mathbb{R}^{N \times N}$ denotes the adjacency matrix. The (j, i) th entry

a_{ji} is the weight associated with the edge (i, j) . We have $a_{ji} \neq 0$ if and only if $(i, j) \in \mathcal{E}$. Otherwise $a_{ji} = 0$. An edge $(i, j) \in \mathcal{E}$ designates that the information flows from node i to node j . A directed path from node i_1 to i_l is a sequence of edges (i_k, i_{k+1}) , $k = 1, 2, \dots, l-1$ in the graph. A directed graph $\mathcal{G}$ is strongly connected if between any pair of distinct nodes i and j in $\mathcal{G}$, there exists a directed path from i to j , $i, j \in \mathcal{N}$.

The Laplacian $\mathcal{L} = [l_{ij}] \in \mathbb{R}^{N \times N}$ of $\mathcal{G}$ is defined as $\mathcal{L} := \mathcal{D} - \mathcal{A}$, where the i th diagonal entry of the diagonal matrix $\mathcal{D}$ is given by $d_i = \sum_{j=1}^N a_{ji}$. By construction, $\mathcal{L}$ has a zero eigenvalue with a corresponding eigenvector $\mathbf{1}_N$ (i.e., $\mathcal{L}\mathbf{1}_N = 0_N$), and if the graph is strongly connected, its algebraic multiplicity is equal to one and all the other eigenvalues lie in the open right-half complex plane.

For strongly connected graphs $\mathcal{G}$, we now review the following lemma.

Lemma 1 ([13–15]). Assume $\mathcal{G}$ is a strongly connected directed graph. Then there exists a unique positive row vector $r = [r_1, \dots, r_N]$ such that $r\mathcal{L} = 0$ and $r\mathbf{1}_N = N$. Define $R := \text{diag}\{r_1, \dots, r_N\}$. Then $\hat{\mathcal{L}} := R\mathcal{L} + \mathcal{L}^T R$ is semi-definite, $\mathbf{1}_N^T \hat{\mathcal{L}} = 0$ and $\hat{\mathcal{L}}\mathbf{1}_N = 0$.

We note that $R\mathcal{L}$ is the Laplacian of the balanced directed graph obtained by adjusting the weights in the original graph. The matrix $\hat{\mathcal{L}}$ is the Laplacian of the undirected graph obtained by taking the union of the edges and their reversed edges in this balanced digraph. This undirected graph is called the mirror of this balanced graph [13].

2.2. Problem formulation and main result

Consider the continuous-time LTI system (1), where $x \in \mathbb{R}^n$ is the state and $y \in \mathbb{R}^m$ is the measurement output. As explained in the introduction we partition the output y as $y = \text{col}(y_1, \dots, y_N)$, where $y_i \in \mathbb{R}^{m_i}$ and $\sum_{i=1}^N m_i = m$. Accordingly, $C = \text{col}(C_1, \dots, C_N)$ with $C_i \in \mathbb{R}^{m_i \times n}$. Here, the portion $y_i = C_i x$ is assumed to be the only output information that can be acquired by node i in the given network graph $\mathcal{G}$. The rank of the local output matrix C_i will be denoted by p_i .

In this paper, a standing assumption will be that the communication graph $\mathcal{G}$ is a strongly connected directed graph. We will also assume that the pair (C, A) is observable. However, (C_i, A) is not assumed to be observable or detectable.

We will design a distributed observer for the system (1) with the given communication network $\mathcal{G}$. The distributed observer will consist of N local observers, and the local observer at node i will have dynamics of the following form:

$$\dot{z}_i = N_i z_i + L_i y_i + \gamma r_i M_i \sum_{j=1}^N a_{ij} (\hat{x}_j - \hat{x}_i) \quad (2)$$

$$\hat{x}_i = P_i z_i + Q_i y_i$$

where $i \in \mathcal{N}$, $z_i \in \mathbb{R}^{n-p_i}$ is the state of the local observer, $\hat{x}_i \in \mathbb{R}^n$ is the estimate of plant state at node i , a_{ij} is the (i, j) th entry of the adjacency matrix $\mathcal{A}$ of the given network, r_i is defined as in Lemma 1, $\gamma \in \mathbb{R}$ is a coupling gain to be designed, $N_i \in \mathbb{R}^{(n-p_i) \times (n-p_i)}$, $L_i \in \mathbb{R}^{(n-p_i) \times m_i}$, $M_i \in \mathbb{R}^{(n-p_i) \times n}$, $P_i \in \mathbb{R}^{n \times (n-p_i)}$ and $Q_i \in \mathbb{R}^{n \times m_i}$ are gain matrices to be designed.

The objective of distributed state estimation is to design a network of local observers (2) that cooperatively estimate the state of the plant (1). Such network of local observers is said to achieve *omniscience asymptotically*, defined as follows:

Definition 2 ([5]). A distributed observer (2) is said to achieve *omniscience asymptotically* if for all initial conditions on (1) and (2) we have

$$\lim_{t \rightarrow \infty} (\hat{x}_i(t) - x(t)) = 0 \quad (3)$$

for all $i \in \mathcal{N}$, i.e. the state estimate maintained by each node asymptotically converges to the true state of the plant.

The main result of this paper is the following:

Theorem 3. Assume that (C, A) is observable and that the network graph $\mathcal{G}$ is a strongly connected directed graph. Let $\alpha \geq 0$ be a desired error convergence rate. Then there exists a distributed observer (2) that achieves omniscience asymptotically and all error trajectories converge to zero with convergence rate at least α . Such distributed observer exists with state space dimension $Nn - \sum_{i=1}^N p_i$, where $p_i := \text{rank } C_i$.

In the remainder of this paper we will prove this result by outlining how to design a desired distributed observer.

3. Design of the distributed observer

To design a distributed observer of the form (2), we make a full rank factorization for each local output matrix C_i . Recall that $\text{rank } C_i = p_i$ and factorize $C_i = D_i F_i$ with $D_i \in \mathbb{R}^{m_i \times p_i}$ full column rank and $F_i \in \mathbb{R}^{p_i \times n}$ full row rank. Recall that $D_i^\dagger = (D_i^T D_i)^{-1} D_i^T$. Since $y_i = C_i x$, we have

$$\tilde{y}_i := D_i^\dagger y_i = F_i x, \quad (4)$$

where $\tilde{y}_i \in \mathbb{R}^{p_i}$ represents a virtual local output. Denote $F = \text{col}(F_1, \dots, F_N)$. Clearly, (F, A) is observable, but for $i \in \mathcal{N}$, (F_i, A) is not necessarily observable or detectable. To proceed, we introduce orthogonal transformations that yield observability decompositions for the pairs (F_i, A) . For $i \in \mathcal{N}$, let T_i be an orthogonal matrix such that the matrices A and F_i are transformed by the state space transformation T_i into the form

$$T_i^T A T_i = \begin{bmatrix} A_{i11} & A_{i12} & 0 \\ A_{i21} & A_{i22} & 0 \\ A_{i31} & A_{i32} & A_{iu} \end{bmatrix}, \quad F_i T_i = \begin{bmatrix} E_i & 0 & 0 \end{bmatrix} \quad (5)$$

where $A_{i11} \in \mathbb{R}^{p_i \times p_i}$, $A_{i12} \in \mathbb{R}^{p_i \times (v_i - p_i)}$, $A_{i21} \in \mathbb{R}^{(v_i - p_i) \times p_i}$, $A_{i22} \in \mathbb{R}^{(v_i - p_i) \times (v_i - p_i)}$, $A_{i31} \in \mathbb{R}^{(n - v_i) \times p_i}$, $A_{i32} \in \mathbb{R}^{(n - v_i) \times (v_i - p_i)}$, $A_{iu} \in \mathbb{R}^{(n - v_i) \times (n - v_i)}$, $E_i \in \mathbb{R}^{p_i \times p_i}$ is a non-singular matrix, and $n - v_i$ is the dimension of the unobservable subspace of the pair (F_i, A) .

For convenience, denote

$$A_{io} = \begin{bmatrix} A_{i11} & A_{i12} \\ A_{i21} & A_{i22} \end{bmatrix}, \quad A_{ir} = \begin{bmatrix} A_{i31} & A_{i32} \end{bmatrix}, \quad F_{io} = \begin{bmatrix} E_i & 0 \end{bmatrix}, \quad (6)$$

where $A_{io} \in \mathbb{R}^{v_i \times v_i}$, $A_{ir} \in \mathbb{R}^{(n - v_i) \times v_i}$, $F_{io} \in \mathbb{R}^{p_i \times v_i}$. Then clearly

$$T_i^T A T_i = \begin{bmatrix} A_{io} & 0 \\ A_{ir} & A_{iu} \end{bmatrix}, \quad F_i T_i = \begin{bmatrix} F_{io} & 0 \end{bmatrix}. \quad (7)$$

By construction, the pair (F_{io}, A_{io}) is observable. Furthermore, it can be checked using the Hautus test that the pair (A_{i12}, A_{i22}) is also observable. Since E_i is nonsingular, then also the pair $(E_i A_{i12}, A_{i22})$ is observable.

In addition, if we partition $T_i = [T_{i1} \quad T_{i2}]$, where T_{i1} consists of the first v_i columns of T_i , then the unobservable subspace is given by $\text{im } T_{i2} = \ker O_{Fi}$, where $O_{Fi} = \text{col}(F_i, F_i A, \dots, F_i A^{n-1})$. Note that $\text{im } T_{i1} = (\ker O_{Fi})^\perp$.

We now proceed with defining the gain matrices P_i and Q_i in the output equation of (2). For $i \in \mathcal{N}$, define $S_i \in \mathbb{R}^{n \times (n - p_i)}$ and $K_i \in \mathbb{R}^{n \times m_i}$ by

$$S_i := \begin{bmatrix} 0 \\ I_{n - p_i} \end{bmatrix} \quad \text{and} \quad K_i := \begin{bmatrix} E_i^{-1} \\ H_i \\ 0 \end{bmatrix} D_i^\dagger. \quad (8)$$

Here, $H_i \in \mathbb{R}^{(v_i - p_i) \times p_i}$ still needs to be defined. Now define

$$T_{is} := T_i S_i \quad (9)$$

as the $n \times (n - p_i)$ matrix consisting of the last $n - p_i$ columns of the orthogonal matrix T_i . Next define

$$P_i := T_{is} \quad \text{and} \quad Q_i := T_i K_i. \quad (10)$$

To analyze and further synthesize the local observer (2), we define the local estimation error of the i th observer as

$$e_i := \hat{x}_i - x. \quad (11)$$

Using the definitions (10) and combining (1) and (2) shows that e_i satisfies:

$$\begin{aligned} \dot{e}_i &= P_i \dot{z}_i + Q_i \dot{y}_i - \dot{x} \\ &= T_{is} \dot{z}_i + T_i K_i \dot{y}_i - \dot{x} \\ &= T_{is} \left(N_i \dot{z}_i + L_i y_i + \gamma r_i M_i \sum_{j=1}^N a_{ij} (\hat{x}_j - \hat{x}_i) \right) + (T_i K_i C_i - I) A x \\ &= T_{is} \left(N_i S_i^T (T_i^T e_i - K_i y_i + T_i^T x) + L_i y_i + \gamma r_i M_i \right. \\ &\quad \times \left. \sum_{j=1}^N a_{ij} (\hat{x}_j - \hat{x}_i) \right) + (T_i K_i C_i - I) A x \\ &= T_{is} N_i S_i^T T_i^T e_i + \gamma r_i T_{is} M_i \sum_{j=1}^N a_{ij} (e_j - e_i) \\ &\quad + T_i ((S_i L_i - S_i N_i S_i^T K_i) D_i F_i T_i + S_i N_i S_i^T \\ &\quad + (K_i D_i F_i T_i - I) T_i^T A T_i) T_i^T x. \end{aligned} \quad (12)$$

As a first step to achieve stable error dynamics it is required that the right hand side of the differential equation (12) does not depend on the state x . This can be achieved by choosing the local observer gain matrices N_i and L_i in such a way that

$$(S_i L_i - S_i N_i S_i^T K_i) D_i F_i T_i + S_i N_i S_i^T + (K_i D_i F_i T_i - I) T_i^T A T_i = 0. \quad (13)$$

It can be checked by straightforward verification that (13) is achieved by choosing

$$N_i = \begin{bmatrix} A_{i22} - H_i E_i A_{i12} & 0 \\ A_{i32} & A_{iu} \end{bmatrix}, \quad (14)$$

$$L_i = \begin{bmatrix} A_{i21} - H_i E_i A_{i11} \\ A_{i31} \end{bmatrix} E_i^{-1} D_i^\dagger + N_i S_i^T K_i. \quad (15)$$

Here, again we note that $H_i \in \mathbb{R}^{(v_i - p_i) \times p_i}$ still needs to be defined. With this choice of N_i and L_i , the local error satisfies the differential equation

$$\dot{e}_i = T_{is} N_i T_{is}^T e_i + \gamma r_i T_{is} M_i \sum_{j=1}^N a_{ij} (e_j - e_i). \quad (16)$$

Let $e := \text{col}(e_1, e_2, \dots, e_N)$ be the joint vector of errors. Define

$$T_s := \text{diag}\{T_{1s}, \dots, T_{Ns}\}, \quad (17)$$

$$M = \text{diag}\{M_1, \dots, M_N\}, \quad (18)$$

$$N = \text{diag}\{N_1, \dots, N_N\}. \quad (19)$$

Clearly then, each global error trajectory satisfies the differential equation

$$\dot{e} = (T_s N T_s^T - \gamma T_s M (R \mathcal{L} \otimes I_n)) e, \quad (20)$$

where R is as defined in Lemma 1.

Note that $\text{im } T_s$ is an invariant subspace for the differential equation (20). Even more, it can be shown that each feasible global error trajectory e lives in the subspace $\text{im } T_s$. We state this as a lemma:

Lemma 4. Assume that the gain matrices P_i , Q_i , N_i and L_i are given by (10), (8), (14) and (15). Let $e := \text{col}(e_1, e_2, \dots, e_N)$ be the joint vector

of errors, with for $i \in \mathcal{N}$ the local error equal to $e_i = \hat{x}_i - x$, where x is a trajectory of the plant (1) and $\hat{x}_i$ satisfies (2). Then $e(t) \in \text{im } T_s$ for all $t \in \mathbb{R}$.

Proof. A proof of Lemma 4 is given in Appendix A. $\square$

From Lemma 4 we infer that the distributed observer (2) achieves omniscience asymptotically (3) if each solution e of (20) such that $e(t) \in \text{im } T_s$ for all $t \in \mathbb{R}$ converges to zero as t runs off to infinity.

Up to now, in the to be designed local observer (2) we have specified the gain matrices P_i , Q_i , N_i and L_i . However, Q_i , N_i and L_i still depend on the parameter matrix $H_i \in \mathbb{R}^{(v_i-p_i) \times p_i}$ that has to be specified. Also the matrix M_i and coupling gain γ still need to be specified. In order to proceed, we state the following two lemmas. The first of these is standard:

Lemma 5 ([16]). For a strongly connected directed graph $\mathcal{G}$, zero is a simple eigenvalue of $\hat{\mathcal{L}} = \mathcal{R}\mathcal{L} + \mathcal{L}^T\mathcal{R}$ introduced in Lemma 1. Furthermore, its eigenvalues can be ordered as $\lambda_1 = 0 < \lambda_2 \leq \lambda_3 \leq \dots \leq \lambda_N$. Furthermore, there exists an orthogonal matrix $U = \begin{bmatrix} \frac{1}{\sqrt{N}}\mathbf{1}_N & U_2 \end{bmatrix}$, where $U_2 \in \mathbb{R}^{N \times (N-1)}$, such that $U^T(\mathcal{R}\mathcal{L} + \mathcal{L}^T\mathcal{R})U = \text{diag}\{0, \lambda_2, \dots, \lambda_N\}$.

Our second lemma was proven in [10]. In order to make this paper self contained, we include the proof in Appendix B.

Lemma 6. Let $\mathcal{L}$ be the Laplacian matrix associated with the strongly connected directed graph $\mathcal{G}$. For all $g_i > 0$, $i \in \mathcal{N}$, there exists $\epsilon > 0$ such that

$$T^T((\mathcal{R}\mathcal{L} + \mathcal{L}^T\mathcal{R}) \otimes I_n)T + G > \epsilon I_{nN}, \quad (21)$$

where $T = \text{diag}\{T_1, \dots, T_N\}$, R is defined as in Lemma 1, $G = \text{diag}\{G_1, \dots, G_N\}$, and $G_i = \begin{bmatrix} g_i I_{v_i} & 0 \\ 0 & 0_{n-v_i} \end{bmatrix}$, $i \in \mathcal{N}$.

The following lemma now deals with the existence of a distributed observer of the form (2) that achieves omniscience asymptotically with an a priori given error convergence rate. A condition for its existence is expressed in terms of solvability of a system of N LMI's. Solutions to these LMI's yield the required gain matrices. Let $r_i > 0$, $i \in \mathcal{N}$, be as in Lemma 1. Let $g_i > 0$, $i \in \mathcal{N}$, and $\epsilon > 0$ be such that (21) holds. Let $\gamma \in \mathbb{R}$. Finally, let $\alpha \geq 0$ be a desired error convergence rate. Recall the definitions (8) and (9) for S_i and T_{is} . We have the following:

Lemma 7. There exist gain matrices N_i , L_i , M_i , P_i and Q_i , $i \in \mathcal{N}$, such that the distributed observer (2) achieves omniscience asymptotically and all solutions of the error system (20) converge to zero with convergence rate at least α if there exist positive definite matrices $\mathcal{P}_{ie} \in \mathbb{R}^{(v_i-p_i) \times (v_i-p_i)}$, $\mathcal{P}_{iu} \in \mathbb{R}^{(n-v_i) \times (n-v_i)}$, and a matrix $W_i \in \mathbb{R}^{(v_i-p_i) \times p_i}$ such that

$$\begin{bmatrix} \Phi_i + \gamma g_i I_{v_i-p_i} & A_{i32}^T \mathcal{P}_{iu} \\ \mathcal{P}_{iu} A_{i32} & A_{iu}^T \mathcal{P}_{iu} + \mathcal{P}_{iu} A_{iu} + 2\alpha \mathcal{P}_{iu} \end{bmatrix} - \gamma \epsilon I_{n-p_i} < 0, \quad \forall i \in \mathcal{N}, \quad (22)$$

where $\Phi_i := \mathcal{P}_{ie} A_{i22} + A_{i22}^T \mathcal{P}_{ie} - W_i E_i A_{i12} - A_{i12}^T E_i^T W_i^T + 2\alpha \mathcal{P}_{ie}$. In that case, the gain matrices in the distributed observer (2) can be taken as

$$K_i := \begin{bmatrix} E_i^{-1} \\ H_i \\ 0 \end{bmatrix} D_i^\dagger, \quad L_i := \begin{bmatrix} A_{i21} - H_i E_i A_{i11} \\ A_{i31} \end{bmatrix} E_i^{-1} D_i^\dagger + N_i S_i^T K_i \quad (23)$$

$$M_i := \begin{bmatrix} \mathcal{P}_{ie}^{-1} & 0 \\ 0 & \mathcal{P}_{iu}^{-1} \end{bmatrix} T_{is}^T, \quad N_i := \begin{bmatrix} A_{i22} - H_i E_i A_{i12} & 0 \\ A_{i32} & A_{iu} \end{bmatrix}, \quad (24)$$

$$P_i := T_{is}, \quad Q_i := T_i K_i, \quad (25)$$

where $H_i := \mathcal{P}_{ie}^{-1} W_i$, $i \in \mathcal{N}$.

Proof. A proof of Lemma 7 is given in Appendix C. $\square$

Using the previous lemmas, we are now able to formulate and prove our main result:

Theorem 8. Assume that (C, A) is observable and that $\mathcal{G}$ is a strongly connected directed graph. Let $\alpha \geq 0$. Then there exists a distributed observer (2) that achieves omniscience asymptotically while all solutions of the error system converge to zero with convergence rate at least α . This distributed observer has state space dimension equal to $Nn - \sum_{i=1}^N p_i$ with $p_i = \text{rank } C_i$. Such observer is obtained as follows:

1. For each $i \in \mathcal{N}$, make a full rank factorization $C_i = D_i F_i$ where $D_i \in \mathbb{R}^{m_i \times p_i}$ and $F_i \in \mathbb{R}^{p_i \times n}$ have full column rank and row rank, respectively.
2. For each $i \in \mathcal{N}$, choose an orthogonal matrix T_i such that

$$T_i^T A_i = \begin{bmatrix} A_{i11} & A_{i12} & 0 \\ A_{i21} & A_{i22} & 0 \\ A_{i31} & A_{i32} & A_{iu} \end{bmatrix}, \quad F_i T_i = \begin{bmatrix} E_i & 0 & 0 \end{bmatrix} \quad (26)$$

with the pair $(\begin{bmatrix} E_i & 0 \end{bmatrix}, \begin{bmatrix} A_{i11} & A_{i12} \\ A_{i21} & A_{i22} \end{bmatrix})$ observable and E_i non-singular. Then $(E_i A_{i12}, A_{i22})$ is also observable.

3. Compute the positive row vector $r = [r_1, \dots, r_N]$ such that $r\mathcal{L} = 0$ and $r\mathbf{1}_N = N$.
4. Put $g_i = 1$, $i \in \mathcal{N}$ and take $\epsilon > 0$ such that (21) holds.
5. Take $\gamma > 0$ sufficiently large so that for all $i \in \mathcal{N}$

$$A_{iu}^T + A_{iu} - (\gamma \epsilon - 2\alpha) I_{n-v_i} + \frac{1}{\gamma \epsilon - 2\alpha} A_{i32} A_{i32}^T < 0. \quad (27)$$

6. Choose H_i such that all eigenvalues of $A_{i22} - H_i E_i A_{i12}$ lie in the region $\{s \in \mathbb{C} \mid \text{Re}(s) < -\alpha\}$.
7. For all $i \in \mathcal{N}$, solve the Lyapunov equation

$$(A_{i22} - H_i E_i A_{i12} + \alpha I_{v_i-p_i})^T \mathcal{P}_{ie} + \mathcal{P}_{ie} (A_{i22} - H_i E_i A_{i12} + \alpha I_{v_i-p_i}) + (\gamma - 2\alpha) I_{v_i-p_i} = 0 \quad (28)$$

to obtain $\mathcal{P}_{ie} > 0$.

8. Define

$$K_i := \begin{bmatrix} E_i^{-1} \\ H_i \\ 0 \end{bmatrix} D_i^\dagger, \quad S_i := \begin{bmatrix} 0 \\ I_{n-p_i} \end{bmatrix}, \quad T_{is} := T_i S_i, \quad (29)$$

$$L_i := \begin{bmatrix} A_{i21} - H_i E_i A_{i11} \\ A_{i31} \end{bmatrix} E_i^{-1} D_i^\dagger + N_i S_i^T K_i, \quad (30)$$

$$M_i := \begin{bmatrix} \mathcal{P}_{ie}^{-1} & 0 \\ 0 & I_{n-v_i} \end{bmatrix} T_{is}^T, \quad N_i := \begin{bmatrix} A_{i22} - H_i E_i A_{i12} & 0 \\ A_{i32} & A_{iu} \end{bmatrix}, \quad (31)$$

$$P_i := T_{is}, \quad Q_i := T_i K_i. \quad (32)$$

Proof. We choose $g_i = 1$, $i \in \mathcal{N}$. Since the pair (C, A) is observable and the graph $\mathcal{G}$ is a strongly connected directed graph, $\epsilon > 0$ can be obtained by Lemma 6.

Putting $\mathcal{P}_{iu} = I_{n-v_i}$, $i \in \mathcal{N}$, the inequality (22) in Lemma 7 becomes

$$\begin{bmatrix} \Phi_i + \gamma I_{v_i-p_i} & A_{i32}^T \\ A_{i32} & A_{iu}^T + A_{iu} + 2\alpha I_{n-v_i} \end{bmatrix} - \gamma \epsilon I_n < 0, \quad \forall i \in \mathcal{N} \quad (33)$$

where $\Phi_i := \mathcal{P}_{ie} A_{i22} + A_{i22}^T \mathcal{P}_{ie} - W_i E_i A_{i12} - A_{i12}^T E_i^T W_i^T + 2\alpha \mathcal{P}_{ie}$. By substituting (28) and $W_i = \mathcal{P}_{ie} H_i$ into (33), we have that the

inequality (33) holds if

$$\begin{bmatrix} -(\gamma\epsilon - 2\alpha)I_{v_i-p_i} & A_{i32}^T \\ A_{i32} & A_{iu}^T + A_{iu} - (\gamma\epsilon - 2\alpha)I_{n-v_i} \end{bmatrix} < 0, \forall i \in \mathcal{N}. \quad (34)$$

By using the Schur complement lemma, (34) is equivalent to

$$A_{iu} + A_{iu}^T - (\gamma\epsilon - 2\alpha)I_{n-v_i} + \frac{1}{\gamma\epsilon - 2\alpha}A_{i32}A_{i32}^T < 0, \forall i \in \mathcal{N}. \quad (35)$$

As stated in step 5, inequality (35) can be made to hold with sufficiently large $\gamma > 0$.

Thus, we find that the parameters introduced in steps 4 to 7 guarantee that the inequality (22) in Lemma 7 holds. Hence, the distributed observer (2) with gain matrices N_i , L_i , M_i , P_i and Q_i achieves omniscience asymptotically with convergence rate at least α . $\square$

Remark 9. For any given $\alpha \geq 0$, the coupling gain $\gamma > 0$ can indeed be taken sufficiently large to guarantee that (27) holds. Since $(E_i A_{i12}, A_{i22})$ is observable, for any $\alpha \geq 0$ the Lyapunov equation (28) in step 7 can be made to have a positive definite solution by choosing the matrix H_i as in step 6.

Remark 10. The design procedure in Theorem 8 gives one possible choice of solutions of the inequality (22) in Lemma 7, which also means that under our standing assumptions that (C, A) is observable and the graph $\mathcal{G}$ is strongly connected the inequality (22) always has the required solutions. In fact, the inequalities (21) in Lemma 6 and (22) in Lemma 7 are both LMI's, which can be solved numerically by using the LMI Toolbox or YALMIP in MATLAB directly.

Remark 11. In the special case that C has full row rank m , all local output matrices C_i have full row rank m_i as well, so $p_i = m_i$ for all $i \in \mathcal{N}$. In this case our distributed observer has order $Nn - m$. In this case step 1 of our design procedure can be skipped since $F_i = C_i$ and $D_i = I_{m_i}$.

Remark 12. Another special case occurs if for some i we have $v_i = p_i$, which means that $\ker C_i$ coincides with the unobservable subspace of (C_i, A) . In this case, in the decomposition (26) the second block column and row are void, so in particular A_{i12} , A_{i22} , A_{i32} and A_{i21} do not appear. Step 5 then reduces to $A_{iu} + A_{iu}^T - (\gamma\epsilon - 2\alpha)I_{n-p_i} < 0$, and steps 6 and 7 can be skipped. The local observer (2) at node i is then given by

$$\begin{aligned} N_i &:= A_{iu}, \quad L_i := A_{i31}E_i^{-1}D_i^\dagger, \quad M_i = T_{is}^T, \quad P_i = T_{is}, \\ Q_i &= T_i K_i, \quad K_i := \begin{bmatrix} E_i^{-1} \\ 0 \end{bmatrix} D_i^\dagger. \end{aligned} \quad (36)$$

Remark 13. Note that the parameters in the distributed observer (2) have been designed based on information on the given communication graph and the local output matrices. However, even without complete knowledge of the graph Laplacian one can still proceed by choosing $\epsilon > 0$ in step 4 sufficiently small. Then, in steps 5 to 8, N_i , L_i , M_i , P_i , Q_i , K_i can be designed independently of the global information on the graph by choosing a sufficiently large coupling gain $\gamma > 0$.

4. Conclusions

In this paper we have studied the problem of reduced order distributed observer design. We have shown that if the observed plant is observable and the network graph is strongly connected, then a distributed observer achieving omniscience exists with state space dimension equal to $Nn - \sum_{i=1}^N p_i$, where N is the number of network nodes, n is the dimension of the plant state space and

p_i is the rank of the output matrix corresponding to the output received by node i . In fact, for any desired rate of error convergence a distributed observer of this order exists. As an intermediate result we have cast the distributed observer design problem in terms of feasibility of LMI's, which is advantageous from a computational point of view. Under our standing assumptions these LMI's are always solvable.

Whereas in the case of a single observer our reduced order is known to be the minimal state space dimension for a stable observer, it remains an open problem to determine the minimal order over all distributed observers with a given network graph. This is left as a problem for future research.

Acknowledgments

This work was partially supported by National Natural Science Foundation of China (Grant No. 61773145, 61403104) and China Scholarship Council (Grant No. 201606120063).

Appendix A. Proof of Lemma 4

Proof. For $i \in \mathcal{N}$, let T_{ip} be the $n \times p_i$ matrix consisting of the first p_i columns of T_i . Then we have $T_i = \begin{bmatrix} T_{ip} & T_{is} \end{bmatrix}$. Since T_i is orthogonal, we have $\text{im } T_{is} = \ker T_{ip}^T$. Let e_i be a local error trajectory. We have

$$\begin{aligned} T_{ip}^T e_i &= T_{ip}^T (\hat{x}_i - x) \\ &= T_{ip}^T T_{is} z_i + T_{ip}^T T_i K_i C_i x - T_{ip}^T x \\ &= \begin{bmatrix} I_{p_i} & 0 \end{bmatrix} K_i C_i x - T_{ip}^T x \\ &= (E_i^{-1} F_i - T_{ip}^T) x. \end{aligned} \quad (37)$$

By (5) we have

$$F_i \begin{bmatrix} T_{ip} & T_{is} \end{bmatrix} = \begin{bmatrix} E_i & 0 \end{bmatrix}, \quad (38)$$

which implies

$$F_i = \begin{bmatrix} E_i & 0 \end{bmatrix} \begin{bmatrix} T_{ip} & T_{is} \end{bmatrix}^T = E_i T_{ip}^T. \quad (39)$$

Thus we obtain $T_{ip}^T e_i = 0$ and hence $e_i(t) \in \ker T_{ip}^T$ for all $t \in \mathbb{R}$. We conclude that $e_i(t) \in \text{im } T_{is}$ so $e(t) \in \text{im } T_s$ for all $t \in \mathbb{R}$. $\square$

Appendix B. Proof of Lemma 6

Proof. The inequality (21) holds if and only if the following inequality holds.

$$(U^T(R\mathcal{L} + \mathcal{L}^T R)U) \otimes I_n + (U^T \otimes I_n)TGT^T(U \otimes I_n) > 0, \quad (40)$$

where U is as in Lemma 5. The inequality (40) holds if the following inequality holds:

$$\lambda_2 I_{Nn} - (U \otimes I_n) \begin{bmatrix} \lambda_2 I_n & 0 \\ 0 & 0_{(N-1)n} \end{bmatrix} (U^T \otimes I_n) + TGT^T > 0. \quad (41)$$

Since $U = \begin{bmatrix} \frac{1}{\sqrt{N}} \mathbf{1}_N & U_2 \end{bmatrix}$ and $U^T = \begin{bmatrix} \frac{1}{\sqrt{N}} \mathbf{1}_N^T \\ U_2^T \end{bmatrix}$, the inequality (41) is equivalent to

$$\lambda_2 I_{Nn} - \frac{\lambda_2}{N} (\mathbf{1}_N \otimes I_n) (\mathbf{1}_N^T \otimes I_n) + TGT^T > 0. \quad (42)$$

By pre- and post-multiplying with T^T and T , the inequality (42) is equivalent to

$$\lambda_2 I_{Nn} - \frac{\lambda_2}{N} T^T (\mathbf{1}_N \otimes I_n) (\mathbf{1}_N^T \otimes I_n) T + G > 0, \quad (43)$$

that is

$$\lambda_2 I_{Nn} + G - \frac{\lambda_2}{N} [T_1 \quad \cdots \quad T_N]^T [T_1 \quad \cdots \quad T_N] > 0. \quad (44)$$

By using the Schur complement lemma [17], the inequality (44) is equivalent to

$$\begin{bmatrix} \Psi_1 & \cdots & 0 & T_1^T \\ \vdots & \ddots & \vdots & \vdots \\ 0 & \cdots & \Psi_N & T_N^T \\ T_1 & \cdots & T_N & \frac{N}{\lambda_2} I_n \end{bmatrix} > 0 \quad (45)$$

where $\Psi_i := \begin{bmatrix} (\lambda_2 + g_i)I_{v_i} & 0 \\ 0 & \lambda_2 I_{n-v_i} \end{bmatrix}$, $i \in \mathcal{N}$. Now, partition the orthogonal matrix T_i as $T_i = [T_{i1} \ T_{i2}]$, with $T_{i1} \in \mathbb{R}^{n \times v_i}$ and $T_{i2} \in \mathbb{R}^{n \times (n-v_i)}$, $i \in \mathcal{N}$. Clearly, $T_{i1}T_{i1}^T + T_{i2}T_{i2}^T = I_n$. Again using the Schur complement lemma, (45) is then equivalent to

$$\begin{bmatrix} \lambda_2 I_{n-v_1} & 0 & \cdots & 0 & T_{12}^T \\ 0 & \Psi_2 & \cdots & 0 & T_2^T \\ \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & \cdots & \Psi_N & T_N^T \\ T_{12} & T_2 & \cdots & T_N & \frac{N}{\lambda_2} I_n - \frac{1}{\lambda_2 + g_1} T_{11}T_{11}^T \end{bmatrix} > 0. \quad (46)$$

By repeatedly using the Schur complement lemma, we finally obtain that inequality (44) holds if and only if

$$\frac{N}{\lambda_2} I_n - \sum_{i=1}^N \frac{1}{\lambda_2 + g_i} T_{i1}T_{i1}^T - \sum_{i=1}^N \frac{1}{\lambda_2} T_{i2}T_{i2}^T > 0. \quad (47)$$

The left-hand side of inequality (47) is equal to

$$\begin{aligned} & \frac{N}{\lambda_2} I_n - \sum_{i=1}^N \frac{1}{\lambda_2 + g_i} T_{i1}T_{i1}^T - \sum_{i=1}^N \frac{1}{\lambda_2} T_{i2}T_{i2}^T \\ &= \frac{N}{\lambda_2} I_n - \sum_{i=1}^N \frac{1}{\lambda_2} T_{i2}T_{i2}^T - \sum_{i=1}^N \frac{1}{\lambda_2} T_{i1}T_{i1}^T \\ & \quad + \sum_{i=1}^N \frac{1}{\lambda_2} T_{i1}T_{i1}^T - \sum_{i=1}^N \frac{1}{\lambda_2 + g_i} T_{i1}T_{i1}^T \\ &= \sum_{i=1}^N \left(\frac{1}{\lambda_2} - \frac{1}{\lambda_2 + g_i} \right) T_{i1}T_{i1}^T \\ & \geq \sum_{i=1}^N \left(\frac{1}{\lambda_2} - \frac{1}{\lambda_2 + g_{\min}} \right) T_{i1}T_{i1}^T \\ &= \left(\frac{N}{\lambda_2} - \frac{N}{\lambda_2 + g_{\min}} \right) [T_{11} \ \cdots \ T_{N1}] [T_{11} \ \cdots \ T_{N1}]^T, \end{aligned} \quad (48)$$

where $g_{\min}$ is the minimum value of g_i , $i \in \mathcal{N}$. Obviously, we have $\left(\frac{N}{\lambda_2} - \frac{N}{\lambda_2 + g_{\min}} \right) > 0$ since $g_{\min} > 0$.

We will now prove that $\text{rank} [T_{11} \ T_{21} \ \cdots \ T_{N1}] = n$, so that it has full row rank. Indeed, for T_{i1} , we have

$$\text{im } T_{i1} = (\ker O_{F_i})^\perp \quad (49)$$

where $O_{F_i} = \text{col}(F_i, F_i A, \dots, F_i A^{n-1})$ is the unobservable subspace of (F_i, A) . Hence,

$$\begin{aligned} (\text{im } [T_{11} \ T_{21} \ \cdots \ T_{N1}])^\perp &= (\text{im } T_{11} + \text{im } T_{21} + \cdots + \text{im } T_{N1})^\perp \\ &= \bigcap_{i=1}^N (\text{im } T_{i1})^\perp \\ &= \bigcap_{i=1}^N \ker O_{F_i} \\ &= \ker \begin{bmatrix} O_{F_1} \\ \vdots \\ O_{F_N} \end{bmatrix} \\ &= 0, \end{aligned} \quad (50)$$

where we have used the fact that the pair (F, A) is observable. This implies

$$\text{rank} [T_{11} \ T_{21} \ \cdots \ T_{N1}] = n. \quad (51)$$

Consequently, $[T_{11} \ T_{21} \ \cdots \ T_{N1}]$ has full row rank n , so we obtain:

$$\left(\frac{N}{\lambda_2} - \frac{N}{\lambda_2 + g_{\min}} \right) [T_{11} \ \cdots \ T_{N1}] [T_{11} \ \cdots \ T_{N1}]^T > 0. \quad (52)$$

We conclude that the left-hand side of (21) is positive definite, and consequently, for any choice of $g_i > 0$, $i \in \mathcal{N}$, there exists a scalar $\epsilon > 0$ such that inequality (21) holds. $\square$

Appendix C. Proof of Lemma 7

Proof. By taking the gain matrices (23), (24) and (25), the global error satisfies the differential equation (20). According to Lemma 4 we also have $e(t) \in \text{im } T_s$ for all $t \in \mathbb{R}$. As a candidate Lyapunov function for the error system we take

$$V(e) = e^T \mathcal{P} e \quad (53)$$

where $\mathcal{P} := \text{diag}\{\mathcal{P}_1, \dots, \mathcal{P}_N\}$ and

$$\mathcal{P}_i := T_i \begin{bmatrix} I_{p_i} & 0 & 0 \\ 0 & \mathcal{P}_{ie} & 0 \\ 0 & 0 & \mathcal{P}_{iu} \end{bmatrix} T_i^T.$$

Clearly then $\mathcal{P} > 0$. The time-derivative of V is

$$\begin{aligned} \dot{V}(e) &= e^T (\mathcal{P} T_s N T_s^T + T_s N^T T_s^T \mathcal{P} - \gamma \mathcal{P} T_s M (R\mathcal{L} \otimes I_n) \\ & \quad - \gamma (\mathcal{L}^T R \otimes I_n) M^T T_s^T \mathcal{P}) e \end{aligned} \quad (54)$$

with T_s , M and N the block diagonal versions of the T_{is} , M_i and N_i as defined by (17), (18) and (19). By substituting $M_i := \begin{bmatrix} \mathcal{P}_{ie}^{-1} & 0 \\ 0 & \mathcal{P}_{iu}^{-1} \end{bmatrix} T_{is}^T$ into (54), the time-derivative of V becomes

$$\dot{V}(e) = e^T \Lambda e, \quad (55)$$

where we have defined

$$\Lambda := \mathcal{P} T_s N T_s^T + T_s N^T T_s^T \mathcal{P} - \gamma T_s T_s^T (R\mathcal{L} \otimes I_n) - \gamma (\mathcal{L}^T R \otimes I_n) T_s T_s^T.$$

On the other hand, by combining (22) with (21) in Lemma 6 it can be verified that

$$\text{diag}\{\mathcal{Q}_1, \dots, \mathcal{Q}_N\} - T_s^T \gamma ((R\mathcal{L} + \mathcal{L}^T R) \otimes I_n) T_s < 0, \quad (56)$$

where $\mathcal{Q}_i := \begin{bmatrix} \Phi_i & A_{i32}^T \mathcal{P}_{iu} \\ \mathcal{P}_{iu} A_{i32} & \mathcal{P}_{iu} A_{iu} + A_{iu}^T \mathcal{P}_{iu} + 2\alpha \mathcal{P}_{iu} \end{bmatrix}$, $i \in \mathcal{N}$, and Φ_i as defined in the statement of the theorem.

Recall that we have defined $H_i := \mathcal{P}_{ie}^{-1} W_i$. Hence $W_i = \mathcal{P}_{ie} H_i$. By substituting this into the expression for Φ_i , we can check that

$$\mathcal{Q}_i = T_{is}^T \mathcal{P}_i T_{is} N_i + N_i^T T_{is}^T \mathcal{P}_i T_{is} + 2\alpha T_{is}^T \mathcal{P}_i T_{is}$$

Substituting this into the inequality (56), using that $T_s^T T_s$ is the identity matrix, we get

$$\begin{aligned} T_s^T (\mathcal{P} T_s N T_s^T + T_s N^T T_s^T \mathcal{P} - \gamma T_s T_s^T (R\mathcal{L} \otimes I_n) \\ - \gamma (\mathcal{L}^T R \otimes I_n) T_s T_s^T + 2\alpha \mathcal{P}) T_s < 0, \end{aligned}$$

so, in other words,

$$T_s^T (\Lambda + 2\alpha \mathcal{P}) T_s < 0. \quad (57)$$

By combining (55) and (57) we will now show that all global error trajectories converge to zero with convergence rate at least α . Indeed let e be such trajectory. By Lemma 4 we have that e can be represented as $e = T_s z$ for some function z . Thus we get

$$\begin{aligned} \dot{V}(e) + 2\alpha V(e) &= e^T \Lambda e + 2\alpha e^T \mathcal{P} e \\ &= z^T T_s^T (\Lambda + 2\alpha \mathcal{P}) T_s z, \end{aligned}$$

and therefore $\dot{V}(e)(t) + 2\alpha V(e)(t) < 0$ whenever $e(t) \neq 0$. Hence the distributed observer (2) achieves omniscience asymptotically and all solutions of the global error system converge to zero asymptotically with convergence rate at least α . $\square$

References

- [1] T. Kim, H. Shim, D.D. Cho, Distributed Luenberger observer design, in: Proc. 55th IEEE Conference on Decision and Control (CDC), Las Vegas, NV, USA, 2016, pp. 6928–6933.
- [2] A. Mitra, S. Sundaram, An approach for distributed state estimation of LTI systems, in: Proc. 54th IEEE Annual Allerton Conference on Communication, Control, and Computing (Allerton), Illinois, USA, 2016, pp. 1088–1093.
- [3] S. Park, N.C. Martins, An augmented observer for the distributed estimation problem for LTI systems, in: Proc. American Control Conference (ACC), Montreal, Canada, 2012, pp. 6775–6780.
- [4] S. Park, N.C. Martins, Necessary and sufficient conditions for the stabilizability of a class of LTI distributed observers, in: Proc. 51th IEEE Conference on Decision and Control (CDC), Maui, HI, USA, 2012, pp. 7431–7436.
- [5] S. Park, N.C. Martins, Design of distributed LTI observers for state omniscience, *IEEE Trans. Automat. Control* 62 (2) (2017) 561–576.
- [6] B.D.O. Anderson, D.J. Clements, Algebraic characterization of fixed modes in decentralized control, *Automatica* 17 (5) (1981) 703–712.
- [7] L. Wang, A.S. Morse, A distributed observer for a time-invariant linear system, 2016, arXiv preprint [arXiv:1609.05800](https://arxiv.org/abs/1609.05800).
- [8] A. Mitra, S. Sundaram, Secure distributed observers for a class of linear time invariant systems in the presence of byzantine adversaries, in Proc. 55th IEEE Conference on Decision and Control (CDC), Las Vegas, NV, USA: IEEE, 2016, pp. 2709–2714.
- [9] A. Mitra, S. Sundaram, Distributed observers for LTI systems, 2016, arXiv preprint [arXiv:1608.01429](https://arxiv.org/abs/1608.01429).
- [10] W. Han, H.L. Trentelman, Z. Wang, Y. Shen, A simple approach to distributed observer design for linear systems, 2017, arXiv preprint [arXiv:1708.01459](https://arxiv.org/abs/1708.01459).
- [11] D. Luenberger, An introduction to observers, *IEEE Trans. Automat. Control* 16 (6) (1971) 596–602.
- [12] W.M. Wonham, *Linear Multivariable Control: A Geometric Approach*, Springer-Verlag, New York, 1979.
- [13] R. Olfati-Saber, R.M. Murray, Consensus problems in networks of agents with switching topology and time-delays, *IEEE Trans. Automat. Control* 49 (9) (2004) 1520–1533.
- [14] W. Ren, R.W. Beard, Consensus seeking in multiagent systems under dynamically changing interaction topologies, *IEEE Trans. Automat. Control* 50 (5) (2005) 655–661.
- [15] W. Yu, G. Chen, M. Cao, J. Kurths, Second-order consensus for multiagent systems with directed topologies and nonlinear dynamics, *IEEE Trans. Syst. Man Cybern. Part B Cybern.* 40 (3) (2010) 881–891.
- [16] Z. Li, Z. Duan, *Cooperative Control of Multi-Agent Systems: A Consensus Region Approach*, CRC Press, 2014.
- [17] S. Boyd, L. El Ghaoui, E. Feron, V. Balakrishnan, *Linear Matrix Inequalities in System and Control Theory*, SIAM, 1994.