University of Groningen

Model Simplification in Manufacturing Simulation - Review and Framework

van der Zee, Durk-Jouke

Published in:
Computers & Industrial Engineering

DOI:
[10.1016/j.cie.2018.11.038](https://doi.org/10.1016/j.cie.2018.11.038)

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version
Publisher's PDF, also known as Version of record

Publication date:
2019

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):
van der Zee, D-J. (2019). Model Simplification in Manufacturing Simulation - Review and Framework. *Computers & Industrial Engineering*, 127, 1056-1067. <https://doi.org/10.1016/j.cie.2018.11.038>

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Model simplification in manufacturing simulation – Review and framework

Durk-Jouke van der Zee

Department of Operations, Faculty of Economics & Business, University of Groningen, P.O. Box 800, 9700 AV, Groningen, the Netherlands

ARTICLE INFO

Keywords:

Simulation
Model simplification
Manufacturing systems

ABSTRACT

Simulation models are meant to support industrial engineers in understanding complex problems and provide useful insights facilitating their solution. Models achieve this by reducing focus to system elements that matter. Surprisingly, despite its relevance, simulation model simplification is still very much a green field. This is mirrored in existing literature and course materials. In this article we seek to foster development of the field by proposing a framework for simulation model simplification addressing the manufacturing domain, thereby building on an extensive literature review. The framework structures the field by providing a unifying view on simulation model simplification, in terms of its key activities, i.e., reducing and preventing model complexity, and support offered in performing these. Apart from its role as a focal point for future research, the framework is meant to benefit practitioners and educators, by giving them access to research findings, and enabling and legitimizing development of educational materials and their uptake.

1. Introduction

Many decisions on manufacturing systems design rely on the use of discrete event simulation models (Negahban & Smith, 2014). A prime reason for their popularity is their flexibility in modeling and visualizing the various elements of industrial systems. Exploiting such flexibility, however, sets specific demands on the skills of the industrial engineer and the methods and tools at his/her disposal in simplifying the model relative to the system under study. To reduce modeling efforts, foster model understanding and safeguard computational efficiency of the model, ideally, only system elements that matter for answering to the modeling objectives are included in the model (Ward, 1989).

Surprisingly, despite being a fundamental part of modeling and simulation (Henriksen, 2008; Salt, 1993; Shannon, 1998), simulation model simplification is still very much a green field (Ahmed, Shah, & Umar, 2016; Brooks & Tobias, 2000; Chwif, Barretto, & Paul, 2000; Robinson, 2006; Sevinc, 1991; Van der Zee, Brooks, Robinson, & Kotiadis, 2011). Relatively few contributions have been made over the past decades. Those available make up a fragmented landscape, suggesting the lack of a (unified) view on the field. This is apparent in, for example, alternative choices of terminology, and researchers being unaware of contributions already made. In turn, text books reflect state of the art by restricting their guidance on simulation model simplification to a few rules of thumb, or not addressing it at all.

In this article we seek to foster development of the field by proposing a research framework for simulation model simplification addressing the manufacturing domain, thereby building on an extensive literature review. The framework relates model simplification to simulation study set-up and the modeling process by identifying and detailing two main activities, i.e., reducing and preventing model complexity. Whereas the first activity addresses steps to take to arrive at a simplified model – starting from a more complex model, the latter activity is meant to avoid the need for model simplification by adjusting modeling objectives, (staff) resources provided, and choice of modeling methodology.

By proposing a research framework we aim to (i) structure the field by highlighting distinctive features of simulation model simplification in terms of key activities and support in executing these, (ii) recollect existing contributions for the field, where such an overview is not available, and (iii) identify main research avenues. Apart from researchers both practitioners and educators may find the framework useful as it outlines major lines of research in the field.

The article is structured as follows. Section 2 discusses the method and base for the literature review. Descriptive analysis of articles resulting from the literature search is provided in Section 3. In Section 4 the research framework is proposed and related to existing literature. Section 5 assesses contributions made by the framework by considering implications for research and practice. Concluding remarks are summarized in Section 6.

E-mail address: d.j.van.der.zee@rug.nl.

<https://doi.org/10.1016/j.cie.2018.11.038>

Received 17 August 2018; Received in revised form 31 October 2018; Accepted 19 November 2018

Available online 20 November 2018

0360-8352/ © 2018 Elsevier Ltd. All rights reserved.

2. Research method – literature review

2.1. Basic terminology

To prepare the groundwork for the literature review key terms are defined. Model simplification is defined as the reduction of inappropriate model complexity. Here “inappropriate” is related to model conformance with modeling objectives and the variance in the data available to the modeler (Innis & Rexstad, 1983). Simulation refers to discrete event simulation: “The modeling of a system as it evolves over time by a representation in which the state variables change instantaneously at separate points in time” (Law, 2015). The process of simulation modeling is characterized by four main activities, i.e., conceptual modeling, model coding, experimentation, and implementation (Robinson, 2014). Respective activities are performed within the context of a simulation study, being characterized by the client, stakeholders, problem faced, modeling objectives, modeling methodology, and resources in terms of a project team, hardware, software, budget, and lead time.

2.2. Delimitations and search process

To clarify the boundaries of the literature review we make the following notes:

- (1) This analysis aimed at articles in peer-reviewed scientific journals and conferences in English as they appeared until 2017. Inclusion of conference articles is motivated by the fact that many authors consider the field to be green, see Section 1. In this way we attempt to record progress for the field which has not yet been captured in journal articles. Conference articles that were extended towards journal articles were excluded.
- (2) Articles which only focused at comparing the use of simulation vs. analytical tools for decision support were excluded. We consider simplifications within the context of a simulation model, and do not address the overarching debate on the appropriateness of operational research methods for addressing specific types of problems.
- (3) The domain of interest is in the use of simulation for modeling and analyzing operations systems in manufacturing. Operations systems facilitate the material flow cycle, in terms of supply, production, and distribution. The domain covers a wide choice of systems, ranging from simple job shops to supply chains.

The search for related publications was mainly conducted as a structured keyword search on major databases. The following keywords were used in combination: simulation and model abstraction, simulation and model reduction, simulation and model simplification, simulation and model enrichment, simulation and model complexity, simulation model* and abstract*, simulation model* and reduc*, simulation model* and simpl*, simulation model* and enrich*, simulation model* and complex*, simulation model* and redundan*. In accordance with the delimitations mentioned above we followed two avenues in our search process. Firstly, searches of the Web of Science and Scopus aimed at articles in peer-reviewed scientific journals in English. Secondly, IEEE Xplore was searched for articles presented at the Winter Simulation Conference, being the premier international scientific forum for the simulation field. Relevance of the approach for a good coverage of the field was confirmed by the search outcomes. Content-wise articles resulting from both searches often complemented each other. Many contributions presented at the conference did not appear in journal articles yet. Reading the articles found in aforementioned searches, cited references were used as a secondary resource. Apart from additional journal articles this resulted in a few articles originating from conferences other than the Winter Simulation Conference.

3. Descriptive analysis of articles

3.1. Source characteristics

Our searches resulted in 82 articles with 41, and 41 of them being published as journal articles and conference articles respectively. Fig. 1 illustrates the distribution of the articles over the publication years. It shows how numbers of articles published increase over the years, indicating a somewhat growing popularity of the field. Journal articles are about equally divided among (Industrial) Engineering journals (22) and OR journals (19). The latter category hosts many journals dedicated to the simulation field such as Simulation, and the Journal of Simulation. The rising interest in decision support for semiconductor manufacturing, see above, is marked by several articles being published in IEEE Transactions on Semiconductor Manufacturing (5). Given article numbers, no journal or journals seem(s) to stand out as being the primary outlet(s) for the field.

Fig. 1. Distribution of the articles by the publication year.

3.2. System characteristics – domain, level and use

Most of the articles (45) address the general case of manufacturing systems, i.e., they do not start from specific assumptions about system characteristics. Among those articles that do differentiate a strong focus on semiconductor manufacturing is apparent (19 out of 37). The complexity of manufacturing systems in this domain representing large capital investments, is a likely explanation for the interest shown (Fowler & Rose, 2004; Fowler, Mönch, & Ponsignon, 2015; Jain, Lim, Gan, & Low, 1999). Remainder articles address a large variety of manufacturing domains.

Level refers to the scope of the system under study. Here we differentiate between work centers, manufacturing sites, and supply chains. Typically, the choice of level sets specific demands on the need for, the nature and extent of model simplifications. Most articles favor use of simplification methods for modeling work centers (14) or manufacturing sites (19). Supply chains are hardly addressed (4). The latter finding is confirmed by observations from semiconductor manufacturing, suggesting supply chain simulation to be a rather new area of application (Fowler et al., 2015).

Apart from system scope also model use appears to be a denominator of interest shown in simulation model simplification. Six articles show how model simplification may facilitate simulation-based scheduling, by allowing it to deal with a short horizon for decision making.

3.3. Modeling activities supported

Modeling activities considered in the review are conceptual modeling, model coding and experimentation, linking to the set-up of the conceptual model, the coded model and the experimental frame respectively. With no exception all articles in our study link model simplification to conceptual modeling. Given the high impact of conceptual modeling decisions on remainder modeling activities and – ultimately – study success (Robinson, 2006), this is hardly a surprise. Relatively few articles discuss simplification of the coded model (9) and experimental frame (6).

4. Towards a framework for simulation model simplification

By proposing a framework we seek to structure the field, where such structuring is currently largely lacking. In doing the literature review we found no attempts to structure the field going far beyond listings of methods, good practices or rules of thumb. Moreover, to our knowledge, no literature review has been published so far.

Essentially, the framework links simplification to two main activities, i.e., reducing and preventing model complexity, see Fig. 2. The first activity addresses steps to take to arrive at a simplified model – starting from a more complex model. The majority of articles in our review seek to support this activity by developing and/or testing methods and procedures for (i) tracing inappropriate model complexity, and (ii) model modification aiming to realize a reduction of model

complexity. Need for and success of model reduction build on an assessment of model conformance to modeling objectives in terms of essential model qualities, especially validity, utility and feasibility (Section 4.1). A smaller group of authors shows an interest in the drivers of inappropriate model complexity, thereby hinting at the need for prevention by a careful set-up of the study through adherence to guidelines (Section 4.2). Both aforementioned activities may be related, as successful model reduction may require reconsidering study set-up. A root-cause analysis is meant to establish and underpin the need to do so (Section 4.3). Main focus of the framework is on modeling support for simplifying the conceptual model, entailing model content, inputs and outputs. As such it reflects state of the art for the field, being the net result of most research efforts being directed towards conceptual modeling rather than the development of the coded model or experimental frame, see Section 3.3. In Section 4.4 we consider extensions of the framework addressing simplification of the latter types of models.

4.1. Model complexity reduction

4.1.1. Improving model qualities – assessing costs and benefits of model simplification

Clearly, model simplification is not an end in itself but is meant to improve model qualities that determine its conformance to modeling objectives (Kotiadis & Robinson, 2008; Robinson, 2008a). Essentially, model simplification should facilitate an increase of model utility and feasibility, not being at the expense of its validity (Robinson, 2008a). Model utility stresses the way a model's ease of use, flexibility, visualization, and run speed contribute to its usefulness. Requirements set on time, resources and data determine feasibility of the proposed model set-up and use. Whether model simplification does not hurt its validity, i.e., model accuracy, should be decided upon based on judgement and/or tests by computer models (Edmonds & Moss, 2004; Harrison, Lin, Carroll, & Carley, 2007; Kotiadis & Robinson, 2008; Robinson, 2014).

Many authors suggest benefits of simplification, thereby detailing its added value for model qualities, see Table 1. In turn, benefits identified reveal those outcomes of the study set-up that may be involved in assessing model scope and detail. For example, a reduced model may benefit model feasibility by requiring less input data, thereby decreasing the modeler's efforts, and lessening resource use, as observed by project management. Likewise, it may be considered whether excess model detail is hindering its interpretation by model users.

Relevance of stakeholder perspectives in assessing benefits of model simplification (Maier, Eckert, & Clarkson, 2017) has been reflected in Table 1 by differentiating among various roles in a simulation study. Roles are specified according to Robinson (2014) and Ormerod (2001). While some observed benefits may relate to a specific role, others may be shared among roles. For example, both modeler and domain expert may take advantage of the fact that data requirements may be less. However, simplifications may also imply a trade-off. For example, increasing model speed – by simplifying the model by leaving out detail – may not always improve model understanding among stakeholders. Or

Fig. 2. A framework for simulation model simplification.

Table 1
Benefits of simpler models for various stakeholders.

Role	Tasks	Benefits of simpler models	References
Project manager	Manage process	<u>Project resources</u> <ul style="list-style-type: none"> • Less expensive • Less time involved • Less use of resources • Involves less efforts of project manager <u>Project content</u> <ul style="list-style-type: none"> • Helpful in specifying modeling objectives • Helpful in acquiring more projects • Avoids solutions that are too advanced being implemented 	<ul style="list-style-type: none"> • Innis and Rexstad (1983), Yin and Zhou (1989) • Yin and Zhou (1989), Chwif et al. (2000) • Chwif et al. (2000) • Chwif et al. (2000) • Rexstad and Innis (1985) • Ward (1989), Salt (1993) • Musselman (1994)
Modeler	Model development	<u>Data requirements</u> <ul style="list-style-type: none"> • Less input data required <u>Model building</u> <ul style="list-style-type: none"> • Facilitates more flexible modeling • Easier to develop and maintain • Avoids solutions that are too advanced being implemented <u>Model validation and verification</u> <ul style="list-style-type: none"> • Easier to validate, verify • Higher accessibility of assumptions • Clear exposure of flaws; avoid errors • More accurate <u>Modeling methodology</u> <ul style="list-style-type: none"> • Facilitates evolutionary path for the modeling process 	<ul style="list-style-type: none"> • Innis and Rexstad (1983), Yin and Zhou (1989), Salt (1993), Sinreich and Marmor (2004), Fletcher et al. (2007) • Innis and Rexstad (1983), Yin and Zhou (1989), Salt (1993), Musselman (1994), Chwif et al. (2000) • Rexstad and Innis (1985), Fishwick (1988), Ward (1989), Chwif et al. (2000), Brooks and Tobias (1996, 2000), Salt (1993) • Musselman (1994) • Chwif et al. (2000), Rexstad and Innis (1985) • Ward (1989) • Musselman (1994), Rexstad and Innis (1985), Brooks & Tobias, 1996) • Musselman (1994) • Fishwick (1988)
Model user	Do and analyze experiments	<u>Analysis</u> <ul style="list-style-type: none"> • Easier to interpret • Higher accessibility of assumptions • Easier to use • Enhances insight <u>Experimenting</u> <ul style="list-style-type: none"> • Speeds up experiments • Allows exploratory use of model • Sensitivity analysis is more practicable 	<ul style="list-style-type: none"> • Innis and Rexstad (1983), Fishwick (1988), Yin and Zhou (1989), Brooks and Tobias (1996, 2000), Chwif et al. (2000), Sinreich and Marmor (2004) • Ward (1989) • Fripp (1985), Henriksen (2008), Sinreich and Marmor (2004) • Fripp (1985), Brooks and Tobias (2000), Musselman (1994), Anderson and Morrice (1999), Fletcher et al. (2007) • Fishwick (1988), Sevinc (1991), Brooks and Tobias (1996, 2000), Salt (1993), Rank et al. (2016) • Salt (1993), Fletcher et al. (2007) • Ward (1989), Brooks and Tobias (2000)
Client	Owens problem, recipient of results, funds study	<u>Project resources</u> <ul style="list-style-type: none"> • Less expensive <u>Project content</u> <ul style="list-style-type: none"> • Helpful in specifying modeling objectives • Avoids solutions that are too advanced being implemented 	<ul style="list-style-type: none"> • Innis and Rexstad (1983) • Rexstad and Innis (1985) • Musselman (1994)
Domain expert	Provide data	<u>Data requirements</u> <ul style="list-style-type: none"> • Less input data required 	<ul style="list-style-type: none"> • Innis and Rexstad (1983), Ward (1989), Salt (1993), Sinreich and Marmor (2004), Fletcher et al., 2007
Third party expert	Provide software support and/or modeling expertise	<u>Software</u> <ul style="list-style-type: none"> • Applicability of software may increase <u>Model building</u> <ul style="list-style-type: none"> • Easier to develop and maintain 	<ul style="list-style-type: none"> • Henriksen (2008) • Rexstad and Innis (1985), Ward (1989), Chwif et al. (2000), Brooks and Tobias (1996, 2000), Salt (1993)
Management	Benefit from the study	<u>Implementation of results</u> <ul style="list-style-type: none"> • Quicker results facilitating speedier decision making, allowing more time for alternative actions and implementation • Results being less specific, allowing managers to incorporate their own knowledge and preferences • Recommendations are easier to sell • Improve fit with strategic nature of problem 	<ul style="list-style-type: none"> • Ward (1989), Brooks and Tobias (2000), Fletcher et al. (2007) • Ward (1989), Brooks and Tobias (2000) • Ward (1989) • Ward (1989)

even stronger, efforts towards increasing model understanding by simplifying the model may not always be successful, as stakeholder backgrounds may differ (Salt, 1993; Ward, 1989). Furthermore, the need for simplification may differ over the modeling cycle. For example, during the verification phase, a model that is easy to code and

debug is desirable, whereas during the experimentation phase, a fast implementation is preferred (Schruben & Yücesan, 1993).

Benefits of a simplification are conditional on its impact on model validity. Many authors suggest the existence of a certain range in which a reduction of model complexity in terms of its scope and detail due to

Fig. 3. Simulation complexity and model accuracy - similar to Robinson (2008a).

simplifications does not/hardly impact its validity (Fig. 3), also compare Benjamin, Erraguntla, Delen, and Mayer (1998), Chwif et al. (2000), Astrup, Coates, and Hall (2008), and Robinson (2008a). The “choice of range” will be determined by the modeling objectives and the nature of the answers that are to be provided. Nice illustrations of the choice of range can be found outside the manufacturing domain, in the health scene. Fletcher, Halsall, Huxham, and Worthington (2007) developed a generic model for simulating emergency departments (EDs) throughout England, as a part of a campaign of the National Health Service (NHS) to improve ED performance. They found that in case basic insights in system workings would be asked for the generic model would suffice. However, in case impact of local decisions has to be accounted for the model has to be refined. Starting from the observation that the implementation of many health policies may be extremely expensive, Davies, Roderick, and Raftery (2003) stress the relevance of tailoring model detail towards factors that will make a substantial difference to the results and conclusions of the simulation study. In specific cases, simplifications may even increase model validity (Fig. 3, right hand side), by removing model complexity not or insufficiently supported by data or information (Brooks & Tobias, 2000; Innis & Rexstad, 1983; Robinson, 2008a). Clearly removing too much complexity hurts model validity, compare Fig. 3 (left hand side).

Usually, model simplification comes at a cost. Costs relate to the efforts put in developing, implementing and validating a simplification (Rexstad & Innis, 1985; Brooks & Tobias, 1996; Frantz, 1997; Davies et al., 2003). Moreover, simplification may be a risky undertaking, as efforts put in may not result in an acceptable simplified model (Brooks & Tobias, 1999). Also detailed models may still be required to ascertain model credibility (Brooks & Tobias, 1999). Not surprisingly, several authors point out that decisions on model simplification require a cost-benefit analysis (Barlow, 2009; Innis & Rexstad, 1983), ideally building on clear modeling objectives (Chwif et al., 2000). Expectedly, larger and more complex models will require greater analysis detail – as stakes tend to be higher.

Several authors clarify how benefits may not outweigh costs. Rexstad and Innis (1985) found how in some cases a simpler model may take longer to develop, due to the presence of many alternative simplifications, and/or their development and testing being laborious. Spiegel, Reynolds, and Brogan (2005) demonstrate that even for simple problems model simplification may not be easy, due to undocumented assumptions. What if simplification is not easily attained? Under these circumstances, model transparency is still possible building on good communications of modelers – speaking the language of the problem domain – with the model users, being supported by, for example,

manual simulations or structured walkthroughs of the model (Salt, 1993).

4.1.2. Methods for tracing inappropriate model complexity

How to trace model components that are eligible for simplification, i.e., are of no significant relevance in capturing the causal connection between model inputs and outputs (Benjamin et al., 1998; Law et al., 1993; Robinson, 2008b). Basically, eligible components qualify by allowing for their omission, aggregation or substitution (Pegden, Shannon, & Sadowski, 1990; Rank et al., 2016). Omission of model components builds on the assumption that system elements represented by them have no significant influence on system performance. Aggregating model components into a single component that approximates joint behavior, is another way of reducing the number of model components. Substitution entails replacing complex model components with simpler ones that approximate behavior of the former. Note that aggregation and substitution are related, with the latter being the result of repeated aggregation (Rank et al., 2016).

Various checklists have been put forward suggesting rules supporting the selection of model components for possible simplification. Essentially, rules identify components by studying their behavior. Often mentioned examples are shown in Table 2 (Rank et al., 2016; Robinson, 1994, 2014).

Whereas rules mentioned in Table 2 address the general case of operations systems in manufacturing, other authors provide domain specific guidance. For example, Morrison (2011) suggests considering the possibility to ignore wafer transport robots in a fab-level simulation. Likewise, Jimenez, Mackulak, and Fowler (2008) propose a method for classifying semiconductor wafer fab models by the level of capacity

Table 2

Rules for selecting model components for possible simplification.

Rule
<ul style="list-style-type: none"> ● Exclude resources that are always available ● Group products being processed batch wise ● Represent similar products by a single product type ● Do not distinguish between products showing similarities in part routing and resource use ● Exclude infrequent events ● Exclude non-critical materials ● Do not distinguish between shift patterns suggesting similar operations during shifts ● Exclude rules governing entity flow addressing rare situations ● Substitute model components representing resources for which utilization is low, queue length is small, or waiting or lead times are short with delays

detail and the level of detail of automated handling systems, as deemed required given the modeling objectives. Further evidence on the relevance of recollecting and developing domain specific guidance on model simplification is also found outside manufacturing, in related fields of interest. Starting from the benefits associated with model reuse, [Monks et al. \(2017\)](#) recollect, propose and evaluate a set of simplification rules dedicated to acute stroke care chains.

While checklists start from observations on model behavior, principles of aggregation work the other way around, by first typifying various notions of aggregation and next applying them to the model. [Frantz \(1995, 1997\)](#) distinguishes between four principles of aggregation, i.e., state aggregation, temporal aggregation, entity aggregation, and function aggregation. According to the principle of state aggregation, states whose distinctions are not relevant considering modeling objectives may be combined. For example, if exact routing of an automated guided vehicle (AGV) transporting goods within a manufacturing system is not relevant for decision making, routes taken and routing logic may be left out of the model. Temporal aggregation seeks to improve computational efficiency by seeking a reduction of the number of events, for example, by assuming that events that occur close in time to be simultaneous. Entity aggregation assumes a higher level entity to represent a collection of lower level entities. Reasons for entity aggregations may be found in both function and structure of the entities. For example, parallel identical machines may be modeled by a single machine with correspondingly shorter processing times, but executing functions similar to the machines being represented. Also, hierarchical structures, like workstations or departments being composed of multiple resources may be represented as a single entity. In a similar way, the notion of a product class may be exploited to refer to a group of products for which mutual differences are not relevant given modeling objectives, see, for example, [Piplani and Puah \(2004\)](#). Finally, function aggregation seeks to combine resource activities. For example, instead of decomposing a maintenance job in several individual activities they may be represented by a compound activity, i.e., the maintenance job.

In principle, component selection for model simplification may further underpinned by dynamic analysis, assuming the presence of a coded model ([Webster & Padgett, 1984](#)). This allows selected components to be assessed for their contributions to overall system performance and – interpreting these – impact on model validity. Components for which a low impact on model validity is confirmed are considered for model complexity reduction, also see [Section 4.1.3](#). Alternatively, analysis may be skipped if sufficient trust has been built ([Law, 1991](#); [Robinson, 2014](#)) or performed using simpler or alternative means, such as, rough cut calculations, analytic approximations for estimating effects of selected components on system performance and/or domain expert judgement. Research by [Hood \(1990\)](#), who puts some common simplifications for simulating semiconductor manufacturing lines to test, and [Jain et al. \(1999\)](#), who study criticality of detailed modeling in semiconductor supply chain simulation, show how validation of simplifications should not be taken lightly.

Several authors suggest the notion of complexity metrics in trying to facilitate an a-priori evaluation of a simulation model specification given some criterion. For example, model characteristics like the quantity of components (for example, number of machines), the quantity of connections (for example, part routings), and the quantity of calculations required in determining which connection to take from each component may set demands on computational resources ([Brooks & Tobias, 2000](#); [Jacobson & Yücesan, 1999](#); [Yücesan & Schruben, 1998](#)). Hence, they may influence model utility in terms of speed of experiments. Likewise, [Wallace \(1987\)](#) proposes the term psychological complexity to capture the complexity of model understanding among users. Although some progress is made in this area, it seems to be still very much in its infancy. [Chwif et al. \(2000\)](#), and [Yavari and Roeder \(2012\)](#) underpin this situation by their finding that no standard measures of complexity are widely accepted. [Chwif, Paul, and Barretto \(2006\)](#) offer some explanation for this by clarifying how the definition

of suchlike measures may be dependent on the choice of a proper model representation technique - making model complexity “tangible” by identifying model elements in a structured way. For an entry and initial results in this area see [Zeigler \(1976\)](#), [Brooks and Tobias \(1996\)](#), [Zeigler, Kim, and Praehofer \(2000\)](#), [Chwif et al. \(2006\)](#), and [Yavari and Roeder \(2012\)](#).

Other reasons for simplifications of model components may concern their weak underpinning by data or information ([Law, 1991](#)), also compare [Section 4.1.1](#) ([Fig. 3](#), right hand side). Identifying suchlike components typically requires scrutinizing model assumptions, and model scope and detail. Rule sets ([Robinson, 2014](#)) and input distributions ([Yavari & Roeder, 2012](#)) present two important examples.

4.1.3. Methods for developing simplifications

How to simplify model components? Two main avenues may be considered, i.e., modifying model component behavior, by leaving out or adjusting its detail or changing component form starting from the principle of black-box modeling ([Pidd, 2004](#)). According to the latter principle (parts of) a real system may be represented as a “black box” that can be observed and for which we can relate its inputs to its outputs.

Choice of model detail may be guided by generic model structures. For example, [Rank, Hummel, Schmidt, and Schneider \(2015\)](#) propose an adjustable base model addressing automated material handling systems of semiconductor fabrication plants. Likewise, [Duarte, Fowler, Knutson, Gel, and Shunk \(2007\)](#), and [Pehrsson, Frantzen, Aslam, and Ng \(2015\)](#) suggest to model manufacturing plants and supply chains by a simplified model, concerning a few standard components. [Morrison \(2011\)](#) proposes deterministic multi-class flow line models for representing semiconductor manufacturing equipment such as multi cluster or clustered photolithography tools being part of an overall fab simulation. Extensions of his work are discussed in [Park, Park, and Morrison \(2017\)](#). A next step may be to combine the notion of generic model structures with automatic model generation ([Bergmann & Strassburger, 2010](#)). This would require the definition of a model generation algorithm that builds models from selecting, configuring and structuring the components, relying on available data sources ([Huang, Verbraeck, & Seck, 2016](#)). Various data sources may be considered, for example, technical data describing the production system, organizational data capturing system planning and control, and system load data ([Bergmann & Strassburger, 2010](#)). In addition, techniques like data and process mining and machine learning may be adopted for interpreting data ([Van der Aalst, 2012](#), [Akhavian & Behzadan, 2013](#); [Bergmann, Feldkamp, & Strassburger, 2017](#)). For example, process mining may be helpful in supporting model simplification of complex manufacturing systems, by distilling main product categories by identifying common routings. Hence, the number of product types modeled may be reduced, also compare [Table 2](#) (“Represent similar products by a single product type”).

Multiresolution modeling seeks to improve computational efficiencies of large models by allowing highly detailed parts to be combined with parts of lower detail within a single model ([Vasudevan & Devikar, 2011](#)). Gains are associated by those parts of lower detail – referring to system elements with a perceived low impact on model validity. By means of a case example concerning automotive final assembly [Vasudevan and Devikar \(2011\)](#) clarify how developments during a project life cycle, for example, new solution directions, may require the addition of more detail to the model. Under these circumstances, they suggest not to change the abstraction level of the whole model. Instead it is advocated to restrict additional detail to selected areas. [Fishwick \(1988\)](#) proposes a taxonomy of process abstraction methods in an effort to characterize the fundamental concepts of traversing levels of detail. The notion of dynamic multiresolution models adds the possibility of changing level of selected model parts detail during simulation ([Celik, Lee, Vasudevan, & Son, 2010](#); [Huber & Dangelmaier, 2011](#)). [Huber and Dangelmaier \(2009\)](#) propose a method

Table 3
Drivers of inappropriate model complexity.

Factor	Driver	References
Modeling objectives	<ul style="list-style-type: none"> • Various model development objectives • Unclear modeling objectives 	<ul style="list-style-type: none"> • Nance et al. (1999), Ahmed et al. (2016) • Innis and Rexstad (1983), Yin and Zhou (1989), Salt (1993), Law (1991), Nance et al. (1999), Chwif, Barretto, and Santoro (1998), Chwif et al., 2000, Yavari and Roeder (2012), Rank et al. (2016) • Henriksen (1989)
	<ul style="list-style-type: none"> • Misfit between model nature and modeling objectives • Problem size • Number of model inputs 	<ul style="list-style-type: none"> • Morris (1967), Salt (1993), Chwif et al. (2000) • Innis and Rexstad (1983), Kim et al. (2003), Yavari and Roeder (2012), Ahmed et al. (2016) • Innis and Rexstad (1983), Yavari and Roeder (2012), Ahmed et al. (2016) • Frantz (1995)
Modeler	<p><u>Educational background</u></p> <ul style="list-style-type: none"> • Limited application domain knowledge <p><u>Personality</u></p> <ul style="list-style-type: none"> • Limited training or experience in modeling • Unfamiliarity with simulation software • Poor modeling practices • Preference for impracticably difficult tasks • Show off: complex models are impressive references of the modeler's skills and work • Joy of creating intricate programs <p><u>Pitfalls</u></p> <ul style="list-style-type: none"> • Considering details as inherently good for increasing realism • Being unsure about what to include • Adding complexity is easy • Difficult to get rid of a complex model <p><u>Stakeholder involvement</u></p> <ul style="list-style-type: none"> • Lack of communication with stakeholders • Project team size 	<ul style="list-style-type: none"> • Innis and Rexstad (1983), Yin and Zhou (1989), Law (1991), Nance et al. (1999), Chwif et al. (2000), Rank et al. (2016), Nance et al. (1999) • Law (1991), Salt (1993), Jain et al. (2001), Chwif et al. (2000), Fowler & Rose, 2004, Ahmed et al. (2016), Rank et al. (2016) • Yin and Zhou (1989), Chwif et al. (2000), Rank et al. (2016) • Innis and Rexstad (1983), Yin and Zhou (1989), Chwif et al. (2000), Yavari and Roeder (2012) • Salt (1993) • Salt (1993), Chwif et al. (2000), Rank et al. (2016) • Salt (1993) • Henriksen (1989), Salt (1993), Chwif et al. (2000) • Chwif et al. (2000), Vasudevan and Devikar (2011) • Salt (1993) • Salt (1993), Rank et al. (2016) • Law et al. (1993) • Ahmed et al. (2016)
Simulation software	<ul style="list-style-type: none"> • Default attribute assignments • Library choice of building blocks • Choice of event list algorithm 	<ul style="list-style-type: none"> • Nance et al. (1999) • Jain et al. (2001), Vasudevan and Devikar (2011) • Henriksen (1983)
Diagramming techniques for model specification	<ul style="list-style-type: none"> • Low abstraction levels employed in capturing a real world manufacturing system 	<ul style="list-style-type: none"> • Liu and Iijima (2015)
Computer hardware	<ul style="list-style-type: none"> • Increasing computational power 	<ul style="list-style-type: none"> • Salt (1993), Brooks and Tobias (1999), Jain et al. (1999), Chwif et al. (2000), Rank et al. (2016)
Data	<ul style="list-style-type: none"> • Availability of detailed data 	<ul style="list-style-type: none"> • Henriksen (1989), Law et al. (1993), Jain et al. (2001), Ahmed et al. (2016)
Methodology	<ul style="list-style-type: none"> • Excess attributes • Manual simulation approaches 	<ul style="list-style-type: none"> • Nance et al. (1999) • Lucko et al. (2010)

for mapping simulation state between models of different level of detail. Celik et al. (2010) propose Dynamic-Data-Driven Application Systems (DDDAS) as a new modeling and control paradigm which adaptively adjusts the detail of a simulation model. The need for adapting model detail is established by using an abnormality detection algorithm that detects deviations of system status that violate thresholds set.

Frantz (1995) mentions how the input/output relationships for a model component may be captured by look-up tables, probability distributions, linear function interpolations, and metamodeling. Further examples are provided by Thomas and Charpentier (2005), Thomas and Thomas (2011), Thomas, Thomas, & Suhner (2011), Thomas, Suhner, & Thomas (2014, 2015) who consider representing non-bottleneck machines by neural networks and regression trees. The use of probability distributions received significant attention in semiconductor manufacturing. To simplify the complex models often found for this field, probability distributions are employed to represent subsystems (aggregates of semiconductor resources) or non-bottleneck machines as delays. Proposed probability distributions account for the fact that delays may be influenced by the work-in-process, and possibilities of parts overtaking each other – due to the re-entrant nature of semiconductor manufacturing (Etman, Veeger, Lefeber, Adan, & Rooda,

2011; Ewen et al., 2017; Kabak, Heavy, & Kernan, 2012; Rose, 2000, 2007; Veeger et al., 2011). For modeling non-bottleneck resources several authors advocate use of fixed time delays, see, for example, Hung and Leachman (1999) and Johnson, Fowler, and Mackulak (2005). Some of the aforementioned work also made an entry in related fields. For example, Jansen, Etman, Rooda, and Adan (2012) explored use of probability distributions proposed for semiconductor manufacturing for modeling resources at a Magnetic Resonance Imaging (MRI) department.

4.1.4. Simplification procedures

Simplification procedures seek to contribute to a comprehensive approach towards model complexity reduction by embedding methods for tracing inappropriate complexity (Section 4.1.2) and developing simplifications (Section 4.1.3) in a step-wise procedure. For example, starting from a detailed manufacturing model, Johnson et al. (2005) propose a simple procedure that (i) establishes a list of machines ordered according to their utilization, (ii) selects those machines with a low utilization from the list and replaces them with constant delays, and (iii) validates the resulting reduced model by comparing its outputs with those found for the detailed model. Similar examples, employing different methods and different manufacturing settings, are given by

Brooks and Tobias (2000), Völker and Gmilkowsky (2003), Huber and Dangelmaier (2009), and Zhou, Cao, Liu, and Zhang (2016).

Apart from their choices of underlying methods and focus on specific manufacturing settings, simplification procedures differ for their algorithmic and/or tool-based support. Use of data flow analysis and expert systems for tracing inappropriate model complexity is advocated by Nance, Overstreet, and Page (1999). Chwif et al. (2006) propose a “backtracking” reduction algorithm that traces those model elements that are not connected to model outputs. Likewise Chiang (2010) proposes the use of evolutionary algorithms in order to choose among a great many alternative model simplifications. Other possibilities for tool-based support are linked to the notion of automatic model generation, see Section 4.1.3. Chwif et al. (2006) clarify how the use of algorithmic and tool-based support requires the use of a proper model representation technique. Sevinc (1990) studies possibilities for the automation of model simplification from a theory-based angle, using a weakened definition of homomorphism for simulation models as a formal basis.

4.2. Preventing model complexity

The efforts that may be involved in model reduction – as indicated in the previous section – present a clear case for the need for preventing inappropriate complexity. Avoiding model complexity builds on the modeler’s awareness of its drivers, and his/her appropriate response once detected. Table 3 shows various drivers, being categorized according to the outcomes of the study set-up, i.e., modeling objectives, (staff) resources available or provided, access to data, and choice of modeling methodology. Checking outcomes of simulation study set-up for respective drivers may be considered as an initial guideline. We found little evidence on more elaborate guidelines informing the modeler on how to act once relevance of specific drivers has been established.

Many authors indicate that poorly understood, conflicting, or too many modeling objectives may significantly contribute to model complexity. This starts from the observation that under these circumstances the modeler may easily be tempted to draw the bounds of the model too wide, hoping to cover whatever the model user is interested in (Salt, 1993). Nance et al. (1999) point out how model development objectives in terms of model portability, extensibility and re-usability may increase model complexity. For example, model re-use may be facilitated by generic – but more elaborate – model components. Pace (2000) nuances the role of modeling objectives as complexity drivers by suggesting modeling objectives and model development to be a “chicken-egg” pair. According to him they may each stimulate and derive from the other, thereby possibly making an iterative and interactive formulation of modeling objectives with the model development beneficial. Urenda Moris, Ng, and Svensson (2008) clarify how such a situation may be encountered in the early development phases of an industrial project. Given a clear lack of information and data, models relying on appropriate simplifications are less accurate, but may contribute to system understanding. In turn, these early insights obtained may be helpful in clarifying modeling objectives.

Another explanation for model complexity may be in the fit between model nature and modeling objectives (Henriksen, 1989). For example, would a “toy model” be more appropriate than a “realistic model”. Or, alternatively, should an “abstract” model be preferred over a “detailed” model? See Henriksen (1989) for further examples on alternative choices of model nature, and the way respective choices set requirements to the model.

Not surprisingly, also size of the underlying problem may contribute to model complexity. Problem size may be at a debate if it can be split into simpler problems (Morris, 1967; Courtois, 1985; Salt, 1993; Chwif et al., 2000). Likewise, the presence of many model inputs may act as an indicator of excess model detail (Ahmed et al., 2016; Innis & Rexstad, 1983; Kim, Shim, Choi, & Hwang, 2003; Yavari & Roeder, 2012).

Ideally, some a-priori prove of their relevance is provided building on good reasoning and/or quantitative approximations. Note that, in some cases, implementation of model inputs may imply a modeling exercise of its own. Frantz (1995) hints at the relevance of acknowledging input space, i.e., the conditions under which the system is going to be studied. For example, is it necessary to put a system to the test for fluctuating workloads or is it allowed to focus on its behavior for a single high workload level only. The latter case may allow for model simplifications such as leaving out scheduling logic or approximating queueing behavior.

Most drivers of model complexity are associated with the modeler. We consider four subcategories of drivers, i.e., those that relate to the modeler’s educational background and, personality, possible pitfalls that may be encountered by him/her, and his/her interaction with stakeholders. Novice modelers may easily be tempted to solve modeling issues by adding detail, because they are not aware of alternative lean modeling solutions or coding tricks, not familiar with the domain, or do not (fully) understand potential benefits of simpler models. Note that the likelihood of modelers encountering pitfalls may be related with their modeling training and experience. For example, it may take some time to find out that more detail does not necessarily improve model accuracy (Henriksen, 1989; Chwif et al., 2000). Salt (1993) clarifies how various aspects of a modeler’s personality may impact on model complexity. This may refer to the modeler’s enthusiasm in developing more fancy models, and/or a belief that more complex models are more impressive, i.e., give a better account of modeling competences and the amount of work done, or may more easily convince the client. Finally, Law et al. (1993) and Ahmed et al. (2016) indicate how model complexity may be a net consequence of a lack of stakeholder interaction.

Choice and availability of supportive modeling tools and methodology may present other challenges for the modeler. Increasing computational power may easily add to model complexity, simply because it is there (Chwif et al., 2000). On the other hand, choice of modeling formalisms and methodology may guide the modeler in including (too) much detail by building on generic building blocks meant to address a large class of systems (Jain, Workman, Collins, Ervin, & Lathrop, 2001; Liu & Iijima, 2015; Nance et al., 1999; Vasudevan & Devikar, 2011). Likewise, availability of detailed input data may make the modeler tempted to choose the scope and level of detail for the model accordingly (Henriksen, 1989). Lucko, Benjamin, Swaminathan, and Madden (2010) clarify how the great flexibility entailed by manual simulation generation approaches vs. domain specific (semi)automated simulation generation approaches together with a modeler’s lack of domain knowledge may add to model detail.

Many researchers suggest to prevent model complexity by advocating an evolutionary development of the model, i.e., start with an (overly) simple model and next add detail incrementally until the model is considered valid for its purpose (Pidd, 1999; Robinson, 2008a; Sánchez, 2006). By being (somewhat) in control of modeling steps such an approach may be helpful – although it comes at the cost of an initial set of simplifications relative to the (would be) system under study (Brooks & Tobias, 2000). Also it does not deny relevance of the above complexity drivers.

4.3. Linking activities – Root cause analysis

In previous sections we discussed the two main activities associated with model simplification. Both activities may be linked in case successful model reduction requires reconsidering study set-up. For example, if the need for model reduction is a net effect of poor modeling skills, training of the modeler may be required to improve his/her modeling skills and – next – the model. In the latter case a root-cause analysis may be appropriate which links observations on the model and its development to possible complexity drivers, compare Table 3.

So far, researchers did not acknowledge the need for a root-cause analysis questioning outcomes of the study set-up as a prerequisite for

successful model reduction. A likely reason is in their focus on developing methods for model complexity reduction, rather than questioning model development so far. Starting from main categories of complexity drivers shown in Table 3 many indicators can be defined that may be helpful in establishing the need for such a root-cause analysis. Examples include unclear modeling objectives, poor modeling or coding, large detailed models, lack of communication among stakeholders, and a high number of model inputs, state variables and outputs. In turn, complexity metrics may be associated with these indicators, see Section 4.1.2. Clearly, more research is required supporting questions on when and how to do a root-cause analysis. Concerning the latter question, Vasudevan and Devikar (2011) suggest the use of simple lean techniques like the “5 whys” in analyzing the need for model detail.

4.4. Framework extensions – coded model and experimental frame

Main focus of our framework is on modeling support for simplifying the conceptual model. In this section we explore extensions of the framework towards development of the coded model and experimental frame. Our exploration is restricted to its support for model reduction, compare Section 4.1. It is likely that findings on preventing inappropriate model complexity will also apply to the coded model and experimental frame. However, further research is required to support this thesis, and refine findings given model specifics.

Support for simplifying coded models may be related to development, choice and good use of simulation software. Henriksen (2008) discusses technical requirements for simulation software development that may contribute to a reduction of model complexity by enhancing model development and use. Starting from examples he highlights demands to be put on meaning and availability of language constructs, openness of source code, model extensibility, and model interfacing. Yuan and Ponsignon (2014) develop a dedicated library of building blocks targeting supply chains in semiconductor manufacturing aiming to reduce modeling efforts. Rank et al. (2015) propose a high-level base model for simulating automated material handling systems in wafer fabs, aiming to speed up model execution – as a net effect of reducing model detail.

Innis and Rexstad (1983) clarify how an appropriate choice of simulation software may contribute to model simplification by requiring less code, as the language facilitates an easy mapping of the real-world system on model components, and exploits system properties in model analysis. Recent work on (semi)automated model generation builds on this finding by suggesting the development and use of a library of domain specific model components, allowing for the construction of models using a model generation algorithm (Bergmann et al., 2017; Huang et al., 2016; Lucko et al., 2009, 2010).

Once a choice has been made for a specific simulation software package, it is up to the modeler to make good use of it. This refers to code readability, debugging, and execution speed (Brooks & Tobias, 2000; Frantz, 1997; Innis & Rexstad, 1983). Wallace (1987), Yücesan and Schruben (1998), and Popovics and Monostori (2016) provide metrics which may be helpful in assessing algorithmic and computational complexity of the coded model. Akpan and Shanker (2017) consider the realized benefits and costs associated with modeling and simulation in 3D and virtual reality through a descriptive meta-analysis of evidence from research and practice.

Various authors suggest to simplify the experimental frame by leaving out model inputs or restricting their range (Kim et al., 2003; Yavari & Roeder, 2012). Rank et al. (2016) clarify the need to legitimize the choice of input factors and their range by static deterministic estimates of system performance. Assuming presence of a coded model, McGraw and MacDonald (2000) suggest alternative experimental designs, like extremum experimentation, factorial experimentation, and input sensitization as means for tracing inputs that may be omitted. Furthermore, Innis and Rexstad (1983), and Fowler and Rose (2004) advocate the use of variance reduction techniques to

reduce run lengths, and – hence – computational efforts.

5. Discussion

In the previous section, we have described a framework for simulation model simplification, thereby building on an extensive literature review. We elaborate on the contributions to research and practice, and highlight some potential research directions.

5.1. Contributions to research

The first research contribution is in formulating a framework that incorporates and structures existing knowledge on simulation model simplification for the manufacturing domain. It organizes research contributions in terms of methods, good practices and insights by relating them to two main activities, i.e., reduction and prevention of inappropriate model complexity, and linking these activities to simulation study set-up and the modeling process respectively. Reduction of model complexity entails cost-benefit analysis of model simplification, tracing of inappropriate model complexity, and development and validation of model simplifications. Prevention of inappropriate model complexity is linked to the notion of complexity drivers, concerning the definition of modeling objectives, modeler's skills, available hardware and software tools, choice of modeling methodology and access to data. Both activities may be coupled if successful model reduction may benefit from reconsidering study set-up – as indicated by a root-cause analysis.

The second research contribution of the framework is in serving as a starting point for future research by allowing for the identification of patterns of research development, current research avenues, and research gaps. Early research contributions paved the way by clarifying relevance of the field in terms of the benefits of simplification, compare Table 1. They allowed for further contributions to theory, concerning insights on drivers of complexity (compare Table 3) and simplification methods that are helpful in tracing inappropriate complexity, and development and validation of model simplifications. As far as simplification methods are concerned two research avenues emerged. A first avenue concerns the development of (automated) simplification procedures, i.e., comprehensive methods that address both tracing of inappropriate model complexity, and development of model simplifications. In most cases research on model simplification assumes a manual approach towards modeling – being still the dominant approach. Alternatively, emergence of automated simulation generation approaches sets a new perspective for providing guidance on model simplification by seeking to exploit re-use of domain specific knowledge in terms of elementary building blocks and their construction. In addition, techniques like, for example, data and process mining and machine learning may be helpful in tracing and developing simplifications by interpreting manufacturing data. A second avenue is associated with contributions concerning domain related simplification methods. Main examples concern simplification methods proposed and validated for use in semiconductor manufacturing simulation. We observed how, so far, main focus in research has been on simplification of the conceptual model, rather than the coded model and experimental frame. A likely explanation is in the impact of the conceptual model – acting as a precursor for the coded model and experimental frame – on modeling efforts and study success.

Despite its age, spanning many decades, the field is still rather green. Among others, this may be clarified by a relatively low number of journal articles addressing it. Clearly, this does not deny the relevance of contributions made, and the highly relevant body of knowledge – as captured in the framework – that emerged from these. At the same time many opportunities for future research may be mentioned addressing observed gaps. Without pretending to offer a complete list, we mention the following themes: method-based support for doing cost-benefit analysis for model simplification, developing

standardized metrics for assessing model complexity, validation of model simplifications, theory building enabling automation of model simplification, simplification of model representation, guidelines for preventing inappropriate model complexity, lean techniques for root-cause analysis seeking to explain model complexity from study set-up, and domain-based simplification procedures – also outside semiconductor manufacturing. Clearly, building on the framework, more opportunities may be mentioned, thereby serving the development of research agenda's and fostering the academic debate. In addressing aforementioned issues there is a great need for validating research findings by empirical research. So far, we found how insights provided on cost and benefits of simplification, complexity drivers and proposed methods often lack a rigorous validation.

The third contribution of the research framework may be in acting as a vehicle for research itself. The framework may be used as a starting point for addressing other domains, especially the (health) service industry. Starting from observations on case examples in literature we found how several simplification methods originating from the manufacturing scene made an entry in the service industry. Methods suggesting to group patients sharing similar needs, or simplifying low-utilized (staff) resources are much encountered, see for example Virtue, Chausselet, and Kelly (2011), Higgins, Claudio, and Waliullah (2014), Tako, Kotiadis, Vasilakis, Miras, and Le Roux (2014). Similar examples may be found in finance, where simulation models are simplified by reducing routing options of products (Anderson & Morrice, 1999). We also encountered few examples in service industry being of relevance for the manufacturing domain, thereby underlining the benefits of cross fertilization. Apart from suchlike evidence, research seems to have hardly touched the service industry. Furthermore, we mention the framework's possible use for addressing other types of simulation like agent-based simulation and system dynamics.

5.2. Contributions to practice

The relevance of model simplification for practical use of simulation in the manufacturing domain is undeniable. Moreover, the ever increasing complexity of manufacturing systems suggests an increasing importance of model simplification in targeting and being responsive to management problems. Progress made in simulation software and computer hardware will not likely change this situation in the near future (Chwif et al., 2006). A main problem faced by practitioners concerning model simplification is a lack of overview on what research on model simplification is available, thereby hindering their access to relevant means of support. Furthermore, we observe a missing link, as educational materials for training their skills in employing simplification methods are hardly available. Hence, practitioners are more or less left on their own creativity in addressing model simplification.

The framework contributes to solving issues faced by practitioners by providing an overview of current research. By organizing it according to the framework it is meant to (i) facilitate an easy linkage of decisions to be made in study set-up and the way they may impact model complexity, and (ii) offer modeling support by categorizing simplification methods according to their roles for tracing inappropriate complexity and developing modeling simplifications. In turn, by organizing the field we strive to benefit educators and their students by providing an initial basis for the development of course materials.

6. Conclusion

In summary, this article proposes a framework for simulation model simplification. Building on an extensive literature review, our study contributes to literature in several ways. Firstly, it structures the field by providing a unifying view on simulation model simplification, in terms of its key activities and support offered in performing these. In doing so it clarifies the way model simplification relates to study set-up

and the modeling process. Apart from its relevance as a starting point for future research, the structuring of the field implies direct benefits for practitioners and educators, by giving them access to research findings, and enabling and legitimizing development of educational materials and their uptake. Secondly, the framework facilitates development of research agenda's and fosters academic debate by allowing for the identification of patterns of research development, current research avenues, and research gaps.

Acknowledgements

Some preliminary findings of the literature review were presented in: Van der Zee, D.J. 2017. "Approaches for Simulation Model Simplification". In W.K.V. Chan, A. D'Ambrogio, G. Zacharewicz, N. Mustafee, G. Wainer, and E. Page (Eds.), *Proceedings of the 2017 Winter Simulation Conference* (pp. 4197–4208). Piscataway, NJ: IEEE.

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

References

- Ahmed, R., Shah, M., & Umar, M. (2016). Concepts of simulation model size and complexity. *International Journal of Simulation Modelling*, 15(2), 213–222.
- Akhavan, R., & Behzadan, A. H. (2013). Automated knowledge discovery and data-driven simulation model generation of construction operations. In R. Pasupathy, S.-H. Kim, A. Tol, R. Hill, & M. E. Kuhl (Eds.), *Proceedings of the 2013 winter simulation conference* (pp. 3030–3041). Piscataway, NJ: IEEE.
- Akpan, J., & Shanker, M. (2017). The confirmed realities and myths about the benefits and costs of 3D visualization and virtual reality in discrete event modeling and simulation: A descriptive meta-analysis of evidence from research and practice. *Computers & Industrial Engineering*, 112, 197–211.
- Anderson, E. G., & Morrice, D. J. (1999). A Simulation Model to Study the Dynamics in a Service-Oriented Supply Chain. In P. A. Farrington, H. B. Nemphard, D. T. Sturrock, & G. W. Evans (Eds.), *Proceedings of the 1999 Winter Simulation Conference* (pp. 742–748). Piscataway, NJ: IEEE.
- Astrup, R., Coates, K. D., & Hall, E. (2008). Finding the appropriate level of complexity for a simulation model: An example with a forest growth model. *Forest Ecology and Management*, 256, 1659–1665.
- Barlow, J. (2009). Simplification: Ethical implications for modelling and simulation. In R. S. Anderssen, R. D. Braddock, & L. T. H. Newham (Eds.), *18th World IMACS congress and MODSIM09 international congress* (pp. 432–438). Cairns: IMACS and MSSANZ.
- Benjamin, P., Erraguntla, M., Delen, D., & Mayer, R. (1998). Simulation modeling at multiple levels of abstraction. In D. J. Medeiros, E. F. Watson, J. S. Carson, & M. S. Manivannan (Eds.), *Proceedings of the 1998 winter simulation conference* (pp. 391–398). Piscataway, NJ: IEEE.
- Bergmann, S., Feldkamp, N., & Strassburger, S. (2017). Emulation of Control Strategies through Machine Learning in Manufacturing Simulations. *Journal of Simulation*, 11, 38–50.
- Bergmann, S., & Strassburger, S. (2010). Challenges for the Automatic Generation of Simulation Models for Production Systems. *Proceedings of the 2010 Summer Simulation Multiconference, SummerSim 2010* (pp. 545–549). Ottawa: SCS.
- Brooks, R. J., & Tobias, A. M. (1996). Choosing the best model: Level of detail, complexity, and model performance. *Mathematical and Computer Modelling*, 24(4), 1–14.
- Brooks, R. J., & Tobias, A. M. (1999). Methods and benefits of simplification in simulation. In D. Al-Dabass, & R. Cheng (Eds.), *Fourth national conference of the UK simulation society* (pp. 88–92). Cambridge: UK Simulation Society.
- Brooks, R. J., & Tobias, A. M. (2000). Simplification in the simulation of manufacturing systems. *International Journal of Production Research*, 38(5), 1009–1027.
- Celik, N., Lee, S., Vasudevan, K., & Son, Y. (2010). DDDAS-based multi-fidelity simulation framework for supply chain systems. *IISE Transactions*, 42(5), 325–341.
- Chiang, T. C. (2010). Model simplification for accelerating simulation-based evaluation of dispatching rules in wafer fabrication facilities. *11th international conference control, automation, robotics and vision* (pp. 2005–2011). Singapore: IEEE.
- Chwif, L., Barretto, M. R. P., & Santoro, M. C. (1998). Model Reduction: Some results. *Proceedings of the 31st Annual Simulation Symposium* (pp. 120–125). Los Alamitos, CA: IEEE Computing Society.
- Chwif, L., Barretto, M. R. P., & Paul, R. J. (2000). On simulation model complexity. In J. A. Joines, R. R. Barton, K. Kang, & P. A. Fishwick (Eds.), *Proceedings of the 2000 winter simulation conference* (pp. 449–455). Piscataway, NJ: IEEE.
- Chwif, L., Paul, R. J., & Barretto, M. R. P. (2006). Discrete event simulation model reduction: A causal approach. *Simulation Modelling Practice and Theory*, 14, 930–944.
- Courtois, P. J. (1985). On time and space decomposition of complex structures. *Communications of the ACM*, 28(6), 590–603.
- Davies, R., Roderick, P., & Raftery, J. (2003). The evaluation of disease prevention and treatment using simulation models. *European Journal of Operational Research*, 150, 53–66.
- Duarte, B., Fowler, J. W., Knutson, K., Gel, E., & Shunk, D. (2007). A compact abstraction of manufacturing nodes in a supply network. *International Journal of Simulation and Process Modelling*, 3(3), 115–126.

- Edmonds, B., & Moss, S. (2004). From KISS to KIDS – An ‘Anti-simplistic’ modelling approach. *International workshop on multi-agent systems and agent-based simulation 2004. Lecture notes in computer science book series* (pp. 130–144). New York: Springer.
- Etman, L. F. P., Veegeer, C. P. L., Lefeber, E., Adan, I. J. B. F., & Rooda, J. E. (2011). Aggregate modeling of semiconductor equipment using effective process times. In S. Jain, R. R. Creasy, J. Himmelsbach, K. P. White, & M. Fu (Eds.). *Proceedings of the 2011 winter simulation conference* (pp. 1790–1820). Piscataway, NJ: IEEE.
- Ewen, H., Mönch, L., Ehm, H., Ponsignon, T., Fowler, J. W., & Forstner, L. (2017). A testbed for simulating semiconductor supply chains. *IEEE Transactions on Semiconductor Manufacturing*, 30(3), 293–305.
- Fishwick, P. A. (1988). The role of process abstraction in simulation. *IEEE Transactions on Systems, Man, and Cybernetics*, 18(1), 18–39.
- Fletcher, A., Halsall, D., Huxham, S., & Worthington, D. (2007). The DH Accident and Emergency Department model: a national generic model used locally. *Journal of the Operational Research Society*, 58, 1554–1562.
- Fowler, J. W., Mönch, L., & Ponsignon, T. (2015). Discrete-event simulation for semiconductor wafer fabrication facilities: A tutorial. *International Journal of Industrial Engineering: Theory, Applications and Practice*, 22(5), 661–682.
- Fowler, J. W., & Rose, O. (2004). Grand challenges in modeling and simulation of complex manufacturing systems. *Simulation*, 80(9), 469–476.
- Frantz, F. K. (1995). A taxonomy of model abstraction techniques. In C. Alexopoulos, K. Kang, W. R. Lilegdon, & D. Goldsman (Eds.). *Proceedings of the 1995 winter simulation conference* (pp. 1413–1420). Piscataway, NJ: IEEE.
- Frantz, F. K. (1997). Analyzing models for abstraction. In A. F. Sisti (Ed.). *Proceedings of SPIE Volume 3083* (pp. 14–21). Orlando, FL: SPIE.
- Fripp, J. (1985). How effective are models? *Omega*, 13(1), 19–28.
- Harrison, J. R., Lin, Z., Carroll, G. R., & Carley, K. M. (2007). Simulation Modeling in Organizational and Management Research. *The Academy of Management Research*, 32(4), 1229–1245.
- Henriksen, J. O. (1983). Event list management—A tutorial. In S. Roberts, G. Banks, & B. W. Schneiser (Eds.). *Proceedings of the 1983 winter simulation conference* (pp. 543–552). Piscataway, NJ: IEEE.
- Henriksen, J. O. (1989). Alternative modeling perspectives: Finding the creative spark. In E. A. Macnair, K. J. Musselman, & P. Heidelberger (Eds.). *Proceedings of the 1989 winter simulation conference* (pp. 648–652). Piscataway, NJ: IEEE.
- Henriksen, J. O. (2008). Taming the complexity dragon. *Journal of Simulation*, 2(1), 3–17.
- Higgins, A., Claudio, D., & Waliullah, M. (2014). A Detailed Simulation Model of an Infusion Treatment Center. In A. Tolk, Y. Diallo, I. O. Ryzhov, L. Yilmaz, S. Buckley, & J. A. Miller (Eds.). *Proceedings of the 2014 Winter Simulation Conference* (pp. 1198–1209). Piscataway, NJ: IEEE.
- Hood, S. J. (1990). Detail vs. Simplifying Assumptions for Simulating Semiconductor Manufacturing Lines. In IEMT Symposium, 9th IEEE/CHMT International (pp. 103–108).
- Huang, Y., Verbraeck, A., & Seck, M. (2016). Graph Transformation Based Simulation Model Generation. *Journal of Simulation*, 10, 283–309.
- Huber, D., & Dangelmaier, W. (2009). Controlled simplification of material flow simulation models. In M. D. Rossetti, R. R. Hill, B. Johansson, A. Dunkin, & R. G. Ingalls (Eds.). *Proceedings of the 2009 winter simulation conference* (pp. 839–850). Piscataway, NJ: IEEE.
- Huber, D., & Dangelmaier, W. (2011). A method for simulation state mapping between discrete event material flow models of different level of detail. In S. Jain, R. R. Creasy, J. Himmelsbach, K. P. White, & M. Fu (Eds.). *Proceedings of the 2011 winter simulation conference* (pp. 2872–2881). Piscataway, NJ: IEEE.
- Hung, Y. F., & Leachman, R. C. (1999). Reduced simulation models of wafer fabrication facilities. *International Journal of Production Research*, 37(12), 2685–2701.
- Innis, G., & Rexstad, E. (1983). Simulation model simplification techniques. *Simulation*, 7–15.
- Jacobson, S. H., & Yücesan, E. (1999). On the complexity of verifying structural properties of discrete event simulation models. *Operations Research*, 47(3), 476–481.
- Jain, S., Lim, C. C., Gan, B. P., & Low, Y. H. (1999). Criticality of Detailed Modeling in Semiconductor Supply Chain Simulation. In P. A. Farrington, H. B. Nemhard, D. T. Sturrock, & G. W. Evans (Eds.). *Proceedings of the 1999 winter simulation conference* (pp. 888–896). Piscataway, NJ: IEEE.
- Jain, S., Workman, R. W., Collins, L. M., Ervin, E. C., & Lathrop, A. P. (2001). Development of a high-level supply chain simulation model. In B. A. Peters, J. S. Smith, D. J. Medeiros, & M. W. Rohrer (Eds.). *Proceedings of the 2001 winter simulation conference* (pp. 1129–1137). Piscataway, NJ: IEEE.
- Jansen, F. J. A., Etman, L. F. P., Rooda, J. E., & Adan, I. J. B. F. (2012). Aggregate Simulation Modeling of an MRI Department Using Effective Process Times. In C. Laroque, J. Himmelsbach, R. Pasupathy, O. Rose, & A. M. Uhrmacher (Eds.). *Proceedings of the 2012 Winter Simulation Conference* (pp. 1–12). Piscataway, NJ: IEEE.
- Jimenez, J. A., Mackulak, G. T., & Fowler, J. W. (2008). Levels of capacity and material handling system modeling for factory integration decision making in semiconductor wafer fabs. *IEEE Transactions on Semiconductor Manufacturing*, 21(4), 600–613.
- Johnson, R. T., Fowler, J. W., & Mackulak, G. T. (2005). A Discrete event simulation model simplification technique. In M. E. Kuhl, N. M. Steiger, F. B. Armstrong, & J. A. Joines (Eds.). *Proceedings of the 2005 winter simulation conference* (pp. 2172–2176). Piscataway, NJ: IEEE.
- Kabak, K. E., Heavy, C., & Kernan, B. (2012). Single toolset modeling approaches in semiconductor manufacturing. In C. Laroque, J. Himmelsbach, R. Pasupathy, O. Rose, & A. M. Uhrmacher (Eds.). *Proceedings of the 2012 winter simulation conference* (pp. 2273–2283). Piscataway, NJ: IEEE.
- Kim, Y. D., Shim, S. O., Choi, B., & Hwang, H. (2003). Simplification methods for accelerating simulation-based real-time scheduling in a semiconductor wafer fabrication facility. *IEEE Transactions on Semiconductor Manufacturing*, 16(2), 290–298.
- Kotiadi, K., & Robinson, S. (2008). Conceptual modelling: Knowledge acquisition and model abstraction. In S. J. Mason, R. R. Hill, L. Mönch, O. Rose, T. Jefferson, & J. W. Fowler (Eds.). *Proceedings of the 2008 Winter Simulation Conference* (pp. 951–958). Piscataway, NJ: IEEE.
- Law, A. M. (1991). Simulation model's level of detail determines effectiveness. *Industrial Engineering*, 23(10), 16–18.
- Law, A. M. (2015). *Simulation Modeling and Analysis* (5th ed.). New York: McGraw-Hill.
- Law, A. M., Carson, J. S., Fox, J. G., Halladin, S. K., Musselman, K. J., & Ulgen, O. M. (1993). A forum on crucial issues in the simulation of manufacturing systems. In G. W. Evans, M. Mollaghasemi, E. C. Russell, & W. E. Biles (Eds.). *Proceedings of the 1993 winter simulation conference* (pp. 916–922). Piscataway, NJ: IEEE.
- Liu, Y., & Iijima, J. (2015). Business process simulation in the context of enterprise engineering. *Journal of Simulation*, 9, 206–222.
- Lucko, G., Benjamin, P. C., Swaminathan, K., & Madden, M. G. (2009). Rapid deployment of simulation models for building construction applications. In M. D. Rossetti, R. R. Hill, B. Johansson, A. Dunkin, & R. G. Ingalls (Eds.). *Proceedings of the 2009 winter simulation conference* (pp. 2733–2744). Piscataway, NJ: IEEE.
- Lucko, G., Benjamin, P. C., Swaminathan, K., & Madden, M. G. (2010). Comparison of manual and automated simulation generation approaches and their use for construction applications. In B. Johansson, S. Jain, J. Montoya-Torres, J. Hagan, & E. Yücesan (Eds.). *Proceedings of the 2010 winter simulation conference* (pp. 3132–3144). Piscataway, NJ: IEEE.
- Maier, J. F., Eckert, C. M., & Clarkson, P. J. (2017). Model granularity in engineering design – concepts and framework. *Design Science*, 3, e1.
- McGraw, R. M., & MacDonald, R. A. (2000). Abstract modeling for engineering and engagement level simulations. In J. A. Joines, R. R. Barton, K. Kang, & P. A. Fishwick (Eds.). *Proceedings of the 2000 winter simulation conference* (pp. 326–334). Piscataway, NJ: IEEE.
- Monks, T., Van der Zee, D. J., Lahr, M., Allen, M., Pearn, K., James, M. A., ... Luijckx, G. J. (2017). A framework to accelerate simulation studies of hyperacute stroke systems. *Operations Research for Health Care*, 15, 57–67.
- Morris, W. T. (1967). On the art of modeling. *Management Science*, 13(12), B707–B717.
- Morrison, J. R. (2011). Multiclass flow line models of semiconductor manufacturing equipment for fab-level simulation. *IEEE Transactions of Automation Science and Engineering*, 8(1), 81–94.
- Musselman, K. J. (1994). Guidelines for simulation project success. In J. D. Tew, S. Manivannan, D. A. Sadowski, & A. F. Selles (Eds.). *Proceedings of the 1994 winter simulation conference* (pp. 88–95). Piscataway, NJ: IEEE.
- Nance, R. E., Overstreet, C. M., & Page, E. H. (1999). Redundancy in model specifications for discrete event simulation. *ACM Transactions on Modeling and Computer Simulation*, 9(3), 254–281.
- Negahban, A., & Smith, J. S. (2014). Simulation for manufacturing system design and operation: Literature review and analysis. *Journal of Manufacturing Systems*, 33(2), 241–261.
- Ormerod, R. J. (2001). The Success and Failure of Methodologies – A Comment on Connel (2001): Evaluating Soft OR. *The Journal of the Operational Research Society*, 52(10), 1176–1179.
- Pace, D. K. (2000). Ideas about simulation conceptual model development. *Johns Hopkins APL Technical Digest*, 21(3), 327–336.
- Park, J. Y., Park, K., & Morrison, J. R. (2017). Models of clustered photolithography tools for fab-level simulation: From affine to flow line. *IEEE Transactions on Semiconductor Manufacturing*, 30(4), 547–558.
- Pegden, C. D., Shannon, R. E., & Sadowski, R. P. (1990). *Introduction to Simulation Using SIMAN*. New York: McGraw-Hill.
- Pehrsson, L., Frantzén, M., Aslam, T., & Ng, A. H. C. (2015). Aggregated line modeling for simulation and optimization of manufacturing systems. In L. Yilmaz, W. K. V. Chan, I. Moon, T. M. K. Roeder, C. Macal, & M. D. Rossetti (Eds.). *Proceedings of the 2015 winter simulation conference* (pp. 3632–3643). Piscataway, NJ: IEEE.
- Pidd, M. (1999). Just Modeling Through: A Rough Guide to Modeling. *Interfaces*, 29(2), 118–132.
- Pidd, M. (2004). *Computer Simulation in Management Science* (5th ed.). Chichester: Wiley.
- Piplani, R., & Puah, S. A. (2004). Simplification strategies for simulation models of semiconductor facilities. *Journal of Manufacturing Technology Management*, 15, 618–625.
- Popovics, G., & Monostori, L. (2016). An approach to determine simulation model complexity. *Procedia CIRP*, 52, 257–261.
- Rank, S., Hummel, C., Schmidt, T., Müller, J., Wenzel, A., Lasch, R., & Schneider, G. (2016). The correct level of model complexity in semiconductor fab simulation-lessons learned from practice. *Advanced semiconductor manufacturing conference 2016* (pp. 133–139). IEEE: Saratoga Springs, NY.
- Rank, S., Hummel, C., Schmidt, T., & Schneider, G. (2015). Reducing simulation model complexity by using an adjustable base model for path-based automated material handling systems – A case study in the semiconductor industry. In L. Yilmaz, W. K. V. Chan, I. Moon, T. M. K. Roeder, C. Macal, & M. D. Rossetti (Eds.). *Proceedings of the 2015 winter simulation conference* (pp. 2896–2907). Piscataway, NJ: IEEE.
- Rexstad, E., & Innis, G. S. (1985). Model simplification – Three applications. *Ecological Modelling*, 27, 1–13.
- Robinson, S. (1994). Simulation Projects: Building the Right Conceptual Model. *Industrial Engineering*, 26(9), 34–36.
- Robinson, S. (2006). Conceptual modeling for simulation: Issues and research. In L. F. Perrone, F. R. Wieland, J. Liu, B. G. Lawson, D. M. Nicol, & R. M. Fujimoto (Eds.). *Proceedings of the 2006 winter simulation conference* (pp. 792–800). Piscataway, NJ: IEEE.
- Robinson, S. (2008b). Conceptual modelling for simulation Part II: A framework for conceptual modelling. *Journal of the Operational Research Society*, 59(3), 291–304.
- Robinson, S. (2008a). Conceptual modelling for simulation Part I: Definition and requirements. *Journal of the Operational Research Society*, 59(3), 278–290.

- Robinson, S. (2014). *Simulation – The Practice of Model Development and Use* (2nd ed.). London: Palgrave.
- Rose, O. (2000). Why do Simple Wafer Fab Models fail in certain scenarios? In J. A. Joines, R. R. Barton, K. Kang, & P. A. Fishwick (Eds.). *Proceedings of the 2000 winter simulation conference* (pp. 1481–1490). Piscataway, NJ: IEEE.
- Rose, O. (2007). Improved simple simulation models for semiconductor wafer factories. In S. G. Henderson, B. Biller, M. H. Hsieh, J. Shortle, J. D. Tew, & R. R. Barton (Eds.). *Proceedings of the 2007 winter simulation conference* (pp. 1708–1712). Piscataway, NJ: IEEE.
- Salt, J. D. (1993). Keynote address: Simulation should be easy and fun!. In G. W. Evans, M. Mollaghasemi, E. C. Russell, & W. E. Biles (Eds.). *Proceedings of the 1993 winter simulation conference* (pp. 1–6). Piscataway, NJ: IEEE.
- Sánchez, P. J. (2006). As simple as possible, but no simpler: A gentle introduction to simulating modeling. In L. F. Perrone, F. P. Wieland, J. Liu, B. G. Lawson, D. M. Nicol, & R. M. Fujimoto (Eds.). *Proceedings of the 2006 winter simulation conference* (pp. 2–10). Piscataway, NJ: IEEE.
- Schruben, L., & Yücesan, E. (1993). Complexity of simulation models: A graph theoretic approach. In G. W. Evans, M. Mollaghasemi, E. C. Russell, & W. E. Biles (Eds.). *Proceedings of the 1993 winter simulation conference* (pp. 641–649). Piscataway, NJ: IEEE.
- Sevinc, S. (1990). Automation of simplification in discrete event modelling and simulation. *International Journal of General Systems*, 18, 125–142.
- Sevinc, S. (1991). Theories of discrete event model abstraction. In B. L. Nelson, W. D. Kelton, & G. M. Clark (Eds.). *Proceedings of the 1991 winter simulation conference* (pp. 1115–1119). Piscataway, NJ: IEEE.
- Shannon, R. E. (1998). Introduction to the art and science of simulation. In D. J. Medeiros, E. F. Watson, J. S. Carson, & M. S. Manivannan (Eds.). *Proceedings of the 1998 winter simulation conference* (pp. 7–14). Piscataway, NJ: IEEE.
- Sinreich, D., & Marmor, Y. N. (2004). A Simple and Intuitive Simulation Tool for Analyzing Emergency Department Operations. In R. G. Ingalls, M. D. Rossetti, J. S. Smith, & B. A. Peters (Eds.). *Proceedings of the 2004 winter simulation conference* (pp. 1994–2002). Piscataway, NJ: IEEE.
- Spiegel, M., Reynolds, P. F., Jr., & Brogan, D. C. (2005). A case study of model context for simulation composability and reusability. In M. E. Kuhl, N. M. Steiger, F. B. Armstrong, & J. A. Joines (Eds.). *Proceedings of the 2005 winter simulation conference* (pp. 437–444). Piscataway, NJ: IEEE.
- Tako, A., Kotiadis, K., Vasillakis, C., Miras, A., & Le Roux, C. W. (2014). Improving Patient Waiting Times: A Simulation Study of an Obesity Care Service. *BMJ Quality & Safety*, 23, 373–381.
- Thomas, A., & Charpentier, P. (2005). Reducing simulation models for scheduling manufacturing facilities. *European Journal of Operational Research*, 161, 111–125.
- Thomas, P., Suhner, M. C., & Thomas, A. (2014). CART for supply chain simulation models reduction: Application to a sawmill internal supply chain. In B. Grabot, B. Vallespir, S. Gomes, A. Bouras, & D. Kiritsis (Eds.). *APMS 2014, Part III, IFIP AICT 440* (pp. 530–537). Ajaccio: Springer.
- Thomas, P., Suhner, M. C., & Thomas, A. (2015). Reduced simulation model for flow analysis in a sawmill internal supply chain. In J. M. Framinan, P. Perez Gonzalez, & A. Artiba (Eds.). *6th IESM Conference 2015*. Seville: IEEE.
- Thomas, P., & Thomas, A. (2011). Multilayer perceptron for simulation models reduction: Application to a sawmill workshop. *Engineering Applications of Artificial Intelligence*, 24, 646–657.
- Thomas, P., Thomas, A., & Suhner, M. C. (2011). A neural network for the reduction of a product-driven system emulation model. *Production Planning & Control*, 22(8), 767–781.
- Urenda Moris, M., Ng, A. H. C., & Svensson, J. (2008). Simplification and aggregation strategies applied for factory analysis in conceptual phase using simulation. In S. J. Mason, R. R. Hill, L. Mönch, O. Rose, T. Jefferson, & J. W. Fowler (Eds.). *Proceedings of the 2008 Winter Simulation Conference* (pp. 1913–1921). Piscataway, NJ: IEEE.
- Van der Aalst, W. (2012). Process Mining: Overview and Opportunities. *ACM Transactions on Management Information Systems*, 3(2) article 7.
- Van der Zee, D. J., Brooks, R. J., Robinson, S., & Kotiadis, K. (2011). Conceptual Modeling: Past, Present and Future. In S. Robinson, R. Brooks, K. Kotiadis, & D. J. van der Zee (Eds.). *Conceptual Modeling for Discrete-Event Simulation* (pp. 473–490). Boca Raton: CRC Press.
- Vasudevan, K., & Devikar, A. (2011). Selecting simulation abstraction levels in simulation models of complex manufacturing systems. In S. Jain, R. R. Creasy, J. Himmelsbach, K. P. White, & M. Fu (Eds.). *Proceedings of the 2011 winter simulation conference* (pp. 2268–2277). Piscataway, NJ: IEEE.
- Veeger, C. P. L., Etman, L. F. P., Lefeber, E., Adan, I. J. B. F., van Herk, J., & Rooda, J. E. (2011). Predicting cycle time distributions for integrated processing workstations: An aggregate modeling approach. *IEEE Transactions on Semiconductor Manufacturing*, 24(2), 223–236.
- Virtue, A., Chausselet, T., & Kelly, J. (2011). Using simplified discrete-event models for health care applications. In S. Jain, R. R. Creasy, J. Himmelsbach, K. P. White, & M. Fu (Eds.). *Proceedings of the 2011 winter simulation conference* (pp. 1154–1165). Piscataway, NJ: IEEE.
- Völker, S., & Gmilkowsky, P. (2003). Reduced discrete-event simulation models for medium-term production scheduling. *Systems Analysis Modelling Simulation*, 43, 867–883.
- Wallace, J. C. (1987). The control and transformation metric: Towards the measurement of simulation model complexity. In A. Thesen, H. Grant, & W. David Kelton (Eds.). *Proceedings of the 1987 Winter Simulation Conference* (pp. 597–603). Piscataway, NJ: IEEE.
- Ward, S. C. (1989). Arguments for Constructively Simple Models. *Journal of the Operational Research Society*, 40(2), 141–153.
- Webster, D. B., & Padgett, M. L. (1984). Determining the Level of Detail in a Simulation Model – A Case Study. *Computers & Industrial Engineering*, 8(3/4), 215–225.
- Yavari, E., & Roeder, T. (2012). Model Enrichment: Concept, Measurement, and Application. *Journal of Simulation*, 6, 125–140.
- Yin, H. Y., & Zhou, Z. N. (1989). Simplification Techniques of Simulation Models. *Proceedings of Beijing International Conference on System Simulation and Scientific Computing* (pp. 782–786).
- Yuan, J., & Ponsignon, T. (2014). Towards a Semiconductor Supply Chain Simulation Library (SCSC-SIMLIB). In A. Tolk, S. Y. Diallo, I. O. Ryzhov, L. Yilmaz, S. Buckley, & J. A. Miller (Eds.). *Proceedings of the 2011 Winter Simulation Conference* (pp. 2522–2532). Piscataway, NJ: IEEE.
- Yücesan, E., & Schruben, L. (1998). Complexity of Simulation Models: A Graph Theoretic Approach. *INFORMS Journal on Computing*, 10(1), 94–106.
- Zeigler, B. P. (1976). *Theory of Modelling and Simulation*. Chichester: Wiley.
- Zeigler, B. P., Kim, T. G., & Praehofer, H. (2000). *Theory of Modeling and Simulation: Integrating Discrete Event and Continuous Complex Dynamic Systems* (2nd ed.). Orlando, FL: Academic Press.
- Zhou, C., Cao, Z., Liu, M., & Zhang, J. (2016). Model Reduction Method Based on Selective Clustering Ensemble Algorithm and Theory of Constraints in Semiconductor Wafer Fabrications. *2016 IEEE Conference on Automation Science and Engineering* (pp. 885–890). IEEE: Fort Worth, TX.